



**BUILDING
PLUMBING
DRAINAGE
PRODUCTS**

2052 St Catherine W.
Roof to Basement

K.H. Tremaine
This Catalog Contains

Full Data on:
"Canadian Zurn Industries Ltd"
DRAINS

INTERCEPTORS

TRAPS

WALL FIXTURE CARRIERS

WALL CLOSET FITTINGS

HYDRANTS AND STREET WASHERS

SWIMMING POOL EQUIPMENT

Everything for

Building Plumbing Drainage

ENGINEERED PROTECTION FOR

HUMAN HEALTH AND MODERN STRUCTURES



SERVICE CATALOG

No. 47-1

Revised Edition, March, 1951

Revised, July, 1951

**BUILDING • PLUMBING • DRAINAGE
PRODUCTS**

This catalog is intended as a combination price guide and catalog for quick and easy specification reference. It contains complete tables of sizes, weights and dimensions, together with engineering drawings for every item. Plumbing products not shown herein are contained in other Zurn literature, available upon request.



MEMBER OF PRODUCERS' COUNCIL, INC.

J. A. ZURN MFG. CO., PLUMBING DIVISION, ERIE, PA., U.S.A.



FIGURE NUMBER INDEX

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Z-100	4	Z-450-5	20	Z-655	38	Z-1005	54	Z-1305	66
Z-100A	4	Z-453	20	Z-660	38	Z-1010	54	Z-1310	66
Z-101	4	Z-455	21	Z-661	38	Z-1015	54	Z-1315	66
Z-102	4	Z-460	21	Z-662	38	Z-1021	54	Z-1320	66
Z-103	5	Z-470	21	Z-664	39	Z-1030	55	Z-1326	66
Z-104-1	5	Z-475	21	Z-665	39	Z-1035	55	Z-1327	66
Z-104-2	5	Z-475A	21	Z-668	39	Z-1040	55	Z-1329	67
Z-105	5	Z-476	22	Z-669	39	Z-1041	55	Z-1329-2	67
Z-106	5	Z-500	22	Z-675	40	Z-1042	55	Z-1370	67
Z-107	6	Z-505	22	Z-690	40	Z-1045	55	Z-1380	67
Z-108	6	Z-509	23	Z-691	40	Z-1090	56	Z-1381	68
Z-115	6	Z-510	23	Z-697	41	Z-1091	56	Z-1382	68
Z-118	6	Z-511	23	Z-700	41	Z-1095	56	Z-1385	68
Z-119	7	Z-511-1	24	Z-730	41	Z-1100	56	Z-1385-1	68
Z-119A	7	Z-511-2	24	Z-731	42	Z-1101	57	Z-1386	68
Z-120	7	Z-511-3	24	Z-735	42	Z-1102	57	Z-1386A	69
Z-121	8	Z-511-4	24	Z-750	42	Z-1103	57	Z-1387	69
Z-122	8	Z-515	25	Z-752	42	Z-1105	57	Z-1388	69
Z-124	8	Z-516	25	Z-754	43	Z-1106	57	Z-1389	69
Z-125	9	Z-520	25	Z-754-1	43	Z-1107	57	Z-1392	70
Z-135	9	Z-530	26	Z-755	43	Z-1108	58	Z-1395	70
Z-150	9	Z-535	26	Z-755-2	43	Z-1110	58	Z-1400	70
Z-150A	10	Z-540	27	Z-756	44	Z-1111	58	Z-1405	71
Z-151	10	Z-541	27	Z-760	44	Z-1115	58	Z-1480	71
Z-152	10	Z-541A	28	Z-798	44	Z-1120	58	Z-1481	72
Z-155	10	Z-541B	28	Z-798A	44	Z-1121	59	Z-1482	72
Z-165	11	Z-542	28	Z-798B	44	Z-1125	59	Z-1483	73
Z-170	11	Z-542A	29	Z-800	45	Z-1126	59	Z-1490	73
Z-180	11	Z-542B	29	Z-801	45	Z-1127	59	Z-1491	74
Z-185	12	Z-544	29	Z-805	45	Z-1128	59	Z-1492	74
Z-186	12	Z-544A	30	Z-807	46	Z-1130	59	Z-1493	75
Z-190	12	Z-545	30	Z-808	46	Z-1133	60	Z-1494	75
Z-195	12	Z-546	30	Z-808A	46	Z-1135	60	Z-2036	76
Z-196	13	Z-548	30	Z-809	47	Z-1138	60	Z-2046	76
Z-196-3	13	Z-549	31	Z-809A	47	Z-1140	60		
Z-197	13	Z-550	31	Z-809B	47	Z-1143	60		
Roof Drains—		Z-555	31	Z-810	47	Z-1145	61		
Spare Parts	13	Z-556	31	Z-820	48	Z-1148	61		
Z-200	14	Z-556A	32	Z-821	48	Z-1160	61	Cat. No.	Page
Z-210	14	Z-556B	32	Z-822	48	Z-1161	61	Z-5045	53
Z-220	14	Z-560	32	Z-823	48	Z-1163	61	Z-5070	53
Z-230	14	Z-565	32	Z-825	48	Z-1164	62	Z-5095	53
Z-250	15	Z-575	33	Z-826	49	Z-1167	62	Z-5144	53
Z-265	15	Z-580	33	Z-827	49	Z-1167-1	62	Z-5419A	53
Z-270	15	Z-585	34	Z-830	49	Z-1167L	62	Z-5498	53
Z-280	16	Z-589	34	Z-835	49	Z-1167L-1	62	Z-5500	52
Z-300	16	Z-590	34	Z-837	49	Z-1168	62	Z-5501	52
Z-310	16	Z-600	35	Z-838	50	Z-1168-1	62	Z-5687	52
Z-320	16	Z-605	35	Z-839	50	Z-1168L	63	Z-5687A	52
Strainer Heads	17	Z-610	35	Z-840	50	Z-1168L-1	63	Z-6165	53
Z-400	18	Z-615	35	Z-845	50	Z-1170 C.I.	63	Z-7075	53
Z-405	18	Z-616	36	Z-850	51	Z-1171 C.I.	63	Z-7081A	52
Z-405-5	19	Z-617	36	Z-855	51	Z-1170 V.G.E.	64	Z-7081B	52
Z-415	19	Z-620	36	Z-865	51	Z-1171 V.G.E.	64	Z-7268	53
Z-420	19	Z-630	36	Z-895	51	Z-1175	64	Z-7269	53
Z-430	19	Z-635	37	Z-900	52	Z-1175A	64	Z-9058-3	52
Z-440	20	Z-645	37	Z-902	52	Z-1180	65	Z-9058-4	52
Z-450	20	Z-650	37	Z-1000	53	Z-1300	65	Z-9334	52

ID 93-B957 CORN 10



ALPHABETICAL INDEX

		Cat. No.	Page			Cat. No.	Page
ADAPTERS							
Adapter, Pipe, Straight		Z-1030	55	Area, w/Bell & Bucket, & Deep Flange Strainer		Z-511-2	24
Adapter, Pipe, Straight		Z-1035	55	Area, Continuous Flow, Solids Retaining		Z-540	27
Adapter, Pipe, Straight		Z-1041	55	Area, Continuous Flow, Solids Retaining		Z-541	27
Adapter, Pipe, 45°		Z-1040	55	Area, Continuous Flow, Solids Retaining		Z-541A	28
Adapter, Pipe, 45°		Z-1042	55	Area, Continuous Flow, Solids Retaining		Z-541B	28
Adapter, Pipe, 90°		Z-1042	55	Area, Continuous Flow, Solids Retaining		Z-542	28
				Area, Continuous Flow, Solids Retaining		Z-542A	29
BASIN, CATCH-BOX, VENT				Area, Continuous Flow, Solids Retaining		Z-542B	29
Basin, Catch, Industrial, Frame & Convex Cover	Z-798B	44		Area, Continuous Flow, Solids Retaining		Z-544	29
Basin, Catch, Industrial, Frame & Grate Cover	Z-798A	44		Area, Continuous Flow, Solids Retaining		Z-544A	30
Basin, Catch, Industrial, Frame & Solid Cover	Z-798	44		Area, Deep Type, w/Deep Type Flange Strainer		Z-511	23
Box, Access	Z-1385	68		Area, w/Deflector Strainer		Z-545	30
Box, Access & Vent	Z-1386	68		Area, Double Duty		Z-530	26
Box, Hose, Short Pattern Street Washer	Z-1493	75		Area, Double Duty, Supersize, Secondary Strainer		Z-535	26
Box, Hose, Short Pattern Street Washer	Z-1494	75		Area, Plain		Z-500	22
Box, Hose, Short Pattern Street Washer	Z-1495	75		Area, Plain		Z-510	23
Box, Vent	Z-1386A	69		Area, w/Secondary Strainer, Auxiliary Inlet & Deep Flange Strainer		Z-511-4	24
Box, Vent	Z-1387	69		Area, Shallow Type, Deep Flange Strainer		Z-509	23
				Area, w/Side Outlet		Z-520	25
CAP, CLOSURE-CONNECTION, SWIMMING POOL				Area, Supersize		Z-505	22
Cap, Closure	Z-1400	70		Area, Supersize		Z-515	25
Cleanout, Access	Z-1370	67		Area, w/Trap, Integral, & Backwater Valve w/Trap, Integral Tile Inlets & Backwater Valve		Z-754	43
Cleanout, Access	Z-1380	67		Valve		Z-754-1	43
Cleanout, Areaway	Z-1327	66		w/Adjustable Head, Solids Retaining		Z-405-5	19
Cleanout, Floor Level, Heavy Duty	Z-1329	67		w/Automatic Back Pressure Device		Z-230	14
Cleanout, Perfect Seal	Z-1300	65		w/Automatic Back Pressure Device		Z-270	15
Cleanout, Perfect Seal	Z-1305	66		w/Automatic Back Pressure Device		Z-470	21
Cleanout, Perfect Seal, Floor Level	Z-1326	66		Factory Area, Extra Heavy Duty		Z-516	25
Cleanout, Traffic, Extension	Z-1329-2	67		Factory Area, w/Flashing Provision & Bottom Outlet		Z-660	38
Connection, Closet, V.E.L., Plain	Z-2036	76		Garbage Can Washing, with Mesh Basket		Z-675	40
Connection, Closet, V.E.L., w/Two 45° Tappings	Z-2046	76		Plain		Z-280	16
Connection, Swimming Pool, Vacuum Cleaning	Z-865	51		Plain		Z-548	30
				Plain		Z-555	31
DRAINS				Plain, w/Hinged Strainer		Z-560	32
DRAINS, BASEMENT-DRAINS, BOILER ROOM				Plain, w/Hinged Strainer		Z-565	32
Basement & Foundation, w/Integral Trap & Backwater Valve	Z-750	42		Plain, w/Hinged Strainer & Flashing Provision		Z-556	31
Basement & Sub-Soil, w/Backwater Valve	Z-752	42		Plain, w/Hinged Strainer & Side Outlet		Z-556A	32
Basement & Sub-Soil, Adjustable Combination	Z-755	43		Plain, w/Sediment Bucket		Z-550	31
Basement & Sub-Soil, Adjustable Combination	Z-755-2	43		Plain, w/Trap, Hinged Strainer & Flashing Provision		Z-556B	32
Basement & Sub-Soil, Adjustable Combination, w/Tile Inlet & Backwater Valve	Z-756	44		Refrigerator		Z-320	16
Boiler House, Superservice, w/Backwater Valve, Trap & Sediment Bucket	Z-760	44		w/Sand Retainer		Z-549	31
Boiler Room, Heavy Duty, Side Outlet w/Internal Trap & Sediment Bucket	Z-630	36		w/Sediment Bucket, Bottom Outlet		Z-600	35
Boiler Room, Heavy Duty, Side Outlet w/Seepage Pan & Sediment Bucket	Z-635	37		w/Sediment Bucket, Side Outlet		Z-605	35
				w/Side Outlet		Z-430	19
DRAINS, CORNICE-DRAINS, COURT				w/Solid Hinged Cover		Z-220	14
Cornice or Balcony, w/Dome Strainer 45° Outlet	Z-186	12		w/Solid Hinged Cover		Z-420	19
Cornice or Balcony, w/Dome Strainer 90° Outlet	Z-185	12		w/Supplementary Connection & Side Outlet		Z-460	21
Cornice or Parapet, w/Dome Strainer	Z-180	11		"Thoroflush"		Z-310	16
Court or Area, Heavy Duty, w/Deflector Grate, Side Outlet	Z-617	36		"Thoroflush", w/Side Outlet		Z-300	16
Court or Area, Heavy Duty, w/Cover Locking Device & Bottom Outlet	Z-620	36		w/Trap and Backwater Flap Valve		Z-730	41
				w/Trap, Internal, & Seepage Pan		Z-590	34
				w/Trap, Sediment Bucket & Backwater Valve		Z-735	42
DRAINS, FLOOR				DRAINS, FLOOR OR SHOWER			
Acid Resisting	Z-5500	52		Floor or Shower		Z-200	14
Acid Resisting	Z-5501	52		Floor or Shower		Z-210	14
Acid Resisting	Z-7081A	52		Floor or Shower		Z-405	18
Acid Resisting	Z-7081B	52		Floor or Shower		Z-415	19
Acid Resisting	Z-9058-3	52		Floor or Shower, w/Adjustable Head, Solids Retaining, & Integral Trap		Z-450-5	20
Acid Resisting	Z-9058-4	52		Floor or Shower, w/Integral Trap		Z-250	15
Acid Resisting	Z-5687	52		Floor or Shower, w/Integral Trap		Z-265	15
Acid Resisting	Z-5687A	52		Floor or Shower, w/Integral Trap		Z-450	20
Acid Resisting	Z-9334	52		Floor or Shower, w/Integral Trap		Z-453	20
Area, w/Automatic Backwater Valve	Z-511-1	24		Floor or Shower, w/Integral Trap & Floor Level Cleanout		Z-455	21
Area, w/Automatic Backwater Valve, Bell & Bucket, & Deep Flange Strainer	Z-511-3	24					



ALPHABETICAL INDEX—Continued

DRAINS—Continued

	Cat. No.	Page
DRAINS, FOOT BATH—DRAINS, RAILROAD		
Foot Bath, Antiseptic, w/Solid Screwed Top	Z-808	46
Garage, Extra Heavy Duty, w/Gas Seal Cone, Sediment Bucket, Trap & Cleanout	Z-690	40
Garage, Heavy Duty	Z-668	39
Garage, Heavy Duty, Oil & Gas	Z-691	40
Garage, Heavy Duty, w/Secondary Strainer	Z-661	38
Garage, Highway, w/Sludge Bucket, Overflow Provisions	Z-662	38
Garage, Volatile Liquids—(see "Drains—Trap-Zoo")		
Gutter	Z-589	34
Gutter, Continuous	Z-664	39
Gutter, Heavy	Z-575	33
Gutter, w/Seepage Pan	Z-585	34
Gutter, w/Seepage Pan, Heavy	Z-580	33
Industrial, Heavy Duty, w/Integral Trap		
Sediment Bucket & Side Outlet	Z-645	37
Laundry or Dairy, Side Outlet, w/Seepage Pan, Sediment Bucket	Z-655	38
Playground & School, w/Deflector Grate & Secondary Strainer	Z-546	30
Playground & School, w/Deflector Grate & Bottom Outlet, Heavy Type	Z-616	36
Prison Cell	Z-440	20
Railroad or Track, w/Multi-openings & Sediment Bucket	Z-650	37
DRAINS, ROOF		
Caulked Flashing Type	Z-106	5
Recessed Clamping Surface Type, Flat Dome	Z-108	6
Recessed Clamping Surface Type, Round Dome	Z-107	6
w/High Velocity Discharge	Z-100	4
w/High Velocity Discharge	Z-100A	4
w/Hinged Dome	Z-118	6
for Inclined Roof	Z-102	4
w/Integral Expansion Joint	Z-120	7
w/Long Outlet	Z-104-1	5
w/Standard Length Outlet	Z-104-2	5
Parapet Scupper, w/Downspout Adapter	Z-119	7
Parapet Scupper, 45° Outlet	Z-119A	7
w/Seepage Pan	Z-101	4
w/Side Outlet	Z-115	6
Steel Deck	Z-122	8
Summer-Winter Type	Z-124	8
w/Tile Frame	Z-105	5
w/Twelve Inch Pan	Z-121	8
Water Level	Z-103	5
DRAINS, ROOF OR GUTTER		
Roof or Gutter	Z-125	9
Roof or Gutter, w/Side Outlet	Z-135	9
DRAINS, ROOF OR PROMENADE DECK		
Roof or Promenade Deck	Z-150	9
Roof or Promenade Deck	Z-150A	10
Roof or Promenade Deck	Z-151	10
Roof or Promenade Deck	Z-152	10
Roof or Promenade Deck	Z-165	11
Roof or Promenade Deck, w/Side Outlet	Z-155	10
Roof or Promenade Deck, w/Side Outlet	Z-170	11
DRAINS, SERVICE STATION—DRAINS, SWIMMING POOL		
Service Station, Heavy Type, Bottom Outlet	Z-610	35
Service Station, Heavy Type, Side Outlet	Z-615	35
Shower, Angle	Z-400	18
Steel, Traffic	Z-509	23
Steel, Traffic	Z-511	23
Steel, Traffic	Z-660	38
Sub-Surface	Z-669	39
Sub-Surface, w/Backwater Valve & Integral Trap	Z-700	41
Swimming Pool, w/Non-Slip Top	Z-807	46
Swimming Pool, Discharge	Z-800	45

	Cat. No.	Page
Swimming Pool, Discharge	Z-805	45
Swimming Pool, Discharge, Angle Type		
Reversible	Z-810	47
Swimming Pool, Gutter	Z-820	48
Swimming Pool, Gutter	Z-821	48
Swimming Pool, Gutter	Z-822	48
Swimming Pool, Gutter	Z-823	48
Swimming Pool, Gutter	Z-825	48
Swimming Pool, Gutter	Z-826	49
Swimming Pool, Gutter	Z-827	49
Swimming Pool, Gutter	Z-830	49
Swimming Pool, Lane & Overflow Connection	Z-809A	47
Swimming Pool, Main Outlet	Z-801	45
Swimming Pool or Pit	Z-809	47

DRAINS, TRAP—DRAINS, ZOO

w/Trap, Integral Combined, w/Deep Seal & Backwater Valve	Z-731	42
Trench, Ramp, Deck & Pavement	Z-665	39
Urinal or Shower	Z-475	21
Urinal or Shower	Z-475A	21
Urinal, w/Supporting Flange	Z-476	22
Volatile Liquids Intercepting	Z-697	41
Zoo or Animal Den, w/Flushing Connection	Z-808A	46

FITTINGS

Fitting, Swimming Pool, Recirculating	Z-855	51
Fitting, Vent Flashing	Z-196-3	13

GREASEPTORS

Greaseptor, Regular, C.I.	Z-1170	63
Greaseptor, De Luxe, C.I.	Z-1171	63
Greaseptor, De Luxe, V.G.E.	Z-1171	64

HEADS, STRAINER

Spray, Children's Playpool	Z-838	50
Strainer Heads for Floor or Shower Drains	Type	17, 18
Beehive Dome	G	
Rectangular Full Slotted	J	
Round, Anchoring Lugs, Slotted, Standard	E	
Round, w/Bucket	M	
Round, Adjustable Sleeve, Slotted, Standard	F	
Round, Full Slotted, Hinged, Standard	C	
Round, Square, Perforated, Standard	B	
Round, Slotted, Standard	A	
Round, Solid Hinged Top, Recessed, Standard	D	
Square, Anchoring Lugs, Slotted, Standard	I	
Square, Slotted, Standard	H	
90° Outlet, Female I.P.S.	L	
90° Outlet, Male I.P.S.	K	

HYDRANTS

Compression Valve Type, Dry Pipe, Exposed		
Casing	Z-1482	72
Compression Valve Type, Dry Pipe, Full		
Covered Casing	Z-1480	71
Compression Valve Type, Dry Pipe, Semi-		
Covered Casing	Z-1481	72
Compression Valve Type, Heavy Duty	Z-1483	73
Wall	Z-1395	70

INCREASERS—INTERCEPTORS

Increaser	Z-1045	55
Inlet, Fresh Air	Z-1388	69
Inlet, Fresh Air	Z-1389	69
Inlet, Flushing, Swimming Pool	Z-840	50
Inlet, Flushing, Swimming Pool	Z-845	50
Inlet, Flushing, Swimming Pool	Z-850	51
Inlet, Spray, Chlorine, Swimming Pool	Z-895	51



ALPHABETICAL INDEX—Continued

	Cat. No.	Page
INCREASERS—INTERCEPTORS—Continued		
Inlet, Spray, Swimming Pool	Z-835	49
Inlet, Spray, Swimming Pool	Z-839	50
Inlet, Spray, Wading Pool	Z-837	49
Interceptor, Grease—(see "Greaseptor")		
Interceptor, Hair, Swimming Pool	Z-900	52
Interceptor, Hair, Swimming Pool	Z-902	52
Interceptor, Hair, Side Outlet	Z-1175	64
Interceptor, Hair, Top Swing Outlet	Z-1175-A	64
Interceptor, Solids	Z-1180	65

JOINTS

Joint, Expansion	Z-190	12
Joint, Expansion, Horizontal	Z-197	13
Joint, Insertable, Acid Resisting	Z-5045	53
Joint, Insertable, Acid Resisting	Z-5070	53
Joint, Insertable, Acid Resisting	Z-5095	53
Joint, Insertable, Acid Resisting	Z-5144	53

PLATES—PRIMERS

Plate & Screw, Floor, Bronze	Z-1310	66
Plug, Cleanout, Acid Resisting		52
Plug, Deck, Non-Slip	Z-1381	68
Plug, Deck, Non-Slip	Z-1382	68
Preventer, Siphon	Z-1405	71
Primer, Automatic	Z-1021	54

SLEEVES—STRAINERS

Sleeve, Flashing, Vent Stack	Z-195	12
Sleeve, Flashing, Vent Stack	Z-196	13
Strainer Heads—(see "Heads, Strainer")		
Strainer, Shower, Angle	Z-404	18

TEES

Cleanout, Perfect Seal	Z-1315	66
Cleanout, Perfect Seal	Z-1320	66
Flow Control		63, 64

TRAPS

Acid Resisting, Drum	Z-5498	53
Acid Resisting, Drum	Z-6165	53
Acid Resisting, Long Sink	Z-5419A	53
Acid Resisting, Long Sink	Z-7075	53
Acid Resisting, Non-Siphon "P"	Z-7268	53
Acid Resisting, Non-Siphon "P"	Z-7269	53
Bath, Brass, Adjustable, I.P.	Z-1167	62
Bath, Brass, Adjustable, I.P. w/ Shield	Z-1167-1	62
Bath, Brass, Adjustable, I.P. w/ Tubing Inlet	Z-1168	62
Bath, Brass, Adjustable, I.P. w/ Tubing Inlet & Shield	Z-1168-1	62
Bath, Brass, Adjustable, Lead Pipe	Z-1167-L	62
Bath, Brass, Adjustable, Lead Pipe w/ Shield	Z-1167-L-1	62
Bath, Brass, Adjustable, Lead Pipe w/ Tubing Inlet	Z-1168-L	63
Bath, Brass, Adjustable, Lead Pipe w/ Tubing Inlet & Shield	Z-1168-L-1	63

Bath, Collective Dwelling, Universal Adjustment	Z-1125	59
Bath, Collective Dwelling, Universal Adjustment	Z-1126	59
Bath, Collective Dwelling, Universal Adjustment	Z-1127	59
Bath, Collective Dwelling, Universal Adjustment	Z-1128	59
Bath, Dwelling House, Self-Cleaning	Z-1105	57
Bath, Dwelling House, Self-Cleaning	Z-1106	57
Bath, Dwelling House, Self-Cleaning	Z-1107	57
Bath, Dwelling House, Self-Cleaning	Z-1108	58
Bath, Federal Housing, Adjustable, Self-Cleaning	Z-1110	58
Bath, Federal Housing, Adjustable, Self-Cleaning	Z-1111	58
Bath, Federal Housing, Adjustable, Self-Cleaning	Z-1115	58
Bath, Hospital, Adjustable, Non-Siphoning & Self-Cleaning	Z-1140	60
Bath, Hospital, Adjustable, Non-Siphoning & Self-Cleaning	Z-1143	60
Bath, Hospital, Adjustable, Non-Siphoning & Self-Cleaning	Z-1145	61
Bath, Hospital, Adjustable, Non-Siphoning & Self-Cleaning	Z-1148	61
Bath, Hospital, Non-Siphoning & Self-Cleaning	Z-1130	59
Bath, Hospital, Non-Siphoning & Self-Cleaning	Z-1133	60
Bath, Hospital, Non-Siphoning & Self-Cleaning	Z-1135	60
Bath, Hospital, Non-Siphoning & Self-Cleaning	Z-1138	60
Bath, Residence & Apartment House, Self-Cleaning	Z-1100	56
Bath, Residence & Apartment House, Self-Cleaning	Z-1101	57
Bath, Residence & Apartment House, Self-Cleaning	Z-1102	57
Bath, Residence & Apartment House, Self-Cleaning	Z-1103	57
Combined with Backwater Valve & Cleanout	Z-1015	54
Deep Seal, "P"	Z-1000	53
Deep Seal, "P", w/ Floor Level Cleanout	Z-1005	54
Hotel Tub & Shower, Self-Cleaning	Z-1120	58
Hotel Tub & Shower, Self-Cleaning	Z-1121	59
Lavatory, Resealing	Z-1160	61
Lavatory, Resealing	Z-1161	61
Lavatory, Resealing	Z-1163	61
Lavatory, Resealing	Z-1164	62
Shallow Seal "P"	Z-1010	54

VALVES

Valve, Backwater	Z-1090	56
Valve, Backwater, Open Type	Z-1091	56
Valve, Backwater, w/ Access Extension Provision	Z-1095	56
Valve, Backwater, Acid Resisting		53
Valve and Control Box, Park Sprinkling	Z-1392	70

WASHERS

Street, Compression Valve Type, Dry Pipe, Heavy Duty	Z-1492	74
Street, Compression Valve Type, Dry Pipe, Round Head	Z-1490	73
Street, Compression Valve Type, Dry Pipe, Square Head	Z-1491	74

MISCELLANEOUS

Marker, Lane, Swimming Pool	Z-809-B	47
-----------------------------	---------	----

INDEX TO SECTIONS

Section	Page
Roof Drains	4-13
Floor and Shower Drains	14-22
Industrial Floor and Area Drains	22-34
Special Purpose Drains	35-44
Swimming Pool Drains and Accessories	45-51
Acid Resisting Products	52-53

Section	Page
Traps and Valves	53-63
Interceptors	63-65
Cleanouts	65-67
Miscellaneous	68-69
Hydrants	70-75
Closet Connections	76

ROOF DRAINS . . . Pages 4 to 13

FIG. Z-100 ROOF DRAIN, High Velocity Discharge


Pipe Size		Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
A	E				
2-3-4"	5 1/4"	\$24.00	\$40.20	\$ 92.20	49
5"	5 1/4"	29.30	48.60	109.10	50
6"	5 1/4"	32.30	54.90	133.40	51
8"	5 1/4"	45.00	74.10	192.50	52

Caulk outlet available, see Z-100A.

Extra large, removable, non-clogging, mushroom dome strainer. Clamping collar of vise construction assures tight joint.

Open Area Ratio of Dome Orifices to Outlet

2"—35:1	4"—9:1	6"—4:1
3"—16:1	5"—6:1	8"—2:1



I.P.S. Outlet



Z-100

Furnished With or Without Anchorage Lugs

FIG. Z-100A ROOF DRAIN, High Velocity Discharge


Pipe Size		Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
A	E				
2-3-4"	6 3/4"	\$24.00	\$40.20	\$ 92.20	49
5"	6 3/4"	29.30	48.60	109.10	50
6"	6 3/4"	32.30	54.90	133.40	51
8"	7 3/8"	45.00	74.10	192.50	52

I. P. S. outlet available, see Z-100.

Extra large, removable, non-clogging, mushroom dome strainer.

Open Area Ratio of Dome Orifices to Outlet

2"—35:1	4"—9:1	6"—4:1
3"—16:1	5"—6:1	8"—2:1



Caulk Outlet



Z-100A

Furnished With or Without Anchorage Lugs

FIG. Z-101 ROOF DRAIN, With Seepage Pan, High Velocity Discharge


Pipe Size		Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
A	E				
2-3-4"	5 1/4"	\$36.00	\$60.20	\$138.20	55
5"	4 7/8"	41.30	68.40	153.60	56
6"	5"	44.30	74.70	174.70	57
8"	5 1/4"	57.00	94.50	207.40	66

Caulk outlet available; "E" dimension approximately 1 1/2" longer.

Extra large, removable, non-clogging, mushroom dome strainer.

Open Area Ratio of Dome Orifices to Outlet

2"—35:1	4"—9:1	6"—4:1
3"—16:1	5"—6:1	8"—2:1



Z-101—I.P.S. Outlet


FIG. Z-102 ROOF DRAIN FOR INCLINED ROOF

Pipe Size		Cast Iron Coated (DC)	Galv. (G)	With Bronze Dome Coated (CB)	Galv. (GB)	All Bronze (BR)
A	E					
2-3-4"	3 7/8"	\$31.50	\$49.40	\$42.80	\$60.20	\$127.40
5"	3 7/8"	39.00	60.30	51.00	71.90	152.10
6"	3 7/8"	40.20	68.00	57.40	81.90	187.00


Approx. Wt. Lbs. 2"-3"-4"—43, 5"—44, 6"—45.

Caulk outlet available; "E" dimension approximately 1 1/2" longer.


Standard pitch—22°30'(5" per ft.). Available at different angles according to requirements.



I.P.S. Outlet



Z-102



Z-103

I.P.S. Outlet


Furnished With or Without Anchorage Lugs

ROOF DRAIN **FIG. Z-103**
With Adjustable Water Level Regulator, For Water-Insulated Roof

Pipe Size	A	E	Coated (DC)	Galv. (G)	All Bronze (Br)	Approx. Wt. Lbs.
2"		6 1/4"	\$36.00	\$57.60	\$138.20	61
3"		6 3/8"	39.00	63.00	149.80	63
4"		6 3/8"	42.00	68.40	161.30	64

Caulk outlet available; "E" dimension approximately 1 1/2" longer.

3" water level shown; can be made to specification. Extra large, removable, non-clogging, mushroom dome strainer.



Z-104-1

Caulk Outlet

Furnished With or Without Anchorage Lugs

ROOF DRAIN With Long Outlet **FIG. Z-104-1**


Pipe Size	Cast Iron		With Bronze Dome		All Bronze (BR)	Approx. Wt. Lbs.
	Coated (DC)	Galv. (G)	Coated (CB)	Galv. (GB)		
4"	\$24.00	\$40.20	\$35.30	\$51.20	\$ 92.20	66
5"	29.30	48.60	41.30	60.20	109.10	68
6"	32.30	54.90	46.50	68.70	133.40	70

I. P. S. outlet available.

ROOF DRAIN WITH STANDARD LENGTH OUTLET **FIG. Z-104-2**

Pipe Size A	Top of Pan to Outlet
4", 5", 6"	6 5/8"

Fig. Z-104-1 Prices Apply



Z-105


I.P.S. Outlet

Furnished With or Without Anchorage Lugs

ROOF DRAIN With Tile Frame **FIG. Z-105**

Pipe Size	A	E	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
2-3-4"		5 1/4"	\$33.00	\$52.90	\$106.60	60
5"		5 1/4"	38.30	61.20	123.50	61
6"		5 1/4"	41.30	67.50	147.80	62
8"		5 1/2"	54.00	86.80	206.90	63

Caulk outlet available; "E" dimension approximately 1 1/2" longer.



Z-106

Caulk Outlet

ROOF DRAIN—CAULKED FLASHING TYPE **FIG. Z-106**

Pipe Size	Cast Iron		With Bronze Dome		All Bronze (BR)	
	Coated (DC)	Galv. (G)	Coated (CB)	Galv. (GB)		
3-4"	\$32.60	\$51.10	\$43.50	\$63.50	\$ 94.10	
5-6"	35.00	54.00	47.00	66.60	99.80	
8"	On request	60.30	51.50	72.00	104.00	

Approx. Wt. Lbs. 3"-4"—56, 5"-6"—58, 8"—60.



I. P. S. outlet available.

Metal flashing can be bent over and caulked into flashing seat.

FIG. Z-107 ROOF DRAIN—Recessed Clamping Surface Type

Pipe Size A	Cast Iron		With Bronze Dome		All Bronze (BR)	Approx. Wt. Lbs.
	Coated (DC)	Galv. (G)	Coated (CB)	Galv. (GB)		
2-3-4"	\$18.50	\$30.20	\$24.40	\$36.90	\$53.80	37

Provides firm anchorage for soft flashing when formed into the recess.



Z-107



Furnished With or Without Anchorage Lugs

FIG. Z-108 ROOF DRAIN—Recessed Clamping Surface Type

Pipe Size A	Cast Iron		With Bronze Dome		All Bronze (BR)	Approx. Wt. Lbs.
	Coated (DC)	Galv. (G)	Coated (CB)	Galv. (GB)		
5"	\$29.30	\$48.60	\$41.30	\$60.20	\$109.10	53
6"	32.30	54.90	46.50	68.70	133.40	54
8"	45.00	74.10	77.30	107.00	192.50	55

Caulk outlet available; outlet approximately 1 1/2" longer.

For same service as Z-107 above.



Z-108

I.P.S. Outlet

Furnished With or Without Anchorage Lugs

FIG. Z-115 ROOF DRAIN With Side Outlet


Pipe Size A	E	K	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
2"	6 1/8"	2 3/8"	\$31.50	\$52.80	\$127.40	68
3"	5 5/8"	2 7/8"	31.50	52.80	127.40	69
4"	5 1/16"	3 7/16"	31.50	52.80	127.40	70
5"	4 11/16"	3 4/16"	39.00	65.70	152.10	71
6"	4 5/16"	4 3/16"	43.20	74.50	187.00	72

Caulk Outlet Available.

Extra large, removable, non-clogging, mushroom dome strainer.

Open Area Ratio of Dome Orifices to Outlet

2"—35:1 3"—16:1 4"—9:1 5"—6:1 6"—4:1



Z-115

I. P. S. Outlet

FIG. Z-118 ROOF DRAIN With Hinged Dome


Pipe Size A	E	Coated		Galv.		All Bronze (BR)	Approx. Wt. Lbs.
		Iron Dome	Bronze Dome	Iron Dome	Bronze Dome		
2"	5 1/4"	\$42.00	\$54.00	\$61.20	\$75.60	\$112.00	52
3"	5 1/4"	42.00	54.00	61.20	75.60	112.00	53
4"	5 1/4"	42.00	54.00	61.20	75.60	112.00	54
5"	5 1/4"	57.00	72.00	82.80	100.80	130.70	55
6"	5 1/4"	72.00	90.00	94.40	126.00	183.80	56
Hinged Dome		12.00		25.20		33.60	
Clamping Collar and Retainer		7.50		12.60		19.20	

Caulk outlet available; "E" dimension approximately 1 1/2" longer.

Extra large, hinged, non-clogging, mushroom dome strainer. Hinged dome is easily cleaned; removable if necessary.


Open Area Ratio of Dome Orifices to Outlet

2"—35:1 3"—16:1 4"—9:1 5"—6:1 6"—4:1




Z-118 I.P.S. Outlet

Furnished With or Without Anchorage Lugs



Z-119



45° Oblique Type Strainer

I.P.S. Outlet


**PARAPET SCUPPER ROOF DRAIN**
With Downspout Adaptor For Sheet Metal Connection

FIG. Z-119

Pipe Size A	Coated (DC)		Galv. (G)		With Bronze Strainer	
	Coated (DC)	Galv. (G)	Coated (CB)	Galv. (GB)	All Bronze (BR)	
2-3-4"	\$29.10	\$50.30	\$40.90	\$61.10	\$97.20	
4-5-6"	37.00	60.20	55.00	78.60	104.70	

Price does not include Downspout Adapter or Nipple.
Add for Downspout Adapter.


2-3-4"	11.30	19.80			43.20
4-5-6"	14.30	24.30			50.30

Pipe Size A	B	B'	C	E	E'	G	H	Approx. Wt. Lbs.
2"	6 1/4"	6 1/4"	7 1/2"	2 3/4"	- 3/8"	6 5/8"	7"	20
3"	6 1/4"	6 1/4"	7 1/2"	2 3/4"	+ 1/8"	6 1/8"	5 13/16"	20
4"	6 1/4"	6 1/4"	7 1/2"	2 3/4"	+ 5/8"	5 5/8"	4 5/16"	20
4"	8 1/2"	8 1/2"	12 3/4"	3 5/8"	+ 1/8"	8 3/8"	7 3/4"	52
5"	8 1/2"	8 1/2"	12 3/4"	3 5/8"	+ 1/2"	8"	6 27/32"	52
6"	8 1/2"	8 1/2"	12 3/4"	3 5/8"	+ 1 1/8"	7 3/8"	5 11/16"	52


Sheet metal size for 2", 3" and 4" drain—3" x 5"

Sheet metal size for 4", 5" and 6" drain—4" x 6"

Wall thickness determines nipple length. Provides wall outlet roof drainage to exterior downspout conductors. 90° angle type strainer available—see Z-119A below.



Z-119A



90° Angle Type Strainer

I.P.S. Outlet


**PARAPET SCUPPER ROOF DRAIN With 45° Outlet**

FIG. Z-119A

Pipe Size A	Coated (DC)		Galv. (G)		With Bronze Strainer	
	Coated (DC)	Galv. (G)	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
2-3-4"	\$29.10	\$50.30	\$40.90	\$61.10	\$ 97.20	20
4-5-6"	37.00	60.20	55.00	78.60	104.70	52

Price does not include Downspout Adapter or Nipple.


Pipe Size A	E	E'
2"	1"	1 7/8"
3"	1 1/2"	1 3/4"
4"	1 3/4"	1 1/2"
4-5-6"	On request.	

Wall thickness determines nipple length. Provides wall outlet roof drainage to exterior downspout conductors. 45° oblique type strainer available; 90° angle type regularly furnished.



Z-120

Furnished With or Without Anchorage Lugs



I.P.S. Outlet

ROOF DRAIN
With Internal Expansion Joint; High Velocity Drainage

FIG. Z-120

Pipe Size A	E		Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
	Min.	Max.				
2"	8 1/4"	10 1/4"	\$36.00	\$ 56.60	\$118.60	55
3"	8 1/4"	10 1/4"	39.00	61.10	125.80	57
4"	8 1/4"	10 1/4"	42.00	65.60	130.60	60
5"	8 1/4"	10 1/4"	50.30	78.30	160.30	63
6"	8 1/4"	10 1/4"	56.30	89.10	191.00	65
8"	8 1/4"	10 1/4"	79.50	124.50	262.10	75

Caulk outlet available.

Integral expansion joint provides adjustable installation and insures flexible expansion on leader lines to compensate for structural or temperature variation. Extra large, removable, non-clogging, mushroom dome strainer.


Open Area Ratio of Dome Orifices to Outlet		
2"—35:1	4"—9:1	6"—4:1
3"—16:1	5"—6:1	8"—2:1

FIG. Z-121 ROOF DRAIN


Pipe Size		With Bronze Strainer					Approx. Wt. Lbs.
A	E	Coated (DC)	Galv. (G)	Coated (DC)	Galv. (G)	All Bronze (BR)	
2-3-4"	5"	\$18.80	\$29.70	\$27.00	\$38.80	\$ 64.00	22
5"	5"	22.10	33.80	31.50	44.20	74.60	23
6"	5"	25.10	37.40	39.00	56.50	104.00	24

Caulk outlet available; "E" dimension approximately 1½" longer.

For medium and small roof areas.



I.P.S. Outlet



Z-121


Furnished With or Without Anchorage Lugs

FIG. Z-122 ROOF DRAIN With Anchorage Collar For Steel Deck


Pipe Size		With Bronze Strainer					Approx. Wt. Lbs.
A	E	Coated (DC)	Galv. (G)	Coated (DC)	Galv. (G)	All Bronze (BR)	
2-3-4"	1½"	\$16.50	\$27.00	\$24.80	\$36.10	\$57.60	21

Caulk outlet available; outlet approximately 1½" longer.

For prefabricated steel roof decks. Outlet will clear vertical webs on 6" centers. Eliminates cutting of large holes through decking and webs with resultant weakening of roof.



I.P.S. Outlet



Z-122

FIG. Z-124 ROOF DRAIN, Summer-Winter Type


Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
2-3-4"	\$18.00	\$28.80	\$53.80	20

Add for water level


dome combination 6.00 9.00 14.40

Caulk outlet available; outlet approximately 1½" longer.


Provides efficient residential drainage with regular dome strainer—use of water level dome provides economical heat resistant facility.



I.P.S. Outlet



Water Tight Interchangeable Dome for Water Level on Roof




Z-124


Furnished With or Without Anchorage Lugs



Z-125



Caulk Outlet



I.P.S. Outlet

Furnished With or Without Anchorage Lugs

ROOF OR GUTTER DRAIN


FIG. Z-125

Pipe Size A	E (I.P.S.)	E (I.C.)	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
2-3-4"	4 1/16"	5 5/8"	\$13.50	\$19.80	\$36.00	17
5"	4 3/16"	5 5/8"	15.00	21.60	40.00	18

For narrow valleys and gutters, decks and other small roof areas. Extra large, removable, non-clogging, mushroom dome strainer.

Open Area Ratio of Dome Orifices to Outlet

2"—11:1	4"—3:1
3"—5:1	5"—2:1



Z-135 I.P.S. Outlet

Pipe Size A	K
2"	1 7/16"
3"	2"
4"	2 9/16"
5"	

Caulk outlet available.

For decks, parapets and other small roof areas. Extra large removable, non-clogging, mushroom dome strainer.


ROOF OR GUTTER DRAIN With Side Outlet

FIG. Z-135


Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
\$18.00	\$25.20	\$48.00	31
18.00	25.20	48.00	32
18.00	25.20	48.00	33
20.30	27.90	54.00	38

Open Area Ratio of Dome Orifices to Outlet

2"—11:1	3"—5:1	4"—3:1	5"—2:1
---------	--------	--------	--------



Z-150



I.P.S. Outlet

For flat roof or promenade deck areas.

Furnished With or Without Anchorage Lugs

ROOF OR PROMENADE DECK DRAIN

FIG. Z-150

Pipe Size A	Coated (DC)	Galv. (G)	All Bronze (BR)	W/Bronze Frame and Strainer Coated (CB)	Galv. (GB)	Approx. Wt. Lbs.
2-3-4"	\$30.00	\$49.80	\$109.40	\$52.20	\$ 72.20	57
5"	36.80	58.70	117.10	58.50	82.10	58
6"	40.50	66.00	140.20	68.30	96.30	59
8"	54.00	84.60	159.40	82.50	116.10	60

Add to (CB) or (GB) Lists for

Pipe Size	C. P.	W. M.
2-3-4"	\$11.20	\$14.40
5"	12.00	16.00
6-8"	12.80	17.60



Caulk outlet available; "E" dimension approximately 1 1/2" longer.

Pipe Size A	B	C	D	E	F
2-3-4"	14x14"	16"	2"	5 1/4"	11 1/2"
5"	14x14"	16"	2"	5 1/4"	11 1/2"
6"	14x14"	16"	2"	5 1/4"	11 1/2"
8"	14x14"	16"	2"	5 1/2"	11 1/2"

FIG. Z-150A ROOF OR DECK DRAIN

Pipe Size			W/Bronze Frame and Strainer				
A	D	E	Coated (DC)	Galv. (G)	All Bronze (BR)	Coated (CB)	Galv. (GB)
2-3-4"	2"	5 1/4"	\$42.00	\$69.60	\$154.20	\$64.20	\$ 92.00
5"	2"	5 1/4"	48.80	78.50	161.90	70.50	101.90
6"	2"	5 1/4"	52.50	85.80	185.00	80.30	116.10
8"	2"	5 1/4"	66.00	104.40	204.20	94.50	135.90
			Add to (CB) or (GB) Lists for				
Pipe Size			C. P.		W. M.		
2-3-4"			\$11.20		\$14.40		
5"			12.00		16.00		
6-8"			12.80		17.60		

Caulk outlet available; "E" dimension approximately 1 1/2" longer.
Approx. Wt. Lbs. 2"-3"-4"—60, 5"—61, 6"—62, 8"—63.





Z-150A

FIG. Z-151 ROOF OR PROMENADE DECK DRAIN

Pipe Size			W/Bronze Frame and Strainer				
A			Coated (DC)	Galv. (G)	Coated (CB)	Galv. (GB)	All Bronze (BR)
2-3-4"			\$24.00	\$38.60	\$39.90	\$54.60	\$ 76.00
5"			28.10	43.70	44.70	69.50	83.40
6"			34.40	54.90	56.50	82.80	104.90
Pipe Size			B	C	D	E	F
2-3-4"			11x11"	12"	2"	5"	9 1/4"
5"			11x11"	12"	2"	4 3/4"	9 1/4"
6"			11x11"	12"	2"	5"	9 1/4"
Pipe Size			Approx. Wt. Lbs.				
2-3-4"			34				
5"			35				
6"			36				

Caulk outlet available; "E" dimension approximately 1 1/2" longer.



Z-151

I.P.S. Outlet



Furnished With or Without Anchorage Lugs

FIG. Z-152 ROOF OR PROMENADE DECK DRAIN

Pipe Size			W/Bronze Frame and Strainer				
A			Coated (DC)	Galv. (G)	All Bronze (BR)	Coated (CB)	Galv. (GB)
2"			\$42.00	\$66.00	\$135.80	\$64.20	\$ 88.40
3"			45.00	70.70	136.60	67.20	92.90
4"			48.00	75.00	141.40	70.20	97.40
5"			57.80	87.80	169.90	79.50	111.80
6"			64.50	100.20	202.60	92.30	130.50
Pipe Size			B	C	D	E	F
2"			14x14"	16"	2"	8 1/4"—10 1/4"	11 1/2"
3"			14x14"	16"	2"	8 1/4"—10 1/4"	11 1/2"
4"			14x14"	16"	2"	8 1/4"—10 1/4"	11 1/2"
5"			14x14"	16"	2"	8 1/4"—10 1/4"	11 1/2"
6"			14x14"	16"	2"	8 1/4"—10 1/4"	11 1/2"

Caulk outlet available.

For any type roof construction or composition requiring expansion provision in minimum space.



Z-152


I.P.S. Outlet

Furnished With or Without Anchorage Lugs

FIG. Z-155 ROOF OR PROMENADE DECK DRAIN With Side Outlet


Pipe Size			W/Bronze Frame and Strainer				
A			Coated (DC)	Galv. (G)	All Bronze (BR)	Coated (CB)	Galv. (GB)
2"			\$37.50	\$62.40	\$144.60	\$59.70	\$ 85.60
3"			37.50	62.40	144.60	59.70	85.60
4"			37.50	62.40	144.60	59.70	85.60
5"			46.50	75.80	158.10	68.20	99.00
6"			50.40	85.60	193.80	79.20	158.30
Pipe Size			B	C	D	E	F
2"			14x14"	16"	2"	6 3/4"	5 5/8"
3"			14x14"	16"	2"	6"	5 5/8"
4"			14x14"	16"	2"	5 5/8"	5 5/8"
5"			14x14"	16"	2"	5 1/4"	5 5/8"
6"			14x14"	16"	2"	4 1/2"	5 5/8"
Pipe Size			G				
2"			7 1/4"				
3"			7 1/4"				
4"			7 1/4"				
5"			7 1/4"				
6"			7 1/4"				

Caulk outlet available.




Z-155

I.P.S. Outlet



Z-165



I.P.S. Outlet

Furnished With or Without Anchorage Lugs

ROOF OR PROMENADE DECK DRAIN


FIG. Z-165

Pipe Size	W/Bronze Frame and Strainer					
	Coated (DC)	Galv. (G)	All Bronze (BR)	Coated (CB)	Galv. (GB)	Approx. Wt. Lbs.
2-3-4"	\$18.00	\$27.00	\$45.60	\$27.80	\$37.20	16
5"	19.50	28.80	49.60	29.60	39.30	17

Pipe Size	A	B	C	D	E*	F
2"		8x8"	8"	1 3/4"	4 1/16"	7"
3"		8x8"	8"	1 3/4"	4 1/16"	7"
4"		8x8"	8"	1 3/4"	4 1/16"	7"
5"		8x8"	8"	1 3/4"	4 3/16"	7"

Caulk outlet available; "E" dimension approximately 1 1/2" longer.

For small flat roof areas.




Z-170—I.P.S. Outlet


Pipe Size							and Strainer					
A	B	C	D	E	F	G	Coated (DC)	Galv. (G)	All Bronze (BR)	Coated (CB)	Galv. (GB)	Approx. Wt. Lbs.
2"	8"	8"	1 3/4"	3 9/16"	3 1/2"	5 1/4"	\$22.50	\$32.40	\$57.60	\$32.30	\$42.60	26
3"	8"	8"	1 3/4"	3 9/16"	3 1/2"	5 1/4"	22.50	32.40	57.60	32.30	42.60	27
4"	8"	8"	1 3/4"	3 9/16"	3 1/2"	5 1/4"	22.50	32.40	57.60	32.30	42.60	28
5"	8"	8"	1 3/4"	3 9/16"	3 1/2"	5 1/4"	27.00	39.60	69.60	31.50	43.20	32

Caulk outlet available.

For small flat roof areas requiring side outlet.



Z-180



I.P.S. Outlet

Furnished With or Without Anchorage Lugs

PARAPET OR CORNICE DRAIN With Dome Strainer, FIG. Z-180

Pipe Size	W/Bronze Collar and Strainer						Approx. Wt. Lbs.
	Coated (DC)	Galv. (G)	All Bronze (BR)	Coated (DC)	Galv. (G)	All Bronze (BR)	
2"	3 3/8"	4 1/2"	1 5/8"	8"	\$14.90	\$20.70	10
3"	3 3/8"	4 1/2"	1 5/8"	8"	16.60	22.80	14
2"	3 3/8"	4 1/2"	1 3/8"	4"	10.00	13.70	8
3"	3 3/8"	4 1/2"	1 5/8"	4"	11.80	15.80	12
2"	3 3/8"	4 1/2"	1 5/8"	2"	7.60	10.20	4
3"	3 3/8"	4 1/2"	1 5/8"	2"	9.30	12.30	6

Pipe Size	Add for C. P.	W. M.
2-3"	\$2.80	\$3.50



Caulk Outlet and flat strainer types available. Specify "E" dimension when ordering.

A practical drain for close quarters and out-of-the-way locations.

FIGS. Z-185 & Z-186 CORNICE OR BALCONY DRAIN With Dome Strainer


Pipe Size	W/Bronze Collar and Strainer Coated (DC)	Galv. (G)	All Bronze (BR)
2"	\$10.50	\$13.30	\$14.00
3"	14.00	18.90	22.75
4"	17.50	25.20	28.00

Pipe Size	Add for C. P.	W. M.
2"	\$2.80	\$3.50
3"	4.10	6.20
4"	4.10	6.20



Pipe Size	A	B	C	D	E	F	Approx. Wt. Lbs.
2"	2"	3 3/8"	4 1/2"	1 5/8"	2 1/2"	1 1/2"	5
3"	3"	4 3/4"	6 1/16"	2"	3"	1 1/2"	7
4"	4"	4 3/4"	6 1/16"	2"	3"	5/8"	10

Pipe Size	A	B	C	D	E*	Approx. Wt. Lbs.
2"	2"	3 3/8"	4 1/2"	1 5/8"	4"	5
3"	3"	4 3/4"	6 1/16"	2"	5 1/16"	7
4"	4"	4 3/4"	6 1/16"	2"	5 3/8"	10



Caulk outlet and flat strainer types available

For drainage control on small roof areas.



FIG. Z-190 EXPANSION JOINT

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
2"	\$12.00	\$16.20	\$ 26.40	7
3"	15.00	20.70	33.60	10
4"	18.00	25.20	38.40	14
5"	21.00	29.70	52.80	17
6"	24.00	34.20	62.40	21
8"	34.50	50.40	100.80	32

Pipe Size	A'	C	E	F	J Min.	J Max.
2"	2"	2 11/16"	6"	3 5/8"	7 3/4"	10 3/4"
3"	3"	3 1/4"	6"	4 5/8"	7 3/4"	10 3/4"
4"	4"	3 3/4"	5 3/4"	5 1/2"	7 1/2"	10 1/2"
5"	5"	4 1/4"	6"	6 1/2"	7 7/8"	10 7/8"
6"	6"	5"	6"	7 1/8"	7 7/8"	10 7/8"
8"	8"	5 15/16"	6"	9 7/8"	7 7/8"	10 7/8"

Caulk outlet available

Provides for roof or drainage pipe expansion and contraction due to precipitation loads and temperature changes.





Z-190


FIG. Z-195 VENT STACK FLASHING SLEEVE

Pipe Size	A	C	D	E	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1 1/2"-2"	6 1/2"	3"	5"		\$ 8.40	\$ 12.60	\$ 20.40	13
2 1/2"-3"	7 1/2"	3 1/8"	5"		9.60	15.40	28.80	14
4"	8 1/2"	3 1/8"	5"		13.20	20.80	36.00	15
5"	11 1/2"	2 1/2"	6"		16.40	26.20	48.00	22
6"	10 1/2"	3 1/8"	5"		17.80	28.20	52.00	24
8"	14 1/2"	2 7/8"	6"		24.00	37.20	62.00	27
10"	16 9/16"	2 3/4"	6"		48.00	76.80	116.00	36
12"	18 1/2"	2 3/4"	6"		72.00	108.00	160.00	45
Add for bottom	11 1/2"-3"				2.00	3.60	5.00	
roof clamping	4-6"				4.00	6.00	7.00	
flange	8-12"				5.00	8.40	10.00	


Assures leak-proof vent piping through roof; positive clamping collar.



Z-195



Z-196




VENT STACK FLASHING SLEEVE (COUNTER FLASHING) FIG. Z-196

Pipe Size		Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
A	F				
1 1/2"	2 15/16"	\$1.10	\$1.70	\$3.20	2
2"	3 1/2"	1.40	2.20	4.30	2 1/2
3"	4 11/16"	2.20	3.40	6.60	3 1/2
4"	5 9/16"	3.20	5.00	9.80	4 1/2
5"	6 11/16"	4.70	7.20	14.00	6
6"	7 11/16"	6.20	9.60	18.90	7 1/2

For Soil or Steel Pipe

Provides tight connection by caulking.



Z-196-3

Pipe Size

A

C

E

Coated (DC)

Galv. (G)

Approx. Wt. Lbs.

1 1/2" 2 3/4"
 2" 3 3/4"
 3" 4 3/4"
 4" 5 7/8"
 5" 7"
 6" 8"
 8" 10 7/8"

3 5/8"
 3 7/8"
 4 1/8"
 3 15/16"
 4"
 4 1/2"
 5 3/16"

\$2.00
 2.40
 3.00
 4.20
 5.60
 7.60
 12.00


\$ 3.60
 4.30
 5.80
 6.70
 9.10
 13.90
 20.40

2
 3
 4
 6
 8
 10
 21


Double thread connections.

VENT FLASHING FITTING

FIG. Z-196-3



Z-197



HORIZONTAL EXPANSION JOINT

FIG. Z-197

Pipe Size		Max. Offset	Coated (DC)	Galv. (G)	Approx. Wt. Lbs.
A	C				
2"	8 3/16"	1/2"	\$ 32.00	\$ 46.00	35
3"	9 5/16"	1/2"	36.50	52.00	38
4"	10 5/16"	1/2"	42.00	61.00	41
6"	12 1/2"	1/2"	67.00	92.00	45
8"	14 1/2"	1/2"	108.00	139.00	50
10"	16 1/2"	1/2"	144.00	192.00	59

Provides for horizontal expansion and for offset connections.

ROOF DRAIN PARTS

FIGS. Z-100 TO Z-115 DOMES

Pipe Size	Coated	Galv.	All Bronze	Add for
2-3-4"	\$ 9.00	\$13.50	\$21.60	\$ 9.60
5"	9.80	14.60	23.20	Polish 9.60
6"	10.50	15.90	26.40	Bronze 9.60
8"	17.30	26.70	52.80	Domes 9.60

FIGS. Z-125 TO Z-135 DOMES

2-3-4-5"	\$ 4.50	\$ 6.90	\$12.00	\$ 6.40
----------	---------	---------	---------	---------

FIGS. Z-150 TO Z-155 FLAT STRAINERS

Pipe Size	Coated	Galv.	All Bronze
2-3-4"	\$ 4.50	\$ 7.20	\$ 9.60
5"	5.30	8.10	10.40
6"	6.00	9.90	12.80
8"	6.80	10.80	15.30

FIGS. Z-165 TO Z-170

2-3-4-5"	\$ 4.30	\$ 6.50	\$10.00
----------	---------	---------	---------

FIGS. Z-105 STRAINER RINGS

All Sizes	Coated	Galv.	All Bronze
	\$ 1.80	\$ 2.70	\$ 4.00

BRASS CLAMPING BOLTS \$.70

FIGS. Z-100 TO Z-115 AND Z-150 TO Z-155

CLAMPING COLLARS

Pipe Size	Coated	Galv.	All Bronze
2-3-4"	\$ 4.50	\$ 7.20	\$ 9.60
5"	5.00	7.90	10.60
6"	5.40	8.60	12.50
8"	6.80	10.80	14.40

FIGS. Z-125 TO Z-135 AND Z-165 TO Z-170

CLAMPING COLLARS

2-3-4-5"	\$ 1.50	\$ 2.30	\$ 4.00
----------	---------	---------	---------

For polished bronze clamping collars add 50%

FIGS. Z-105 AND Z-150 TO Z-155 TILE FRAMES

Pipe Size	Coated	Galv.	All Bronze
2-3-4"	\$ 9.00	\$12.60	\$24.00
5"	10.50	15.70	25.90
6"	11.30	16.70	27.20
8"	18.00	24.80	38.40

FIGS. Z-130 AND Z-165 TO Z-170

2-3-4-5"	\$ 6.30	\$ 7.90	\$10.40
----------	---------	---------	---------

FIGS. Z-130 STRAINER RINGS

All Sizes	\$ 1.40	\$ 2.20	\$ 3.20
-----------	---------	---------	---------

FLOOR OR SHOWER DRAINS . . . Pages 14 to 22

FIGS. Z-200 AND Z-210 FLOOR OR SHOWER DRAIN


Pipe Size			E	E		Coated	Galv.	All Bronze	Chrome	Approx.
A	B-Dia.	C	Caulk	I.P.S.	F	(DC)	(G)	(BR)	Str. add	Wt. Lbs.
2"	4"	7"	3 $\frac{3}{4}$ "	3 $\frac{1}{2}$ "	3 $\frac{3}{4}$ "	\$11.30	\$16.20	\$22.40	\$1.60	12
2"	5"***	7"	3 $\frac{3}{4}$ "	3 $\frac{1}{2}$ "	3 $\frac{3}{4}$ "	12.80	18.00	24.00	2.10	13
3"	5"	9"	4"	3 $\frac{5}{8}$ "	4 $\frac{3}{4}$ "	15.00	21.60	28.00	2.10	15
3"	6"***	9"	4"	3 $\frac{5}{8}$ "	4 $\frac{3}{4}$ "	17.30	24.30	30.40	2.60	16
3"	7"	9"	4"	3 $\frac{5}{8}$ "	4 $\frac{3}{4}$ "	21.00	28.80	34.40	3.70	17
4"	5"	9"	4"	3 $\frac{5}{8}$ "	5 $\frac{5}{8}$ "	16.50	24.30	30.40	2.10	16
4"	6"	9"	4"	3 $\frac{5}{8}$ "	5 $\frac{5}{8}$ "	18.80	27.00	32.80	2.60	17
4"	7"***	9"	4"	3 $\frac{5}{8}$ "	5 $\frac{5}{8}$ "	22.50	31.50	36.80	3.70	18
Deduct for clamp collar						1.50	2.70	4.00		
***Recommended sizes										

**Recommended sizes


Strainer adjustable to plane of floor assuring smooth finish. Non-clogging seepage slots in flashing collar and in vertically adjustable head.



Z-200



Z-200—I. P. S. Outlet




Z-210—Caulk Outlet

FIG. Z-220 FLOOR DRAIN With Solid Hinged Cover

Pipe Size	A	B-Dia.	C	E*	F	Coated (DC)	Galv. (G)	All Bronze (BR)	Chrome Str. add	Approx. Wt. Lbs.
1½-2"	5"	7"	3½"	3¾"	3¾"	\$18.80	\$25.20	\$30.40	\$2.10	12
3"	5"	9"	3⅝"	4¾"	4¾"	21.00	28.80	34.40	2.10	14
3"	7"	9"	3⅝"	4¾"	4¾"	30.00	39.60	44.00	3.70	16
4"	7"	9"	3⅝"	5⅝"	5⅝"	31.50	42.30	46.40	3.70	17
Deduct for clamp collar						1.50	2.70	4.00		

Caulk outlet available; "E" dimension approximately 1 1/2" longer.

Strainer provided with solid hinged cover to be used when strainer is not in operation. Provides finished appearance in exposed locations.




Z-220—I. P. S. Outlet

FIG. Z-230 FLOOR DRAIN With Automatic Back Pressure Device

W/Pol. Bronze Strainer										
Pipe Size	A	B-Dia.	D	E	Coated	Galv.	All Bronze	Coated	Galv.	Chrome
					(DC)	(G)	(BR)	(DC)	(G)	Str. add
2"	5"	5/8"-1 3/8"	7 1/8"	\$16.50	\$26.10	\$44.80	\$26.30	\$36.00	\$ 2.10	24
3"	6"	1"-2"	8 1/8"	18.00	27.90	48.80	27.80	37.80	2.60	25
4"	7"	1"-2"	8 1/8"	19.50	29.70	52.80	29.30	39.60	3.70	26
Deduct for clamping collar					1.50	2.70	4.00			
Grate only					2.60	4.50	6.40			
Secondary Strainer					1.50	2.70	3.20			
Primer Tapping					2.50	2.50	2.50			

I. P. S. outlet available.

For control of backwater from other fixtures or street sewers. Strainer head adjustable to finished floor level.




Z-230—Caulk Outlet




FLOOR OR SHOWER DRAIN With Integral Trap

FIG. Z-250



Z-250



Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Chrome Str. add	Approx. Wt. Lbs.
A					
1 1/2"-2"	\$19.50	\$29.70	\$51.20	\$1.60	16
1 1/2"-2"	21.00	31.50	52.80	2.10	17
3"	27.00	40.50	69.90	2.10	24
3"	29.30	43.20	72.30	2.60	25
3"	33.00	47.70	76.30	3.70	26
4"	33.80	52.20	94.90	2.10	31
4"	36.00	54.90	97.30	2.60	32
4"	39.80	59.40	101.30	3.70	33

Deduct for clamp collar

1.50

2.70

4.00

Pipe Size


A	B-Dia.	C	E	F	G	H
1 1/2"-2"	4"	7"	1 1/2"	1 3/4"	6 1/8"	6 3/4"
1 1/2"-2"	5"***	7"	1 1/2"	1 3/4"	6 1/8"	6 3/4"
3"	5"	9"	2 1/8"	2 5/16"	8 1/8"	9"
3"	6"***	9"	2 1/8"	2 5/16"	8 1/8"	9"
3"	7"	9"	2 1/8"	2 5/16"	8 1/8"	9"
4"	5"	9"	2 3/4"	2 5/16"	8"	9"
4"	6"	9"	2 3/4"	2 5/16"	8"	9"
4"	7"***	9"	2 3/4"	2 5/16"	8"	9"

**Recommended sizes

Caulk outlet available.

Strainer adjustable to plane of floor—see Fig. Z-200—assuring smooth finish. Non-clogging seepage slots in flashing collar and in vertically adjustable head.

FLOOR DRAIN With Solid Hinged Cover and Integral Trap FIG. Z-265



Z-265—I.P.S. Outlet


Pipe Size	B-Dia.	C	D	E	G	H	Coated (DC)	Galv. (G)	All Bronze (BR)	Chrome Str. add	Approx. Wt. Lbs.
A											
1 1/2"-2"	5"	7"	1"-2"	1 1/2"	6 1/8"	6 3/4"	\$27.00	\$38.70	\$59.20	\$2.10	17
3"	5"	9"	1"-2"	2 1/8"	8 1/8"	9"	33.00	47.70	75.30	2.10	25
3"	7"	9"	1"-2"	2 1/8"	8 1/8"	9"	42.00	58.50	85.90	3.70	27
4"	7"	9"	1"-2"	2 3/4"	8"	9"	48.80	70.20	110.90	3.70	33

Deduct for clamp collar

Caulk outlet available.

Strainer provided with solid hinged cover to be used when strainer is not in operation. Provides finished appearance in exposed locations.

FLOOR DRAIN With Automatic Back Pressure Device and Integral Trap FIG. Z-270



Z-270—Caulk Outlet

Pipe Size	B-Dia.	C	E	F	G	H	Coated (DC)	Galv. (G)	All Bronze (BR)	Chrome Str. add	Approx. Wt. Lbs.
A											
2"	3"	7"	1 1/2"	1 3/16"	9"	6 3/4"	\$27.00	\$37.80	\$56.80	\$2.10	14
3"	5"	9"	2 1/8"	2 5/8"	11"	9"	33.00	46.80	72.90	2.10	21
3"	7"	9"	2 1/8"	2 5/8"	11"	9"	39.00	54.00	80.30	3.70	23
4"	7"	9"	2 3/4"	2 5/8"	11"	9"	45.80	66.60	107.70	3.70	30

Deduct for less back pressure device 2-3"—\$4.80 4"—\$6.40


I. P. S. outlet available.

For control of backwater from other fixtures or street sewers. Strainer adjustable to plane of floor—see Fig. Z-200.

FIG. Z-280 FLOOR DRAIN

Pipe Size	A	B-Dia.	C	D	E	F	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1½-2"	5"	7"	1"-4"	2½"	3¾"		\$ 9.80	\$13.20	\$16.30	8
3"	5"	9"	1"-4"	2¾"	4¾"		11.60	16.20	20.40	15
3"	7"	9"	1"-4"	2¾"	4¾"		17.60	23.40	26.10	16
4"	7"	9"	1"-4"	2¾"	5⅝"		18.80	25.60	28.20	17
Str. rest 3" high add							1.50	2.20	2.90	
Str. rest 4" high add							2.10	2.90	3.50	

Strainer adjustable to plane of floor—see Fig. Z-200.




Z-280—I.P.S. Outlet

FIG. Z-300 "THOROFLUSH" FLOOR DRAIN With Side Outlet

Pipe Size			Pol. Bronze Coated (DC)	Grate Galv. (G)	All Bronze (BR)	C. P. Add	W. M. Add	Approx. Wt. Lbs.
A	B-Dia.	E						
2-3"	11"	2½"	\$66.00	\$93.50	\$142.40	\$11.20	\$14.40	50
2-3"	12"x12"	2½"	83.00	116.30	176.40	12.80	19.20	52
Clamp collar, deduct			6.00	9.00	12.80			
Removable plug or stopper in strainer add			\$7.20					
Caulk outlet available.								

Water pressure flushing provides for sanitary washing of drain interior. Recommended for hospitals.



Z-300—I.P.S. Outlet

FIG. Z-310 "THOROFLUSH" FLOOR DRAIN WITH POL. BRONZE HINGED GRATE

Pipe Size	A	Coated (DC)	Galv. (G)	All Bronze (BR)	C. P. Add	W. M. Add	Approx. Wt. Lbs.
2-3"		\$54.00	\$75.30	\$111.70	\$11.20	\$14.40	18
2-3"		65.80	95.30	133.60	12.80	19.20	20
Clamp collar, deduct		6.00	9.00	12.80			
Removable plug or stopper in strainer add		\$7.20					

Caulk outlet available; outlet dimension approximately 1½" longer.

Water pressure flushing provides for sanitary washing of drain interior. Recommended for hospitals.



Z-310—I.P.S. Outlet





FIG. Z-320 REFRIGERATOR FLOOR DRAIN With Flushing Connection

Pipe Size	A	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1-2"		\$18.80	\$25.70	\$38.40	15

Chrome plated rim and strainer add \$4.80
White metal rim and strainer add \$9.60

Flushing connection guards against contamination from melted ice water residues.












Z-320—I.P.S. Outlet



STRAINER HEADS FOR FLOOR OR SHOWER DRAINS

INTERCHANGEABLE

ALL I.P.S. STANDARD THREADS

Standard Round—Slotted
Type "A"Standard Round—Square
Perforations
Type "B"Standard Round—with Hinged
Strainer, Full Slotted
Type "C"Standard Round—with Solid Top
Hinged with Recessed Strainer
Type "D"Standard Round—with Anchoring
Lugs and Slotted Strainer
Type "E"Standard Round—with Adjustable
Sleeve and Slotted Strainer
Type "F"Round—Basket Strainer
Type "M"90° Male I.P.S.
Type "K"Beehive Dome Strainer
Type "G"Rectangular—Full Slotted
Type "J"90° Female I.P.S.
Type "L"


STRAINER HEADS For Floor or Shower Drains

Types "A" "B" and "F" (2" Length) Standard Round

Top Diam.	I.P.S. Th'd Size	Pol. Bronze	C. P. Add	W. M. Add	Approx. Wt. Lbs.
4"	2"	\$ 4.80	\$ 1.60	\$ 2.40	1
4 1/2"	2"	5.60	1.80	2.80	1 1/2
5"	3 1/2"	6.40	2.10	3.20	2
6"	3 1/2"	8.80	2.60	4.40	3
7"	3 1/2"	12.80	3.70	6.40	4 1/2
8"	3 1/2-5"	14.40	4.80	7.20	5
10"	3 1/2-5"	20.80	8.00	10.40	11
12"	3 1/2-5"	28.80	11.20	14.40	17

Type "H"—Standard Square


Top Dim.	I.P.S. Th'd Size	Pol. Bronze	C. P. Add	W. M. Add	Approx. Wt. Lbs.
4"	2"	\$ 6.00	\$ 2.00	\$ 3.00	2
4 1/2"	2"	6.90	2.30	3.40	2 1/2
5"	3 1/2"	8.00	2.60	4.00	3
6"	3 1/2"	11.00	3.20	5.60	4 1/2
7"	3 1/2"	16.00	4.60	8.00	5
8"	3 1/2"	18.00	6.00	9.00	6
10"	3 1/2"	26.00	10.00	13.00	12
12"	3 1/2"	36.00	14.00	18.00	18

Standard Square—Slotted
Type "H"Standard Square—with Anchoring
Lugs and Slotted Strainer
Type "I"TYPES "K" and "L" ANGLE SHOWER STRAINER,
90° Male or Female, I.P.S.

Strainer Size	Pipe Size	Pol. Bronze	C. P. Top	W. M. Top	Approx. Wt. Lbs.
3 1/2 x 3 1/2 x 4 1/2"—C. I. Body	3 1/2"	\$10.40	\$15.20	\$17.60	8
6 1/2 x 6 1/2 x 7"—C. I. Body	3 1/2"	20.80	30.40	35.20	15
3 1/2 x 3 1/2 x 4 1/2"—Bronze Body	3 1/2"	14.40	19.20	21.60	9
6 1/2 x 6 1/2 x 7"—Bronze Body	3 1/2"	28.80	38.40	43.20	6

TYPE "G"—DOME OR BEEHIVE

Size Diam.	Pol. Bronze	C. P.	W. M.	Approx. Wt. Lbs.
4"	\$ 6.40	\$ 8.60	\$ 9.60	1 1/2
4 1/2"	7.40	9.80	11.30	2
5"	8.60	11.30	12.90	2 1/2
6"	11.80	15.10	17.60	3 1/2



Type "N"

Continued on Following Page



TYPE "C"—HINGED TOP

Size Diam.	Pol. Bronze	C. P.	W. M.	Approx. Wt. Lbs.
4"	\$ 8.00	\$ 9.60	\$10.40	1
4 1/2"	8.80	10.60	11.60	1 1/2
5"	9.60	11.70	12.80	2
6"	12.00	14.60	16.40	3
7"	16.00	19.80	22.40	4 1/2
8"	17.60	22.40	24.80	5

TYPE "D"—SOLID HINGED TOP With Secondary Strainer

Size Diam.	Pol. Bronze	C. P.	W. M.	Approx. Wt. Lbs.
5"	\$12.80	\$15.90	\$17.60	3
6"	16.40	20.20	23.00	4
7"	22.40	28.20	32.00	5 1/2
8"	24.80	32.00	35.60	6

TYPE "J"—RECTANGULAR

Size Top	Pol. Bronze	C. P.	W. M.	Approx. Wt. Lbs.
4 1/2 x 8"	\$18.40	\$21.60	\$27.60	4
5 x 9"	20.00	23.20	30.00	5
5 x 17"	27.20	35.20	40.80	13 1/2

TYPE "M"—ROUND With Basket Strainer

Size Diam.	Pol. Bronze	C. P.	W. M.	Approx. Wt. Lbs.
5"	\$10.70	\$13.20	\$16.10	4

TYPE "N"—ROUND With Tractor Type Strainer

Size Diam.	Pol. Bronze	C. P.	W. M.	Approx. Wt. Lbs.
7"	\$16.60	\$20.50	\$25.10	8
9"	25.00	31.40	37.40	12

Type "I"—Add 30% to Type "H" prices—see page 17.

Type "E"—Add 30% to Type "A" prices—see page 17.

Drains or parts of Everdur Metal, Monel Metal, Malleable Iron or Cast Steel—Prices on Application.

Concave or Convex Strainer, add 25%.

Hinged Strainer Square, add to Type "C" \$4.80.

Adjustable Sleeves longer than 2"—see Type "F", prices on application.

Bronze Extension Pieces, prices on application.

All Standard Strainer Heads have a maximum adjustment on threaded shank of 1 1/4" - 1 1/2" depending on drain size.

FIG. Z-400 SHOWER DRAIN With Angle Strainer


Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1 1/2-2"	\$20.80	\$26.00	\$32.00	10
1 1/2-2"	35.20	40.40	46.40	24
3"	22.60	31.40	36.00	11
3"	37.00	45.80	50.40	25
4"	38.40	47.70	52.80	26

Deduct for clamp collar


Pipe Size	1.50				2.75		4.00		
	A	B	B'	C	D		E	J	K
					Min.	Max.			
1½-2"	3½"	3½"	3½"	7⅞"	1½"	2½"	1¾"	1"	¾"
1½-2"	6½"	6½"	6½"	9½"	3"	4"	2⅛"	3½"	1"
3"	3½"	3½"	3½"	7⅞"	1½"	2½"	1¾"	1"	¾"
3"	6½"	6½"	6½"	9½"	3"	4"	2⅜"	3½"	1"
4"	6½"	6½"	6½"	9½"	3"	4"	2⅜"	3½"	1"

Caulk outlet available; "E" dimension approximately 1 1/2" longer.

Floor and wall drainage. Prevents flooding due to paper or towels on strainer. Strainer adjustable to finished floor.



I.P.S. Outlet



Z-400


FIG. Z-405 FLOOR OR SHOWER DRAIN

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Chrome Str. Add	Approx. Wt. Lbs.
1 1/2-2"	\$11.30	\$16.20	\$22.40	\$1.60	10
1 1/2-2"	12.80	18.00	24.00	2.10	11
3"	14.60	23.40	28.00	2.10	11
3"	17.00	25.80	30.40	2.60	12
3"	21.00	29.80	34.40	3.70	13
4"	18.40	27.70	32.80	2.60	12
4"	22.40	31.70	36.80	3.70	13
4"	24.00	33.30	38.40	4.80	14
5"	28.70	36.00	43.40	4.80	16
6"	31.20	40.00	48.40	4.80	17


Deduct for clamp collar

Pipe Size	A	B-Dia.	D	E	F
1 1/2-2"	4"	1"	1"-2"	2 1/8"	2 3/4"
1 1/2-2"	5"	1 1/4"-2 1/4"	2 1/8"	2 3/8"	2 3/4"
3"	5"	1 1/4"-2 1/4"	2 3/8"	4"	4"
3"	6"	1 1/4"-2 1/4"	2 3/8"	4"	4"
3"	7"	1 1/4"-2 1/4"	2 3/8"	4"	4"
4"	6"	1 1/4"-2 1/4"	2 3/8"	5"	5"
4"	7"	1 1/4"-2 1/4"	2 3/8"	5"	5"
4"	8"	1 1/2"-3"	2 3/8"	5"	5"
5"	8"	1 1/2"-3"	2 3/8"	6 1/4"	6 1/4"
6"	8"	1 1/2"-3"	2 3/8"	7 1/4"	7 1/4"

**Recommended sizes



I.P.S. Outlet




Z-405

Provides positive seepage control. Strainer adjustable to floor level.



FLOOR OR SHOWER DRAIN, Adjustable Head, Basket Strainer Type FIG. Z-405-5



Z-405-5—I.P.S. Outlet


Pipe Size A	D Min.—Max.	E	Diam. Str.	Cast Iron W/Pol. Str.			Add for C. P.	W. M.	Approx. Wt. Lbs.
				Coated (DC)	Galv. (G)	All Bronze (BR)			
1½-2"	1¼"-2½"	2½"	5"	\$17.10	\$22.30	\$28.30	\$2.50	\$5.40	13
3"	1¼"-2½"	2¾"	5"	18.90	27.70	32.30	2.50	5.40	14
4"	1¼"-2½"	2¾"	5"	20.30	29.60	34.70	2.50	5.40	15
Deduct for clamping collar				1.50	2.70	4.00			

Caulk outlet available; "E" dimension approximately 1½" longer.

Removable interior basket strainer keeps lines clean.

FLOOR OR SHOWER DRAIN

FIG. Z-415



Z-415—Caulk Outlet

Pipe Size A	B-Dia.	C	D Min.—Max.	E	F	Coated (DC)	Galv. (G)	All Bronze (BR)	Chrome Str. add	Approx. Wt. Lbs.
2"	4"	9½"	1"-2"	3⅜"	3½"	\$11.30	\$16.20	\$22.40	\$1.60	11
2"	5"	9½"	1¼"-2¼"	3⅜"	3½"	12.80	18.00	24.00	2.10	12
3"	5"	9½"	1¼"-2¼"	3⅜"	4⅝"	14.60	23.40	28.00	2.10	12
3"	6"	9½"	1¼"-2¼"	3⅝"	4⅝"	17.00	25.80	30.40	2.60	13
3"	7"	9½"	1½"-3"	3⅝"	4⅝"	21.00	29.80	34.40	3.70	14
4"	6"	10"	1¼"-2¼"	3⅝"	5¾"	18.40	27.70	32.80	2.60	14
4"	7"	10"	1¼"-2¼"	3⅝"	5¾"	22.40	31.70	36.80	3.70	15
4"	8"	10"	1½"-3"	3⅝"	5¾"	24.00	33.30	38.40	4.80	16
**Recommended sizes Deduct for clamp collar						1.50	2.70	4.00		

FIG. Z-440 PRISON CELL DRAIN


Pipe Size	A	B-Dia.	C	D Min.—Max.	E	F	G	Coated (DC)	Galv. (G)	All Bronze (BR)	Add for C. P.	Approx. Wt. Lbs.
1½-2"	4"	7½"	11½"-21¼"	21½"	21¼"	13⅝"	37⅝"	\$16.60	\$22.80	\$30.20	\$1.60	12
1½-2"	5"	7½"	11½"-21¼"	21½"	21¼"	13⅝"	37⅝"	18.90	25.40	32.60	2.10	13
3"	5"	9½"	11½"-21¼"	21½"	21¼"	13⅝"	37⅝"	21.40	31.70	39.80	2.10	14
3"	6"	9½"	11½"-21¼"	21½"	21¼"	13⅝"	37⅝"	25.20	35.50	43.60	2.60	15
3"	7"	9½"	11½"-21¼"	21½"	21¼"	13⅝"	37⅝"	32.30	42.60	50.70	3.70	16
								1.50	2.70	4.00		

Deduct for clamp collar

**Recommended sizes

Caulk outlet available.

Strainer provided with anchorage lugs. Top strainer integrally cast to strainer head to prevent its removal.



Z-440—I.P.S. Outlet

FIG. Z-450 FLOOR OR SHOWER DRAIN With Integral Trap (Drum Type)

Pipe Size	D			Coated	Galv.	All Bronze
A	B-Dia.	Min.—Max.	E	(DC)	(G)	(BR)
1½-2"	4"	1¼"-2¼"	2½"	\$19.50	\$29.70	\$51.20
1½-2"	5"***	1¼"-2¼"	2½"	21.00	31.50	52.80
3"	5"	1¼"-2¼"	2"	26.60	41.30	69.90
3"	6"***	1¼"-2¼"	2"	29.00	43.70	72.30
3"	7"	1½"-3"	2"	33.00	47.70	76.30
4"	6"	1¼"-2¼"	2½"	35.70	55.60	97.30
4"	7"	1¼"-2¼"	2½"	39.70	59.60	101.30
4"	8"***	1½"-3"	2½"	41.30	61.20	102.90


Deduct for clamp collar

Approx. Wt. Lbs. 1½-2"—17, 18, 3"—30, 31, 32, 4"—31, 32, 33.


**Recommended sizes

Caulk outlet available.

Provides positive seepage control. Strainer adjustable to floor level.



I.P.S. Outlet



Z-450

FIG. Z-450-5 FLOOR OR SHOWER DRAIN With Integral Trap (Drum Type), Adjustable Head, Basket Strainer Type

					Cast Iron with Polished Strainer			
Pipe Size	D	Diam.			Coated	Galv.	All Bronze	Approx.
A	Min.—Max.	Strainer	F		(DC)	(G)	(BR)	Wt. Lbs.
1½-2"	1¼"—2½"	5"	2½"		\$25.30	\$35.80	\$57.10	32
3"	1¼"—2½"	5"	2"		30.90	45.60	74.20	33
4"	1¼"—2½"	5"	2½"		37.60	57.50	99.20	34
Deduct for clamp collar					1.50	2.70	4.00	


Deduct for clamp collar

Add for Chrome Plate Top \$2.50

Add for White Metal Top 5.40

Caulk outlet available.

Removable interior basket strainer keeps lines clean.



Z-450-5—I.P.S. Outlet


FIG. Z-453 FLOOR OR SHOWER DRAIN With Integral Trap (Uniform Diameter Type)

Pipe Size		D		Coated	Galv.	All Bronze	Add for		Approx.
A	B-Dia.	Min.—Max.	F	(DC)	(G)	(BR)	C. P.	W. M.	Wt. Lbs.
1½-2"	5"	1¼"—2½"	2½"	\$21.00	\$31.50	\$52.80	\$2.10	\$3.20	30
3"	6"	1¼"—2¾"	2½"	29.00	43.70	72.30	2.60	4.40	31
4"	7"	1½"—3"	3¼"	39.70	59.60	101.30	3.70	6.40	32
Deduct for clamp collar				1.50	2.70	4.00			


Deduct for clamp collar

Caulk outlet available.


Provided with positive clamping collar and adjustable head.



Z-453—I.P.S. Outlet



Z-455




I.P.S. Outlet

FLOOR OR SHOWER DRAIN
With Integral Trap and Floor Level Cleanout

FIG. Z-455

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Chrome Top Add	Approx. Wt. Lbs.
A					
1½-2"	\$30.00	\$44.10	\$68.00	\$3.40	37
3"	35.60	53.50	71.80	3.40	38
3"	38.00	55.90	74.20	3.80	39
4"	42.30	61.80	77.90	3.40	40
4"	44.70	64.20	80.30	3.80	41
Deduct for clamp collar	1.50	2.70	4.00		
Pipe Size	B-Dia.		D Min.—Max.		E
A					
1½-2"	5"		1¼"-2¼"		2⅜"
3"	5"		1¼"-2¼"		2⅜"
3"	6"		1¼"-2¼"		2⅜"
4"	5"		1¼"-2¼"		2⅝"
4"	6"		1¼"-2¼"		2⅝"

**Recommended sizes
Caulk outlet available.




Z-460—I.P.S. Outlet

Pipe Size	B-Dia.	D	E	J	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
A								
1½-2"	4"	1"-2"	2½"	1½"-2"	\$21.00	\$33.00	\$52.80	18
1½-2"	5"	1¼"-2¼"	2½"	1½"-2"	22.50	34.50	54.40	19
3"	5"	1¼"-2¼"	2"	1½"-2"	28.10	43.60	71.50	31
3"	6"	1¼"-2¼"	2"	1½"-2"	30.50	46.00	73.90	32
3"	7"	1⅞"-3"	2"	1½"-2"	34.50	50.00	77.90	33
4"	6"	1¼"-2¼"	2½"	1½"-2"	34.80	56.20	96.50	32
4"	7"	1¼"-2¼"	2½"	1½"-2"	37.20	58.60	98.90	33
4"	8"	1½"-3"	2½"	1½"-2"	41.20	62.60	102.90	34
Deduct for clamp collar					1.50	2.70	4.00	

Caulk outlet available.

For drinking fountains, refrigerator rooms and other floor areas where combined floor drainage and fixture waste connections are desired.



Z-470—I.P.S. Outlet


FLOOR DRAIN With Automatic Back Pressure Device

FIG. Z-470


Pipe Size	B-Dia.	D Min.—Max.	E	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
A							
1½-2"	5"	1¼"-2¼"	2½"	\$28.50	\$40.50	\$62.40	35
3"	7"	1½"-3"	2"	40.50	50.70	84.30	36
4"	7"	1½"-3"	2½"	49.20	68.60	109.30	37
Deduct for clamp collar				1.50	2.70	4.00	

Caulk outlet available.

For control of backwater from other fixtures or street sewers.



Z-475A—I.P.S. Outlet



Z-475—I.P.S. Outlet

SHOWER OR URINAL DRAINS

FIGS. Z-475 & Z-475A

Pipe Size	All Bronze Pol.	C. P.	W. M.	Add for Dome Strainer	Approx. Wt. Lbs.
A					
2"	\$11.00	\$12.80	\$14.70	\$1.90	2
3"	15.00	16.80	18.70	2.20	5
Z-475					
Pipe Size	D Min.—Max.		Pipe Size	D Min.—Max.	
A			A		
2"	2½"-3¾"		2"	2½"-3¾"	
3"	2¼"-3¾"		3"	2¼"-3¾"	

Caulk outlet available; "D" dimension approximately 1½" longer.




FIG. Z-476 URINAL DRAIN With Supporting Flange

Pipe Size			D	E	J	K	Coated (DC)	Galv. (G)	All Bronze (BR)	Add for	
A	B-Dia.	C	Min.—Max.			Min.—Max.				C. P.	W. M.
2"	4½"	9½"	3"—5"	2¼"	8¼"	¼"—3"	\$35.90	\$47.90	\$60.20	\$1.80	\$2.80
3"	4½"	9½"	3"—5"	2¼"	8¼"	¼"—3"	38.40	50.80	62.10	1.80	2.80
Add for clamp collar							2.30	3.60	4.80		

Approx. Wt. Lbs. 2"—14, 3"—15.

Caulk outlet available; "E" dimension approximately 1 1/2" longer.

Eccentric adjustability provides simple alignment required for variation in pottery or roughing.



Z-476—I.P.S. Outlet

INDUSTRIAL FLOOR AND AREA DRAINS . . . Pages 22 to 34


FIG. Z-500 AREA FLOOR DRAIN

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Grate Coated (CB)	Galv. (GB)	Approx. Wt. Lbs.
2-3-4"	\$10.50	\$18.30	\$41.60	\$20.30	\$29.20	22
With square top	16.00	25.90	56.00	26.40	36.80	
Clamping collar add	2.40	4.80	6.40			
Grate only	2.80	4.80	7.70			
Secondary strainer add	1.60	2.90	4.00			
Low dome strainer	4.40	7.70	10.90			
High dome strainer	6.80	11.50	14.90			
Hinged grate add	3.20	3.20	3.20			
Locking device add	2.50	2.50	2.50			
Primer connection add	2.50	2.50	2.50			



Z-500

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
2-3-4"	\$12.00	\$16.30	\$19.50	
	Add for B. W. Valve			
	Add to (CB) and (GB) Lists for			
	C. P.			
	Round Top \$4.80			\$ 9.60
	Square Top 7.20			12.80




I.P.S. Outlet

For caulk outlet, see Z-510.

For floor areas in dairies, packing plants, breweries, laundries, and other industrial and public buildings where floors are flushed and waste water does not carry sediment.

FIG. Z-505 AREA FLOOR DRAIN—Super Size

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Grate Coated (CB)	Galv. (GB)	Approx. Wt. Lbs.
4-5-6"	\$19.50	\$35.00	\$83.20	\$36.00	\$53.00	46
With square top	27.20	47.00	107.20	44.80	64.20	
Clamping collar add	3.20	4.80	8.00			
Grate only	4.00	7.70	19.20			
Secondary strainer add	2.40	3.80	4.80			
Low dome strainer	6.40	11.50	24.00			
High dome strainer	10.80	17.80	28.80			
Hinged grate add	3.20	3.20	3.20			
Locking device add	2.50	2.50	2.50			
Primer connection add	2.50	2.50	2.50			



Z-505—I.P.S. Outlet


Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Pipe Size	E
4"	\$12.00	\$16.30	\$19.50	4"	3 1/8"
5-6"	16.00	22.60	31.00	5"	2 3/4"
	Add to (CB) and (GB) Lists for			6"	2 3/4"
	C. P.				
	Round Top \$ 9.60				
	Square Top 11.20				

For caulk outlet, see Z-515

For same service as Z-500, but for heavier usage.



Z-509



Caulk Outlet

**AREA FLOOR DRAIN—
Shallow Type With Deep Flange Strainer**

FIG. Z-509


Pipe Size A	Cast Iron		With Bronze Top		All Bronze (BR)
	Coated (DC)	Galv. (G)	Coated (CB)	Galv. (GB)	
2-3"	\$ 9.80	\$17.10	\$18.80	\$26.10	\$38.40
3-4"	10.50	18.30	20.30	29.10	41.60
4-6"	19.50	35.00	36.00	53.00	83.20

Pipe Size A	B-Dia.	C	F	Approx. Wt. Lbs.
2"	7"	9"	3 1/16"	14
3"	7"	9"	4 13/16"	15
3"	9"	11"	4 13/16"	17
4"	9"	11"	5 13/16"	21
4"	12"	15"	5 13/16"	45
6"	12"	15"	7 13/16"	46

I. P. S. outlet available.

Two piece body affords tight clamping for flashing; serrated upper clamping surfaces carry off seepage water from flashing or seepage pan.

For extra heavy traffic loads, rim and grate can be furnished in steel.



Z-510—Caulk Outlet

Pipe Size A
2-3-4"
With square top
Clamping collar add
Grate only
Secondary strainer add
Low dome strainer
High dome strainer
Hinged grate add
Locking device add
Primer connection add

AREA FLOOR DRAIN

FIG. Z-510

Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Grate		Approx. Wt. Lbs.
			Coated (CB)	Galv. (GB)	
\$10.50	\$18.30	\$41.60	\$20.30	\$29.20	24
16.00	25.90	56.00	26.40	36.80	
2.40	4.80	6.40			
2.80	4.80	7.70			
1.60	2.90	4.00			
4.40	7.70	10.90			
6.80	11.50	14.90			
3.20	3.20	3.20			
2.50	2.50	2.50			
2.50	2.50	2.50			

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)
2-3-4"	\$12.00	\$16.30	\$19.50

Add for B. W. Valve

Add to (CB) and (GB) Lists for

Pipe Size	C. P.	W. M.
2-3-4"	\$ 4.80	\$ 9.60
2-3-4"	7.20	12.80

Round Top
Square Top


Pipe Size A	E
2"	4 3/4"
3"	4 3/4"
4"	4 1/4"

For I. P. S. outlet, see Z-500

For same service as Z-500.



Z-511



Caulk Outlet

**AREA FLOOR DRAIN—
Deep Type With Deep Flange Strainer and Bucket**

FIG. Z-511

Pipe Size A	Cast Iron		With Bronze Top		All Bronze (BR)	Approx. Wt. Lbs.
	Coated (DC)	Galv. (G)	Coated (CB)	Galv. (GB)		
3-4"	\$23.40	\$37.80	\$38.70	\$54.20	\$ 65.40	41
3-4"	39.00	65.70	55.50	83.70	124.80	90

Pipe Size A	B-Dia.	C	E	F	K
3-4"	9"	12"	7 1/2"	8 5/8"	21 1/2"
3-4"	12 1/2"	16"	9 3/4"	12"	31 1/4"

I. P. S. outlet available.


For same service as Z-509. Provided with deep body and sediment bucket.

For extra heavy traffic loads, rim and grate can be furnished in steel.

FIG. Z-511-1 AREA FLOOR DRAIN With Automatic Back-Water Valve

Pipe Size	Cast Iron		All	Pol. Top—Iron Body		Approx.
A	(DC)	(G)	Bronze	(DC)	(G)	Wt. Lbs.
3-4"	\$27.80	\$43.40	\$58.20	\$43.10	\$59.70	47
Add for auxiliary inlet	4.50	6.30	8.00			

Caulk outlet available.
For same service as Z-511. Vertical swing gate type backwater valve.




Z-511-1—I.P.S. Outlet

FIG. Z-511-2 AREA FLOOR DRAIN With Bell, and Deep Flange Strainer

Pipe Size	Cast Iron		All	Pol. Top—Iron Body		Approx.
A	(DC)	(G)	Bronze	(DC)	(G)	Wt. Lbs.
3-4"	\$21.50	\$35.40	\$69.30	\$36.80	\$51.90	41

I. P. S. outlet available.

For same service as Z-511. Inverted dome in body forms bell trap.




Z-511-2—Caulk Outlet

FIG. Z-511-3 AREA FLOOR DRAIN With Bell, Automatic Back-Water Valve, and Deep Flange Strainer

Pipe Size	Cast Iron		All	Pol. Top—Iron Body		Approx.
A	(DC)	(G)	Bronze	(DC)	(G)	Wt. Lbs.
3-4"	\$30.60	\$48.50	\$88.60	\$45.90	\$64.80	48

I. P. S. outlet available.

For same service as Z-511. Has combination bell trap and backwater valve assembly.




Z-511-3—Caulk Outlet


FIG. Z-511-4 AREA FLOOR DRAIN With Secondary Strainer Auxiliary Inlet, and Deep Flange Strainer

Pipe Size	Cast Iron		All	Pol. Top—Iron Body		Approx.
A	(DC)	(G)	Bronze	(DC)	(G)	Wt. Lbs.
3-4"	\$25.40	\$40.50	\$75.80	\$40.70	\$56.90	44

I. P. S. outlet available.



Z-511-4—Caulk Outlet



Z-515—Caulk Outlet

Pipe Size	A
4-5-6"	
With square top	
Clamping collar add	
Grate only	
Secondary strainer add	
Low dome strainer	
High dome strainer	
Hinged grate add	
Locking device add	
Primer connection add	

Pipe Size	E
4"	4 5/8"
5"	5"
6"	5"

For I. P. S. connection, see Z-505

AREA FLOOR DRAIN—Super Size


FIG. Z-515

Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Grate Coated (CB)	Galv. (GB)	Approx. Wt. Lbs.
\$19.50	\$34.90	\$83.20	\$36.00	\$52.90	46
27.20	47.00	107.20	44.80	64.10	
3.20	4.80	8.00			
4.00	7.70	19.20			
2.40	3.80	4.80			
6.40	11.50	24.00			
10.80	17.80	28.80			
3.20	3.20	3.20			
2.50	2.50	2.50			
2.50	2.50	2.50			

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)
4"	\$12.00	\$16.30	\$19.50
5-6"	16.00	22.60	31.00

Pipe Size	C. P. Round Top	W. M. Round Top
4-5-6"	\$ 9.60	\$14.40
4-5-6"	11.20	19.20

For same service as Z-500 but for greater volume.



Z-516—Caulk Outlet

Pipe Size	A
2-3-4"	
5-6"	
I. P. S. available	

For heavy trucking shock loads. Deep strainer flange prevents displacement of strainer from seat.

FACTORY AREA FLOOR DRAIN, Extra Heavy Duty Type

FIG. Z-516

Coated (DC)	Galv. (G)	All Bronze (BR)	Add for I. P. S. Outlet	Approx. Wt. Lbs.
\$17.40	\$33.90	\$67.70	\$.50	65
17.70	34.20	67.80	.60	77

AREA FLOOR DRAIN With Side Outlet

FIG. Z-520



Z-520—I.P.S. Outlet

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Grate Coated (CB)	Galv. (GB)	Approx. Wt. Lbs.
1 1/2-2"	\$19.20	\$30.80	\$62.40	\$29.00	\$42.50	32
3"	19.20	30.80	62.40	29.00	42.50	33
4"	19.20	30.80	62.40	29.00	42.50	34
5"	32.60	55.50	126.70	49.10	73.70	50
6"	32.60	55.50	126.70	49.10	73.70	50
With square top—9x9"	25.30	39.00	76.80	37.30	51.00	
With square top—12x12"	41.10	67.20	150.70	58.70	86.20	
Clamp. col. "small" add	2.40	3.80	6.40			
Clamp. col. "large" add	3.20	4.80	8.00			
Grate only—8 1/4"	2.80	4.80	7.70			
Grate only—11 1/4"	4.00	7.70	19.20			
Sec. str. "small" add	1.60	2.90	4.00			
Sec. str. "large" add	2.40	3.80	4.80			
Hinged grate add	3.20	3.20	3.20			
Locking device add	2.50	2.50	2.50			

Pipe Size	C. P. Round Top	C. P. Square Top	W. M. Round Top	W. M. Square Top
2-3-4"	\$ 4.80	\$ 7.20	\$ 9.60	\$12.80
5-6"	9.60	11.20	14.40	19.20

For same service as Z-500 but with side outlet for limited space.

(Z-520 continued on following page)


FIG. Z-520 AREA FLOOR DRAIN (Cont.)

FIG. Z-520 I. P. S.


Pipe Size	A	B-Dia.	C	D	E	F	G
1½"	8⅞"	13½"	1¼"	3¾"	4⅞"	5⅝"	
3"	8⅞"	13½"	1¼"	3½"	4⅞"	5⅝"	
4"	8⅞"	13½"	1¼"	3¼"	4⅞"	5⅝"	
5"	11¾"	17"	2"	5¼"	5⅞"	7½"	
6"	11¾"	17"	2"	5"	5⅞"	7½"	

FIG. Z-520 Caulk

Pipe Size	A	B-Dia.	C	D	E	F	G
1 1/2"	8 7/8"	13 1/2"	1 1/4"	3 3/4"	4 7/16"	9 1/4"	
3"	8 7/8"	13 1/2"	1 1/4"	3 1/2"	4 7/16"	9 3/8"	
4"	8 7/8"	13 1/2"	1 1/4"	3 1/4"	4 7/16"	9 1/2"	
5"	11 3/4"	17"	2"	5 1/4"	5 7/8"	10 3/4"	
6"	11 3/4"	17"	2"	5"	5 7/8"	10 7/8"	



Z-520—Hub Outlet



Z-520—I.P.S. Outlet

FIG. Z-530 DOUBLE DUTY AREA DRAIN


With Supplementary Strainer

Pipe Size	A	E	E'	Coated (DC)	Galv. (G)	All Bronze (BR)	Coated (CB)	Galv. (GB)
2-3-4"	3"	4 5/8"		\$21.80	\$37.80	\$92.80	\$38.30	\$55.80
With square top				31.20	52.80	118.40	48.80	69.10
Clamping collar add				3.20	4.80	9.60		
Secondary strainer only				2.40	3.80	4.80		
Grate only				4.80	8.60	17.60		
Low dome strainer				8.00	13.40	25.60		
High dome strainer				14.40	22.10	32.00		
Hinged grate add				3.20	3.20	3.20		
Locking device add				2.50	2.50	2.50		
Primer connection add				2.50	2.50	2.50		


Approx. Wt. Lbs. 2-3-4"—48.

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)
2-3-4"	\$12.00	\$16.30	\$19.50
Add for B. W. Valve			
2-3-4"			
Add to (CB) and (GB) Lists for			
2-3-4"			
2-3-4"	Round Top \$ 9.60		W. M. \$14.40
2-3-4"	Square Top 11.20		19.20

For floor areas in industrial buildings where waste water carries foreign solids or other clogging material.



I.P.S. Outlet



Caulk Outlet




Z-530


FIG. Z-535 DOUBLE DUTY AREA DRAIN—Super Size With Secondary Strainer

Pipe Size	A	E	E'	Coated (DC)	Galv. (G)	All Bronze (BR)	Coated (CB)	Galv. (GB)	Approx. Wt. Lbs.
3-4"	5"	3 1/2"		\$34.80	\$61.90	\$134.40	\$64.80	\$93.10	82
5"	5"	3 1/8"		36.30	63.70	136.00	66.30	94.90	84
6"	5 1/4"	3 1/4"		37.60	65.50	137.60	67.80	96.70	86
8"	5"	3 1/2"		42.30	70.90	142.30	72.30	102.10	88
Square rim and round grate add				11.20	11.40	36.00	11.20	11.40	
Clamping device add				6.40	10.60	16.00			
Grate only				12.00	20.20	35.20			
Secondary strainer only				4.00	5.80	7.20			
Low dome strainer				16.80	28.80	50.40			
High dome strainer				20.00	34.60	57.60			
Hinged Grate add				3.20	3.20	3.20			
Locking device add				2.50	2.50	2.50			
Primer connection add				2.50	2.50	2.50			

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)
3-4"	\$12.00	\$16.30	\$19.50
5-6"	16.00	22.60	30.00
8"	22.40	30.70	44.80
Add for B. W. Valve			
3-4"			
Add to (CB) and (GB) Lists for			
3-4"			
3-4"	Round Top \$14.40		W. M. \$25.60
3-4"	Square Top 16.00		32.00



I.P.S. Outlet




Z-535—Caulk Outlet


For same service as Z-530 but for heavier usage.



Z-540



I.P.S. Outlet



Caulk Outlet

FLOOR AND AREA DRAIN, Continuous Flow Solids Retaining Shallow Type FIG. Z-540

Pipe Size			Coated	Galv.	Bronze Rim and Grate			Approx.
A	E	E*	(DC)	(G)	Coated	Galv.	All Bronze	Wt. Lbs.
					(CB)	(GB)	(BR)	
2-3-4"	4 1/2"	2 1/2"	\$14.40	\$23.00	\$30.40	\$41.40	\$42.60	35
With square top			17.00	26.90	27.40	38.00	57.00	
With side outlet			20.00	31.80	30.00	43.50	63.40	
With side outlet and square top			18.70	29.90	38.70	53.90	54.30	
Grate only			2.40	3.80	5.60	6.70	6.10	
Hinged Grate, add			3.20	3.20	3.20	3.20	3.20	
Clamping device, add			3.40	5.80	2.40	3.80	7.40	
B.W.V., add			12.00	16.30				

Add to Bronze Top Price for C. P. or W. M. Top


Pipe Size	C. P.	W. M.
2-3-4"	\$5.00	\$10.60
With square top	8.20	13.80
With side outlet	5.80	5.80
With side outlet and square top	8.20	8.20

Provided with removable perforated sediment bucket. Assures continuous flow even though sediment bucket is filled. Bucket must always be returned, as top strainer will make improper fit without it.

All features of Z-540 type drain are incorporated in all drains from Z-540 to Z-544A—Pages 27 to 30 inclusive.



Z-541



Caulk Outlet

FLOOR AND AREA DRAIN, Continuous Flow Solids Retaining Shallow Type FIG. Z-541

Pipe Size			Coated	Galv.	Bronze Rim and Grate			Approx.
A			(DC)	(G)	Coated	Galv.	All Bronze	Wt. Lbs.
					(CB)	(GB)	(BR)	
3-4"			\$28.80	\$49.90	\$54.40	\$78.70	\$100.10	64
5-6"			32.00	53.80	57.60	82.60	103.50	67
With square top 3-4"			30.20	52.30	57.10	82.60	105.00	
With side outlet 3-4"			36.00	60.50	68.00	98.40	125.00	
With side outlet and square top 3-4"			37.40	63.00	70.70	102.20	130.10	
With square top 5-6"			33.40	56.20	60.30	86.40	108.60	
With side outlet 5-6"			39.20	64.30	71.20	102.20	128.50	
With side outlet and square top 5-6"			40.60	66.90	73.90	106.10	133.50	
Grate only			4.80	8.60	12.80	12.80	12.80	
Hinged grate, add			3.20	3.20	3.20	3.20	3.20	
Clamping device, add			5.00	6.90	5.00	6.90	11.10	
B.W.V. 3-4", add			12.00	16.30	12.00	16.30		
B.W.V. 5-6", add			16.00	22.60	16.00	22.60		

Pipe Size	C. P.	W. M.
3-4"	\$7.30	\$12.50
5-6"	7.30	12.50
With square top 3-4"	8.70	14.60
With side outlet 3-4"	7.30	13.00
With side outlet and square top 3-4"	8.70	14.60
With square top 5-6"	8.70	14.60
With side outlet 5-6"	7.30	13.00
With side outlet and square top 5-6"	8.70	14.60

Add for

Pipe Size	A	A'	E	E'
3"	3"	3"	6 3/4"	3 1/8"
4"	4"	4"	6 3/4"	3 1/2"
5"			6 3/4"	
6"			6 3/4"	4 3/4"


I.P.S. outlet available

See details under Fig. Z-540.

**FIG. Z-541A FLOOR AND AREA DRAIN, Continuous Flow Solids Retaining Shallow Type,
With Removable Perforated Sediment Bucket**

Pipe Size A	Bronze Rim and Grate					Approx. Wt. Lbs.
	Coated (DC)	Galv. (G)	Coated (CB)	Galv. (GB)	All Bronze (BR)	
3-4"	\$76.80	\$129.00	\$108.80	\$158.40	\$205.40	135
5-6"	80.00	127.70	112.00	162.20	208.80	137
With square top 3-4"	80.60	129.90	114.20	166.20	234.90	
With square top 5-6"	83.80	133.90	117.40	170.10	238.40	
Grate only	6.40	10.60	14.40	14.40	15.70	
Hinged grate, add	6.40	6.40	8.00	8.00	8.00	
Clamping Device, add	9.60	13.40	9.60	13.40	29.60	

Pipe Size	Add for C. P.	W. M.	Pipe Size		E	E'
3-4"	\$13.10	\$20.90	A	A'	8 1/2"	4 1/8"
5-6"	13.10	20.90	3"	3"	8 1/2"	3 7/8"
With square top 3-4"	15.70	26.00	4"	4"	8 1/2"	
With square top 5-6"	15.70	26.00	5"	5"	8 1/2"	
I. P. S. outlet available.			6"	6"	8 1/2"	




Z-541A—Caulk Outlet

See details under Fig. Z-540.

**FIG. Z-541B FLOOR AND AREA DRAIN, Continuous Flow Solids Retaining Shallow Type,
With Removable Perforated Sediment Bucket**

Pipe Size A	Bronze Rim and Grate					Approx. Wt. Lbs.
	Coated (DC)	Galv. (G)	Coated (CB)	Galv. (GB)	All Bronze (BR)	
3-4"	\$139.20	\$207.40	\$212.80	\$290.00	\$440.30	256
5-6"	142.40	211.20	216.00	293.80	443.70	259
With square top 3-4"	163.20	242.00	233.60	313.90	480.30	
With square top 5-6"	166.40	245.80	236.80	318.80	483.80	
Grate only	8.00	13.40	32.00	32.00	34.80	
Hinged grate, add	11.20	11.20	12.80	12.80	11.20	
Clamping device, add	12.80	19.20	12.80	19.20	36.50	

Pipe Size	Add for C. P.	W. M.	Pipe Size		E	E'
3-4"	\$21.80	\$43.50	A	A'	11 1/2"	6 1/2"
5-6"	21.80	43.50	3"	3"	11 1/2"	6 1/2"
With square top 3-4"	29.60	52.20	4"	4"	11 1/2"	6 1/2"
With square top 5-6"	29.60	52.20	5"	5"	11 1/2"	6 1/2"
I. P. S. outlet available.			6"	6"	11 1/2"	6"




Z-541B—Caulk Outlet

See details under Fig. Z-540.


**FIG. Z-542 FLOOR AND AREA DRAIN, Continuous Flow Solids Retaining Deep Type,
With Removable Perforated Sediment Bucket**

Pipe Size A	Bronze Rim and Grate					Approx. Wt. Lbs.
	Coated (DC)	Galv. (G)	Coated (CB)	Galv. (GB)	All Bronze (BR)	
3-4"	\$52.80	\$ 77.80	\$71.20	\$ 97.90	\$140.90	76
5-6"	56.00	81.60	74.40	101.80	144.40	80
With square top 3-4"	57.60	84.50	75.20	104.60	151.40	
With side outlet 3-4"	79.20	110.40	96.80	129.60	211.40	
With side outlet and square top 3-4"	84.00	117.10	101.60	136.30	221.90	
With square top 5-6"	60.80	88.30	78.40	108.50	154.90	
With side outlet 5-6"	82.40	114.20	100.00	133.40	214.90	
With side outlet and square top 5-6"	87.20	121.00	104.80	140.20	225.30	
Grate only	4.80	8.70	12.80	12.80	12.80	
Hinged grate, add	3.20	3.20	3.20	3.20	3.20	
Clamping device, add	5.00	6.90			11.10	

Pipe Size	Add for C. P.	W. M.	Pipe Size		E	E'
3-4"	\$7.30	\$13.90	A	A'	11"	6 1/2"
5-6"	7.30	13.90	3"	3"	11"	6 1/2"
With square top 3-4"	8.70	14.60	4"	4"	11"	6 1/2"
With side outlet 3-4"	7.30	13.00	5"	5"	11"	6"
With side outlet & square top 3-4"	8.70	14.60	6"	6"	11"	5 1/2"
With square top 5-6"	8.70	14.60				
With side outlet 5-6"	7.30	13.00				
With square top & side outlet 5-6"	8.70	14.60				




Z-542




Caulk Outlet

See details under Fig. Z-540.

**FLOOR AND AREA DRAIN, FIG. Z-542A**
Continuous Flow Solids Retaining Deep Type, With Removable Perforated Sediment Bucket


Pipe Size A	Bronze Rim and Grate					Approx. Wt. Lbs.
	Coated (DC)	Galv. (G)	Coated (CB)	Galv. (GB)	All Bronze (BR)	
3-4"	\$ 92.80	\$130.60	\$124.80	\$184.30	\$240.10	159
5-6"	96.00	134.40	128.00	188.20	243.60	163
With square top 3-4"	97.40	138.10	131.00	193.40	271.40	
With square top 5-6"	100.60	141.90	134.20	197.30	274.90	
With side outlet 3-4"	116.00	168.00	156.00	230.40	365.40	
With side outlet 5-6"	119.20	171.90	159.20	234.30	368.90	
With side outlet and square top 3-4"	117.40	171.90	159.00	235.70	393.30	
With side outlet and square top 5-6"	120.60	175.50	162.20	239.70	396.80	
Grate only	6.40	10.60	14.40	14.40	14.40	
Hinged grate, add	6.40	6.40	8.00	8.00	8.00	
Clamping device, add	9.60	13.40	9.60	13.40	29.60	
Add for						
Pipe Size	C. P.	W. M.	Pipe Size		E	E'
3-4"	\$13.10	\$20.90	A	A'	11 1/2"	7 3/4"
5-6"	13.10	20.90	3"	3"	11 1/2"	7"
With square top 3-4"	15.70	26.00	4"	4"	11 1/2"	7 1/2"
With square top 5-6"	15.70	26.00	5"	5"	11 1/2"	6 1/2"
With side outlet 3-4"	13.10	20.90	6"	6"	11 1/2"	6"
With side outlet 5-6"	13.10	20.90	I. P. S. outlet available.			
With square top & side outlet 3-4"	15.70	26.00				
With square top & side outlet 5-6"	15.70	26.00				

See details under Fig. Z-540.


FLOOR AND AREA DRAIN, FIG. Z-542B
Continuous Flow Solids Retaining Deep Type, With Removable Perforated Sediment Bucket

Pipe Size A	Bronze Rim and Grate					Approx. Wt. Lbs.
	Coated (DC)	Galv. (G)	Coated (CB)	Galv. (GB)	All Bronze (BR)	
3-4"	\$152.60	\$228.00	\$225.60	\$312.00	\$490.70	256
5-6"	154.80	231.80	228.80	315.80	495.00	259
With square top 3-4"	179.20	263.00	246.40	337.90	532.40	
With square top 5-6"	182.40	266.90	249.60	341.80	535.90	
Grate only	8.00	13.40	32.00	32.00	32.00	
Hinged grate, add	11.20	11.20	12.80	12.80	12.80	
Clamping device, add	12.80	19.20	12.80	19.20	36.50	
Add for						
Pipe Size	C. P.	W. M.	Pipe Size		E	E'
3-4"	\$21.80	\$43.50	A	A'	14 1/2"	10"
5-6"	21.80	43.50	3"	3"	14 1/2"	9 1/2"
With square top 3-4"	29.60	52.20	4"	4"	14 1/2"	9"
With square top 5-6"	29.60	52.20	5"	5"	14 1/2"	8 1/2"
I. P. S. outlet available.						

See details under Fig. Z-540.

FLOOR AND AREA DRAIN, FIG. Z-544
With Combined Trap and Floor Level Cleanout;
Continuous Flow Solids Retaining Type

Z-544



Caulk Outlet

Pipe Size	Add for C. P.	W. M.	Pipe Size	E
2-3-4"	\$21.80	\$43.50	A	
			2"	6 1/2"
			3"	6"
			4"	5 1/2"

I. P. S. outlet available.

See details under Fig. Z-540.

FIG. Z-544A FLOOR AND AREA DRAIN, Continuous Flow Solids Retaining Type, With Combined Trap and Floor Level Cleanout

Pipe Size	Coated (DC)	Galv. (G)	Bronze Rim and Grate		All Bronze (BR)	Approx. Wt. Lbs.
A			Coated (CB)	Galv. (GB)		
2-3-4"	\$273.60	\$391.70	\$393.60	\$537.60	\$814.40	260
Grate only	8.00	13.50	32.00	32.00	34.80	
Hinged grate, add	11.20	11.20	12.80	12.80	11.20	
Clamping device, add	27.20	40.30	27.20	40.30		
B.W.V. add	12.80	12.80				


Pipe Size	Add for C. P.
2-3-4"	\$31.30

W. M.
\$59.20

Pipe Size
A
2"
3"
4"

E
5 3/8"
4 7/8"
4 3/8"

I. P. S. outlet available.




Z-544A—Caulk Outlet

FIG. Z-545 AREA FLOOR DRAIN With Deflector Strainer

Pipe Size	B-Square	D	E	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
A							
2-3"	6 3/4"	4"	2"	\$18.00	\$29.20	\$55.70	27
3-4"	10 1/2"	7 3/4"	2 3/4"	30.00	50.40	96.00	70
5-6"	10 1/2"	7 3/4"	2 3/4"	33.00	55.80	105.60	72
"Deflector" strainer only, small				5.10	8.60	15.40	
Flat strainer only, small				1.90	4.00	5.80	
"Deflector" strainer only, large				7.00	11.90	21.10	
Flat strainer only, large				2.90	5.80	8.60	

I. P. S. outlet available.

For schools, playgrounds, asylums, and other institutions to protect drainage lines from clogging by injection of sticks and other objects through the strainer.



Z-545—Caulk Outlet

FIG. Z-546 SCHOOL PLAYGROUND DRAIN With Deflector Grate and Secondary Strainer

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
A				
2-3-4"	\$21.60	\$36.70	\$58.60	28
4-5-6"	36.90	60.50	96.00	52
"Deflector" grate only— Small				9.60
Large				14.40
Secondary strainer only— Small				2.40
Large				2.90
Clamping collar add— Small				2.40
Large				3.20


Pipe Size	B-Dia.	C	D	E
A				
2"	8 3/4"	13 1/2"	1 5/8"	2 3/4"
3"	8 3/4"	13 1/2"	1 5/8"	2 3/4"
4"	8 3/4"	13 1/2"	1 5/8"	2 3/4"
4"	11 3/4"	17"	2"	4 5/8"
5"	11 3/4"	17"	2"	5"
6"	11 3/4"	17"	2"	5"

I. P. S. outlet available.

For same service as Z-545.



Z-546



Caulk Outlet

FIG. Z-548 FLOOR DRAIN

Pipe Size	B-Dia.	D	E	Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Grate		Approx. Wt. Lbs.
A							Coated (CB)	Galv. (GB)	
2"	8 3/4"	4 1/2"	6"	\$ 9.80	\$17.20	\$37.10	\$21.00	\$29.60	24
3"	8 3/4"	4 1/2"	6"	11.10	20.70	45.80	22.40	33.10	25
4"	8 3/4"	4 1/2"	6"	13.70	25.80	52.30	26.00	38.30	26
2"	11 3/4"	5"	6"	13.50	23.40	51.20	34.50	46.80	47
3"	11 3/4"	5"	6"	15.00	27.00	60.80	37.50	52.20	48
4"	11 3/4"	5 1/8"	6"	18.00	32.40	67.20	42.00	59.40	49

Add for back water valve (only furnished when specified)


2"—\$6.40

3"—\$9.60

4"—\$12.80

I. P. S. outlet available.

Where long outlet is required.




Z-548—Caulk Outlet



FLOOR DRAIN With Sand Retainer

FIG. Z-549




Z-549—I.P.S. Outlet

Pipe Size	B-Dia.	C	D	E	Coated (DC)	Galv. (G)	Bronze Rim and Grate		Approx. Wt. Lbs.
A							Coated (CB)	Galv. (GB)	
3-4"	11 $\frac{3}{4}$ "	17"	2"	3 $\frac{1}{8}$ "	\$25.90	\$42.30	\$44.60	\$63.00	47
5"	15 $\frac{3}{8}$ "	19 $\frac{3}{4}$ "	2"	3"	42.00	70.60	78.00	112.00	88
6"	15 $\frac{3}{8}$ "	19 $\frac{3}{4}$ "	2"	3"	43.50	72.40	79.50	113.80	90
Clamping collar add—Small					3.20	4.80			
Large					6.40	10.60			

Caulk outlet available; "E" dimension approximately 1 $\frac{1}{2}$ " longer.

For heavy trucking areas; strainer will carry 2000 lbs. Interior sand retaining ring will keep sediment out of drain line.




Z-550—Caulk Outlet

PLAIN FLOOR DRAIN With Sediment Bucket

FIG. Z-550

Pipe Size	E	Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Grate		Approx. Wt. Lbs.
A					Coated (CB)	Galv. (GB)	
2-3-4"	5 $\frac{1}{4}$ "	\$ 9.90	\$15.50	\$30.40	\$16.70	\$22.70	11
FIG. Z-550A with dome strainer, inside caulk connection							
2-3-4"		11.40	17.50	33.00	19.30	25.30	12
Semi-dome strainer only		3.80	5.60	12.20	12.20	12.20	
Sediment bucket deduct		3.90	5.00	5.40			
Flat strainer only		2.30	3.60	9.60			
I. P. S. outlet available.							

For window wells, basement entrances or floors where seepage control is unnecessary.




Z-555—I.P.S. Outlet

PLAIN FLOOR DRAIN

FIG. Z-555

Pipe Size	B	E	Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Strainer		Approx. Wt. Lbs.
A						Coated (CB)	Galv. (GB)	
2"	6"	3"	\$ 3.00	\$ 7.20	\$18.00	\$ 7.40	\$11.70	3
3"	9"	5 $\frac{1}{4}$ "	7.20	17.30	43.20	13.20	24.00	10
4"	12"	5 $\frac{3}{8}$ "	9.60	23.00	57.60	26.30	41.20	20
Add for hinged strainer			3.00	3.00	3.00	3.00	3.00	
Caulk outlet available; "E" dimension approximately 1 $\frac{1}{2}$ " longer.								



Z-556—Caulk Outlet

PLAIN FLOOR DRAIN With Hinged Strainer and Flashing Provision

FIG. Z-556

Pipe Size	H	Coated (DC)	Galv. (G)	Bronze Rim and Strainer		Approx. Wt. Lbs.
A				Coated (CB)	Galv. (GB)	
3"	2 $\frac{1}{2}$ "	\$ 9.60	\$16.20	\$18.00	\$26.10	13
4"	2 $\frac{1}{2}$ "	10.70	19.40	19.70	30.20	14
Strainer only		2.60	4.50			
I. P. S. outlet available.						

For floor areas where copper or lead flashing is necessary for seepage control.




FIG. Z-556A PLAIN FLOOR DRAIN With Side Outlet, Hinged Strainer and Flashing Provision

Pipe Size			Coated (DC)	Galv. (G)	Bronze Rim and Strainer		Approx. Wt. Lbs.
A	E	G			Coated (CB)	Galv. (GB)	
2"	5 1/4"	7 1/2"	\$21.00	\$35.30	\$30.00	\$46.10	30
3.4"	5 1/4"	7 1/2"	22.50	37.10	31.50	47.90	35
Strainer only			2.60	4.50			

I. P. S. outlet available.

For same service as Z-556.




Z-556A—Hub Outlet

FIG. Z-556B FLOOR DRAIN AND TRAP With Hinged Strainer and Flashing Provision

Pipe Size		Coated (DC)	Galv. (G)	Bronze Rim and Strainer		Approx. Wt. Lbs.
A				Coated (CB)	Galv. (GB)	
3"		\$27.00	\$45.40	\$40.50	\$61.60	42
4"		28.50	47.20	42.00	63.40	43

I. P. S. outlet available.


For floor areas requiring integral trap and copper or lead flashing for seepage control.



Z-556B—Hub Outlet

FIG. Z-560 PLAIN FLOOR DRAIN With Hinged Strainer

Pipe Size			Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Strainer		Approx. Wt. Lbs.
A	B	E				Coated (CB)	Galv. (GB)	
2"	6x6"	3"	\$ 2.70	\$ 6.30	\$15.80	\$ 7.90	\$12.60	4
3"	9x9"	6 1/2"	5.30	12.60	31.50	14.70	24.00	15
4"	12x12"	7 3/4"	10.50	25.20	63.00	28.20	46.40	27




Z-560—Spigot Outlet

FIG. Z-565 PLAIN FLOOR DRAIN With Hinged Strainer


Pipe Size				Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Strainer	
A	B	E	G				Coated (CB)	Galv. (GB)
2"	6"	3 1/4"	5 3/4"	\$ 6.00	\$14.40	\$ 36.00	\$12.00	\$21.60
3"	9"	5 1/2"	6 1/2"	12.00	28.80	72.00	22.80	41.80
4"	12"	6 3/8"	7 1/2"	24.00	57.60	144.00	44.20	81.80

Approx. Wt. Lbs. 2"—7, 3"—18, 4"—21.

I. P. S. outlet available.



Spigot Outlet




Z-565



HEAVY GUTTER DRAIN

FIG. Z-575



Z-575—Caulk Outlet


Pipe Size A	Length B	Width	E	Bronze Rim and Grate					Approx. Wt. Lbs.
				Coated (DC)	Galv. (G)	All Bronze (BR)	Coated (CB)	Galv. (GB)	
2-3-4"	13"	5 1/2"	5 3/4"	\$11.20	\$18.40	\$38.40	\$20.80	\$28.80	18
5-6"	15 1/2"	7 5/8"	5 1/2"	22.40	37.40	87.40	39.70	46.60	30
3-4-5-6"	24 1/8"	7 1/8"	6"	44.80	67.20	94.00	68.80	72.80	42
Grate only							Chrome plated top		
12" x 4 1/2"				4.00	6.70	9.60	add \$8.00		
14 1/4" x 6 1/2"				5.60	9.60	16.00	add 9.20		
23" x 6"				10.40	17.30	19.20	add 14.00		
Convex grate only									
12" x 4 1/2"				7.20	10.60	12.80			
14" x 6 1/2"				8.80	13.40	19.20			
23" x 6"				16.00	24.00	26.40			

I. P. S. outlet available.

For narrow gutters in swimming pools and battery shower rooms, providing rapid drainage.

HEAVY GUTTER DRAIN With Seepage Pan


FIG. Z-580



Z-580

Pipe Size A	Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Grate		Approx. Wt. Lbs.
				Coated (CB)	Galv. (GB)	
2-3-4"	\$16.00	\$25.40	\$49.60	\$28.00	\$38.40	31
5-6"	28.80	48.00	101.80	46.10	66.40	38
3-4-5-6"	54.40	75.80	128.00	78.70	102.70	55
Grate only				Chrome Plated Top		
12" x 4 1/2"	4.00	6.70	8.00	add \$8.00		
14 1/4" x 6 1/2"	5.60	9.60	16.00	add 10.20		
23" x 6"	10.40	17.30	19.20	add 14.00		
Clamping collar add						
2-3-4"	5.00	7.20	9.60			
5-6"	6.00	10.80	16.00			
3-4-5-6"	12.00	18.00	22.00			


FIG. Z-580 I. P. S.



I.P.S. Outlet

Pipe Size A	Length of Top B	Width of Top	Body Length C	Body Width	D	E
2"	13"	5 1/2"	17 1/2"	10"	2"	2"
3"	13"	5 1/2"	17 1/2"	10"	2"	2"
4"	13"	5 1/2"	17 1/2"	10"	2"	2"
5"	15 1/2"	7 5/8"	19 1/2"	12"	1 5/8"	4"
6"	15 1/2"	7 5/8"	19 1/2"	12"	1 5/8"	4"
3"	24 1/8"	7 1/8"	28 1/2"	11 1/2"	2"	2 3/4"
4"	24 1/8"	7 1/8"	28 1/2"	11 1/2"	2"	2 3/4"
5"	24 1/8"	7 1/8"	28 1/2"	11 1/2"	2"	2 3/4"
6"	24 1/8"	7 1/8"	28 1/2"	11 1/2"	2"	2 3/4"

FIG. Z-580 I. C.



Caulk Outlet

Pipe Size A	Length of Top B	Width of Top	Body Length C	Body Width	D	E
2"	13"	5 1/2"	17 1/2"	10"	2"	3 3/4"
3"	13"	5 1/2"	17 1/2"	10"	2"	3 1/2"
4"	13"	5 1/2"	17 1/2"	10"	2"	3 1/2"
5"	15 1/2"	7 5/8"	19 1/2"	12"	1 5/8"	3 7/8"
6"	15 1/2"	7 5/8"	19 1/2"	12"	1 5/8"	3 7/8"
3"	24 1/8"	7 1/8"	28 1/2"	11 1/2"	2"	4"
4"	24 1/8"	7 1/8"	28 1/2"	11 1/2"	2"	4"
5"	24 1/8"	7 1/8"	28 1/2"	11 1/2"	2"	4"
6"	24 1/8"	7 1/8"	28 1/2"	11 1/2"	2"	4"


For same service as Z-575.




FIG. Z-585 GUTTER DRAIN With Hinged Grate and Seepage Pan

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Coated (CB)	Galv. (GB)
A					
2-3-4"	\$27.00	\$50.40	\$86.40	\$37.50	\$59.40
Clamp collar, add	3.00	4.00	6.00		
With loose strainer deduct \$2.30					
Approx. Wt. Lbs. 2-3-4"—30.					


Practical rectangular drain with removable sediment bucket.



Z-585



Z-585—Caulk Outlet




Z-585—I.P.S. Outlet

FIG. Z-589 GUTTER DRAIN

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.	Pipe Size
A				75	A
2-3-4-5-6"	\$66.00	\$108.00	\$208.00		4"
Clamp collar, add	10.10	17.30	32.00		5"
					6"

Caulk outlet available.
Clamping facility for flashing if required.




Z-589—I.P.S. Outlet

FIG. Z-590 FLOOR DRAIN With Internal Trap, With Seepage Pan

Pipe Size	E	G	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
A						
2"	2 3/8"	4 3/4"	\$21.00	\$36.00	\$69.10	35
3"	2 3/8"	4 3/4"	25.50	42.30	77.10	36
4"	2 5/8"	4 3/4"	31.50	51.30	85.10	37
5"	3 3/4"	5 1/4"	37.50	58.50	93.10	38
6"	3 3/4"	5 1/4"	43.50	65.70	102.70	39
Clamp collar add			3.00	4.50	5.60	

Pipe Size	Coated (CB)	Galv. (GB)	Chrome Top Add	W. M. Top Add
A				
2"	\$30.80	\$47.70	\$ 8.00	\$10.40
3"	36.80	55.80	8.00	10.40
4"	43.50	65.70	8.00	10.40
5"	51.00	74.70	8.00	10.40
6"	57.00	81.90	8.00	10.40


Hinged strainer add \$3.00
Caulk outlet available.
Provides large drainage capacity within limited space.




Z-590—I.P.S. Outlet



SPECIAL PURPOSE DRAINS . . . Pages 35 to 44



Z-600—Caulk Outlet



Z-605—Caulk Outlet

Z-600, Bottom Outlet

Pipe Size	Top Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Grate Coated (CB)	Galv. (GB)	Approx. Wt. Lbs.
A							
2-3-4"	9"x9"	\$18.00	\$30.20	\$69.10	\$31.20	\$45.50	25
2-3-4"	12"x12 1/2"	36.00	60.50	138.20	55.20	80.70	66
5-6"	12"x12 1/2"	42.00	67.70	144.60	61.20	87.80	70
7" grate only		3.20	5.80	11.20			
10" grate only		5.20	9.20	19.20			
Small bucket only		5.60	8.70	19.20			
Large bucket only		8.80	14.40	28.80			
Small secondary strainer or dam only		1.60	2.90	4.00			
Large secondary strainer or dam only		2.40	3.80	4.80			
Hinged grate add		3.20	3.20	3.20			

Pipe Size

A	B	E	F
2-3-4"	9"x9"	7 1/2"	7"
2-6"	12"x12 1/2"	12 3/4"	10 1/4"


I. P. S. outlet available.

Z-605, Side Outlet, add to above prices 9" x 9" \$6.40 12" x 12 1/2" \$9.60.


Pipe Size	A	B	E	F	G	H	Approx. Wt. Lbs.
2"		9"x9"	3 1/2"	3 1/2"	5 7/8"	5"	25
3"		9"x9"	3"	3 1/2"	5 7/8"	5"	25
4"		9"x9"	3 1/4"	3 1/2"	5 7/8"	5"	25
2"		12"x12 1/2"	8"	5 3/16"	7 7/8"	10 1/4"	71
3"		12"x12 1/2"	7 3/4"	5 3/16"	7 7/8"	10 1/4"	71
4"		12"x12 1/2"	7 1/2"	5 3/16"	7 7/8"	10 1/4"	71
5"		12"x12 1/2"	7 1/4"	5 3/16"	7 7/8"	10 1/4"	71
6"		12"x12 1/2"	7"	5 3/16"	7 7/8"	10 1/4"	71

I. P. S. outlet available.


For waste water containing sediment.



Z-610—Caulk Outlet



Z-615



Caulk Outlet

Z-610 Bottom Outlet

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Grate Coated (CB)	Galv. (GB)	Approx. Wt. Lbs.
A						
2-3-4"	\$39.00	\$65.70	\$124.80	\$55.50	\$83.20	75
5-6"	45.00	72.90	131.20	61.50	90.40	78
Clamping collar	3.20	4.80	9.60			
Grate	4.80	8.60	17.60			
Bucket	9.60	16.10	28.80			
Secondary strainer	2.40	3.80	4.80			
Hinged grate add	3.20	3.20	3.20			
Locking device add	2.50	2.50	2.50			

Add to (CB) and (GB) Lists for

C. P.	W. M.	Coated (DC)	Galv. (G)	All Bronze (BR)
\$12.80	\$16.00	\$12.00	\$16.30	\$19.50

Service Station DRAIN, Heavy Type

FIGS. Z-610 & Z-615

Pipe Size

A	E
2-6"	10 7/8"

I. P. S. outlet available.

Z-615 Side Outlet—Add to above prices \$9.60.

Pipe Size	A	B	C	E	F	G	H	Approx. Wt. Lbs.
2"	12"x12 $\frac{1}{2}$ "	15" sq.	5 $\frac{7}{8}$ "	5 $\frac{1}{8}$ "	8 $\frac{1}{4}$ "	10 $\frac{1}{4}$ "	81	
3"	12"x12 $\frac{1}{2}$ "	15" sq.	5 $\frac{5}{8}$ "	5 $\frac{1}{8}$ "	8 $\frac{1}{4}$ "	10 $\frac{1}{4}$ "	81	
4"	12"x12 $\frac{1}{2}$ "	15" sq.	5 $\frac{3}{8}$ "	5 $\frac{1}{8}$ "	8 $\frac{1}{4}$ "	10 $\frac{1}{4}$ "	81	
5"	12"x12 $\frac{1}{2}$ "	15" sq.	5 $\frac{1}{8}$ "	5 $\frac{1}{8}$ "	8 $\frac{1}{4}$ "	10 $\frac{1}{4}$ "	81	
6"	12"x12 $\frac{1}{2}$ "	15" sq.	4 $\frac{7}{8}$ "	5 $\frac{1}{2}$ "	8 $\frac{1}{4}$ "	10 $\frac{1}{4}$ "	81	

I. P. S. outlet available.



For waste water containing sediment, and where seepage control or floor anchorage is required.



FIG. Z-616 School and Playground DRAIN, Heavy Type, With Deflector Grate and Bottom Outlet

Pipe Size					Coated (DC)	Galv. (G)	All Bronze (BR)
A	B	E	F				
2-3-4"	8 1/2" x 8 1/2"	9"	7" sq.		\$21.60	\$38.30	\$ 72.00
4-5-6"	12" x 12 1/2"	13"	10 3/8" sq.		36.00	60.30	115.20
7" "deflector" grate only					8.00	14.40	24.80
10" "deflector" grate only					12.00	19.20	48.00
Small intercepting dam strainer only					2.40	4.80	6.40
Large intercepting dam strainer only					4.00	6.70	8.80

I. P. S. outlet available.
Approx. Wt. Lbs. 2"-3"-4"—24, 4"-5"-6"—66.




For schools, playgrounds, asylums and other institutions to prevent drain clogging by injection of sticks and other objects through the strainer.

FIG. Z-617 Court or Area DRAIN, Heavy Type, With Deflector Grate and Side Outlet

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.	Pipe Size	A	B	E	F	G	H
A					A						
2-3-4"	\$25.20	\$44.30	\$ 80.00	24	2"	8 1/2" x 8 1/2"	5 1/4"	3 15/16"	8"	6 1/2"	
4-5-6"	42.30	75.60	172.80	68	3"	8 1/2" x 8 1/2"	4 11/16"	3 15/16"	9 13/16"	6 1/2"	
Small seepage pan add	6.40	10.60	22.40		4"	8 1/2" x 8 1/2"	4 3/16"	3 15/16"	10 3/16"	6 1/2"	
Large seepage pan add	8.00	13.40	28.80		4"	12" x 12 1/2"	7 1/2"	5 3/16"	7 7/8"	10 1/4"	
7" "deflector" grate only	8.00	14.40	24.80		5"	12" x 12 1/2"	7 1/4"	5 3/16"	7 7/8"	10 1/4"	
10" "deflector" grate only	11.00	19.20	48.00		6"	12" x 12 1/2"	7"	5 3/16"	7 7/8"	10 1/4"	
Small sediment bucket only	8.00	11.50	22.40								
Large sediment bucket only	11.20	15.40	30.40								

I. P. S. outlet available.



For same service as Z-616.

FIG. Z-620 Court or Area DRAIN, Heavy Type, With Grate Locking Device, Bottom Outlet

Pipe Size	E	Coated Body	Galv. Body	Approx. Wt. Lbs.
A				
2-3-4"	12 3/4"	\$36.00	\$60.50	66
5-6"	13"	40.50	65.90	68
Dirt arrestor in lieu of bucket—deduct		2.00	4.80	
Malleable bucket only		14.00	24.00	
Malleable grate only		12.00	21.60	

I. P. S. outlet available.

Provided with non-slip cover.







FIG. Z-630 Boiler Room Heavy Duty DRAIN, With Internal Trap and Sediment Bucket, Side Outlet

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Grate (CB)	Galv. (GB)	Approx. Wt. Lbs.
A						
2-6"	\$60.00	\$100.80	\$230.40	\$93.00	\$137.70	108

Hinged grate, add \$3.00





Z-635—Caulk Outlet


Boiler Room Heavy Duty DRAIN, With Seepage Pan and Sediment Bucket

FIG. Z-635

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Grate	
A				Coated (CB)	Galv. (GB)
2-6"	\$69.00	\$113.00	\$248.30	\$102.80	\$153.50
Clamping collar add	3.00	6.30	9.60		
Grate	7.50	11.70	27.20		
Bucket	12.00	19.80	43.20		
Add for hinged grate	\$3.00				

Pipe Size	Approx. Wt. Lbs.	
A	E	
2-3-4"	4"	120
5"	4 1/2"	125
6"	5"	126

I. P. S. outlet available.



Z-645—Caulk Outlet

Industrial Heavy Duty DRAIN, With Integral Trap, Sediment Bucket and Side Outlet

FIG. Z-645

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Grate		Approx. Wt. Lbs.
A				Coated (CB)	Galv. (GB)	
2-6"	\$45.60	\$76.20	\$149.80	\$80.80	\$114.60	113
Grate only	8.50	12.70	23.20	23.20	23.20	
Bucket only	12.00	21.00	48.00	12.00	21.10	
Hinged grate add	3.20	3.20	3.20	3.20	3.20	
With seepage pan add	9.60	14.40		9.60	14.40	
With clamping collar add	8.00	10.00		4.80	8.60	

Add to (CB) and (GB) Lists for


Pipe Size
A
2-6"

C. P.
\$17.60


W. M.
\$22.40

Pipe Size
A
2-3"
4"
5"
6"

E
5 1/8"
5 1/8"
5 1/8"
5 1/8"



Caulk Outlet



Z-650

Railroad or Track DRAIN, With Multi-Connections, and Sediment Bucket

FIG. Z-650

Z-650 Bottom Outlet

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Grate		Approx. Wt. Lbs.
A				Coated (CB)	Galv. (GB)	
2-6"	\$39.80	\$67.90	\$146.60	\$75.80	\$107.50	100
Grate	7.50	12.60	25.60			
Bucket	11.30	19.80	48.00			
Hinged grate add	3.00	3.00	3.00			
Seepage pan	9.60	14.40				
Clamping collar	8.00	10.00				

Pipe Size
A
2-6"


E
14"

I. P. S. outlet available.

Z-650 Side Outlet—Add to above prices, \$9.60

Pipe Size	E	G	Approx. Wt. Lbs.
A			
2"	9 7/8"	7 3/4"	98
3"	9 1/4"	8"	100
4"	8 3/4"	8 1/4"	102
5"	8 1/4"	8 1/4"	103
6"	7 3/4"	8 1/4"	104

I. P. S. outlet available.



Side Caulk Outlet


For station trackways, driveways and floor areas where drains are connected in a series and not trapped individually.

FIG. Z-655 Laundry Or Dairy DRAIN With Seepage Pan and Sediment Bucket, Side Outlet

Pipe Size	Coated	Galv.	All Bronze	Bronze Rim and Grate	
A	(DC)	(G)	(BR)	Coated (CB)	Galv. (GB)
2-6"	\$67.40	\$110.20	\$214.60	\$122.90	\$165.70
Grate	11.70	19.30	34.60	Hinged grate add	
Bucket	13.20	22.10	42.20	\$4.50	
Add for B. W. Valve 2"—\$6.00; 3"—\$9.00; 4"—\$12.00					
Pipe Size	E		Approx.		
A			Wt. Lbs.		
2-3-4"	7 ³ / ₄ "		115		
5"	7"		116		
6"	6 ¹ / ₂ "		118		

Bottom outlet or I.P.S. outlet available.

For laundries, dairies and other floor areas where large capacity and seepage control or floor anchorage is required.




Z-655—Caulk Outlet

FIG. Z-660 Factory DRAIN With Flashing Provision For Variable Slabs, Bottom Outlet


				Bronze Rim and Grate	
Pipe Size	Coated	Galv.	All Bronze	Coated	Galv.
A	(DC)	(G)	(BR)	(CB)	(GB)
2-3-4"	\$40.80	\$ 68.40	\$101.80	\$58.80	\$ 84.90
4-5-6"	72.00	121.00	257.30	99.00	136.80
10" grate only	8.00	13.40	25.00	Hinged Grate	
13" grate only	14.00	22.80	30.00	add \$4.00	
Small bucket only	10.00	16.80	30.00	Locking device	
Large bucket only	13.00	21.60	54.00		
Small dam only	3.00	6.00	10.00	add \$2.00	
Large dam only	6.00	10.20	16.00	Side outlet	
Approx. Wt. Lbs. 2-3-4"—49, 4-5-6"—102.				add \$9.60	
Pipe Size					
A	B	D	E	F	
2-3-4"	12"x12½"	3"	7½"	7" sq.	
4-5-6"	16" sq.	3½"	10¾"	10½" sq.	

I. P. S. outlet available.

For extra heavy traffic loads, rim and grate can be furnished in steel.



Caulk Outlet




Z-660

FIG. Z-661 Highway Garage DRAIN With Sludge Bucket and Overflow Provision, Bottom Outlet

Pipe Size	E	Coated (DC)	Galv. (G)	Approx. Wt. Lbs.
A				
2-3-4-5-6"	21 1/2"	\$240.00	\$432.00	300
Top grate only		72.00	129.60	
Sludge bucket only		48.00	86.40	

I. P. S. outlet available.

For highway or public garages where heavy truck, tractor or snow-removal equipment is used. Grate will withstand shock load.




Z-661—Caulk Outlet

FIG. Z-662 Heavy Duty Garage DRAIN With Secondary Strainer


Pipe Size	Coated (DC)	Galv. (G)	Pipe Size	B	E	F	Approx. Wt. Lbs.
A			A				
2-3-4"	\$37.20	\$62.60	2"	12 3/8" sq.	11 1/2"	7 7/8" sq.	59
Grate only	15.00	25.20	3"	12 3/8" sq.	11 1/8"	7 7/8" sq.	
Secondary strainer only	1.50	2.70	4"	12 3/8" sq.	10 3/4"	7 7/8" sq.	

I. P. S. outlet available.

Extra heavy top grate will carry heaviest loads.



Z-662—Caulk Outlet



Z-664—Caulk Outlet

Continuous Gutter DRAIN With Secondary Strainer FIG. Z-664

Pipe Size


A	B	C	D	E	F	G	H	J	K	L	M
2"-3"-4"	5' 8"	6"	9 1/8"	5 3/4"	8"	30"	3 3/8"	7/8"	29 5/8"	5 1/8"	Max.

For each foot in addition to drain body ("F" Dimension)

Detail "A" above—trench body contour; detail "B"—method of joining additional trench sections.
Approx. Wt. Lbs., Drain with grate ("F" Dimension)—24, trench with grate per foot—35.**Very desirable for use with stairs, ramps or any drainage need in gutters or trenches. Extendable to longer than minimum shown, in units of 30" per section. Complete assembly made at factory ready for job installation.**

Drain Only
"F" Dimension
Coated
(DC)
\$37.50
Add 15.00

Ramp, Deck And Pavement DRAIN With Trench FIG. Z-665



Z-665—Caulk Outlet

Pipe Size

A	B
4"-5"-6"	10 5/8"
4"-5"-6"	10 5/8"
4"-5"-6"	10 5/8"
4"-5"-6"	10 5/8"
4"-5"-6"	10 5/8"

Length of


Drain
2 1/2 ft.
5 ft.
7 1/2 ft.
10 ft.
12 1/2 ft.

Cast Iron Coated

(DC)	Galv. (G)
\$103.20	\$142.50
158.20	222.50
213.20	302.50
268.20	382.50
323.20	462.50
6.60	10.40

Approx.

Wt. Lbs.
190
291
536
580
633

Less Sediment bucket, deduct
I. P. S. outlet available.**Interlocking trench and drain assemblies made to any length required. Ample drainage pitch provided.**

Z-668—Caulk Outlet

Heavy Duty DRAIN

FIG. Z-668

Pipe Size

A
4"
Add for seepage pan
Add for clamping collar
Grate only

Coated


(DC)
\$82.50
11.30
19.50
12.00

Galv.

(G)
\$145.20
16.20
25.20
20.70

Approx.

Wt. Lbs.
240

Heavy duty drain for general utility. Removable interior strainer protects outlet against heavy solids.

Z-669—I.P.S. Outlet

Sub Surface DRAIN

FIG. Z-669

Pipe Size

A
4"
5"
6"
8"
Less clamping collar, deduct Z-669 I. P. S.

Coated

(DC)
\$49.00
50.00
51.00
52.50
4.80

Galv.

(G)
\$73.80
75.60
77.40
79.20
6.80

Bronze Rim and Grate

Coated

(CB)
\$83.30
84.00
85.50
86.30
4.80

Galv.

(GB)
\$108.90
109.80
111.60
113.40
6.80

All Bronze

(BR)
\$140.00
141.60
144.80
148.80
11.20

Pipe Size

A	B-Dia.
4"	15"
5"	15"
6"	15"
8"	15"

Z-669 Inside Caulk Connection

Pipe Size

A	B-Dia.
4"	15"
5"	15"
6"	15"
8"	15"

C

20 1/2"
20 1/2"
20 1/2"
20 1/2"

D


4 1/2"
4 1/2"
4 1/2"
4 1/2"

E

3 1/2"
3 1/2"
3 1/2"
3 1/2"

Approx.

Wt. Lbs.
34
35
37
39



Z-669—Caulk Outlet

Semi-dome type strainer provides excess drainage ratio of strainer to outlet.

FIG. Z-675 Garbage Can Washing Floor DRAIN, With Mesh Basket


Pipe Size	E	Coated (DC)	Galv. (G)	Approx. Wt. Lbs.
A 2-6"	20 $\frac{3}{4}$ "	\$246.00	\$406.80	240

Deduct when galv. wire basket is required \$10.50

Deduct when cast iron bucket is required \$26.70

I. P. S. Bottom or Side Outlets and Caulk Side Outlets available.


Can be used with sediment bucket as extra large sump. Flange type strainer.
16 mesh basket.



Z-675—Caulk Outlet

FIG. Z-690 Garage DRAIN Extra Heavy Duty, With Gas Seal Cone, Sediment Bucket, Trap and Cleanout

Pipe Size					Slab Depth	Coated		Bronze Rim and Grate		Approx. Wt. Lbs.
A & A'	D	E	H	J		(DC)	(G)	Coated (CB)	Galv. (GB)	
3-4"	2 $\frac{1}{2}$ "	6 $\frac{1}{2}$ "	22 $\frac{3}{4}$ "	6 $\frac{1}{2}$ "	4"	\$207.60	\$345.90	\$252.60	\$399.90	384
3-4"	4 $\frac{1}{2}$ "	6 $\frac{1}{2}$ "	24 $\frac{3}{4}$ "	8 $\frac{1}{2}$ "	6"	207.60	345.90	252.60	399.90	390
3-4"	6 $\frac{1}{2}$ "	6 $\frac{1}{2}$ "	26 $\frac{3}{4}$ "	10 $\frac{1}{2}$ "	8"	219.60	365.70	264.60	419.70	396
3-4"	8 $\frac{1}{2}$ "	6 $\frac{1}{2}$ "	28 $\frac{3}{4}$ "	12 $\frac{1}{2}$ "	10"	231.60	385.60	276.60	439.60	402
3-4"	10 $\frac{1}{2}$ "	6 $\frac{1}{2}$ "	30 $\frac{3}{4}$ "	14 $\frac{1}{2}$ "	12"	243.60	405.30	288.60	459.30	410
Clamping collar add						20.00	34.80			
Grate only						18.00	30.00	36.00	36.00	
Bucket only						30.40	50.80			
Gas seal cone only						14.40	24.20			
Less seepage pan, deduct						33.00	48.00			
Hinged grate add						10.00	10.00	10.00	10.00	
Back water valve add \$16.00										
I. P. S. outlet available.										




Z-690—Caulk Outlet

Will carry load of heaviest trucks. For floor areas where waste water contains gasoline, oil and sediment.


FIG. Z-691 Oil And Gas Heavy Duty Garage DRAIN

Pipe Size					Slab Depth	Coated		Bronze Rim and Grate		Approx. Wt. Lbs.
A & A'	D	E	H	J		(DC)	(G)	Coated (CB)	Galv. (GB)	
3-4"	2 $\frac{5}{8}$ "	18 $\frac{1}{2}$ "	22 $\frac{3}{4}$ "	6 $\frac{1}{2}$ "	4"	\$151.20	\$221.80	\$187.20	\$265.00	303
3-4"	4 $\frac{5}{8}$ "	20 $\frac{1}{2}$ "	24 $\frac{3}{4}$ "	8 $\frac{1}{2}$ "	6"	162.00	237.20	198.40	281.30	308
3-4"	6 $\frac{5}{8}$ "	22 $\frac{1}{2}$ "	26 $\frac{3}{4}$ "	10 $\frac{1}{2}$ "	8"	172.80	253.50	208.80	297.60	313
3-4"	8 $\frac{5}{8}$ "	24 $\frac{1}{2}$ "	28 $\frac{3}{4}$ "	12 $\frac{1}{2}$ "	10"	171.80	252.90	205.50	293.40	318
3-4"	10 $\frac{5}{8}$ "	26 $\frac{1}{2}$ "	30 $\frac{3}{4}$ "	14 $\frac{1}{2}$ "	12"	183.20	269.80	219.20	313.00	323
Clamping collar add						9.10	12.80			
Trap connection add						16.00	26.40			
Grate only						6.00	9.60	18.00	18.00	
Bucket only						30.40	50.80			
Gas seal cone only						14.40	24.20			
Less seepage pan, deduct						33.00	48.00			
I. P. S. outlet available.										




Z-691—Caulk Outlet

Will carry load of heaviest trucks. For floor areas where waste water contains gasoline, oil and sediment.



Caulk Outlet
Shows Oil Drawoff—1 1/4" I.P.S.



Z-697
Patented

Retention Capacities—550 Cu. In. or approximately 2 1/2 Gal.

Intercepts, separates and recovers oils, gasoline, etc. from waste water. Provides engineered protection against fires, explosions and water pollution. Specially designed for installations where volatile fluids such as gasoline, oil, naphtha, etc., having a lower specific gravity than water, are apt to be discharged into drainage lines. Volatile liquids safety seal in a chamber directly beneath the heavy grate prevents the possibility of explosion and limits the possibility of ignition to a small area in the center of the drain where a flame can be extinguished easily.

Volatile Liquids Intercepting DRAIN

FIG. Z-697

Pipe Size		Coated (DC)	Approx. Wt. Lbs.
A	E		
3"	9"	\$285.00	400
4"	9"	285.00	400
Add for B.W. Valve, if required		22.50	

Volatile Liquids Intercepting DRAIN

With Oil Drawoff


FIG. Z-697-1

Add to Z-697 price

\$45.00



Z-700



Caulk Outlet

Vertical, secondary strainer provides float seat; by reversing this strainer, it serves as a solid plug to close the line entirely, as protection of line during installation, and as positive closure against excessive backwater.


Subsurface Backwater DRAIN, With Integral Trap

And Floor Level Cleanout FIG. Z-700


Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Strainer		Approx. Wt. Lbs.
				Coated (CB)	Galv. (GB)	
A						
2"	\$32.30	\$49.00	\$ 93.90	\$45.00	\$63.00	26
3"	44.30	67.00	125.60	54.80	78.30	36
4"	56.40	84.30	161.30	69.80	99.90	39

Hinged strainer add \$3.00
Less cleanout deduct \$1.50 all sizes
Less float valve deduct 2"—\$6.00; 3"—\$9.00; 4"—\$12.00

Pipe Size	B-Dia.	E	G	H	K
A					
2"	8 1/4"	3 1/4"	11 7/8"	10 5/8"	1 1/2"
3"	8 3/8"	3 7/8"	13 9/16"	12 3/4"	2 1/2"
4"	12"	4 3/8"	15 1/2"	15"	3 1/2"



Z-730



Caulk Outlet

FLOOR DRAIN And TRAP, With Backwater Flap Valve FIG. Z-730

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Grate		Approx. Wt. Lbs.
				Coated (CB)	Galv. (GB)	
A						
2"	\$32.30	\$48.90	\$ 93.90	\$45.00	\$63.00	36
3"	44.30	66.90	125.60	54.80	78.30	54
4"	56.40	85.40	161.20	69.80	99.90	79

Add for auxiliary inlet 8.00 10.60 11.20

Pipe Size	E	G	H	J	K
A					
2"	3 3/4"	14 7/8"	11"	4"	3 1/2"
3"	4 3/8"	17 1/8"	13"	4"	4 1/2"
4"	4 3/4"	19 1/2"	16"	5"	5 1/2"


Chrome P. top add	2"	\$7.70
	3"	8.00
	4"	8.80
If furnished without B. W. Valve, deduct	2"	\$6.40
	3"	9.60
	4"	12.80

Combined drain and deep seal trap. Extra heavy grate. Floor level access cleanout.

FIG. Z-731 Combined DRAIN and Integral, Deep Seal TRAP With B. W. Valve And Floor Level Cleanout

Pipe Size	Bronze Rim and Grate				Approx. Wt. Lbs.
	Coated (DC)	Galv. (G)	Coated (CB)	Galv. (GB)	
2"	\$22.50	\$30.60	\$31.50	\$ 40.50	32
3"	40.50	55.80	56.30	73.80	50
4"	63.00	89.10	79.50	104.40	80

Less B.W.V. deduct 2"—\$11.20; 3"—\$14.40; 4"—\$23.20



Z-731

Caulk Outlet

Pipe Size	A	B	E	G	H	J	K
2"	3 15/16"	3 7/8"	13 1/16"	11 1/4"	4"	2" I.P.S.	
3"	5 1/8"	5"	17"	13 1/2"	4"	3" I.P.S.	
4"	6"	5 7/8"	18 1/2"	16 1/4"	4"	4" I.P.S.	


Swing check valve provided on house side of drain.

FIG. Z-735 FLOOR DRAIN And TRAP With Sediment Bucket And Backwater Valve

Pipe Size	Bronze Rim and Grate				Approx. Wt. Lbs.
	Coated (DC)	Galv. (G)	All Bronze (BR)	Coated (CB)	
2"	\$ 53.60	\$ 82.20	\$132.30	\$ 67.20	65
3"	69.60	105.80	167.80	80.80	90
4"	85.80	131.70	218.90	101.60	105

C. P. Top, add 2" \$7.70
3" 8.00
4" 8.80

Clamping collar add 4.00 6.00 12.00
Deduct for bucket 6.40 11.50 19.20
If Less B.W. Valve, Deduct 2"—\$6.40; 3"—\$9.60; 4"—\$12.80



Z-735


Pipe Size	A	C	E	G	H	J	K
2"	18"	3 3/4"	14 7/8"	11"	4"	3 1/2"	
3"	19 7/8"	4 1/4"	17 1/8"	13"	4"	4 1/2"	
4"	19 7/8"	4 1/4"	17 1/8"	13"	4"	4 1/2"	

Combined drain and deep seal trap. Extra heavy grate. Floor level access cleanout.

FIG. Z-750 Basement And Foundation DRAIN With Integral Trap And Backwater Valve

Pipe Size	Bronze Rim and Grate				Approx. Wt. Lbs.
	Coated (DC)	Galv. (G)	All Bronze (BR)	Coated (CB)	
3"	\$54.30	\$96.90	\$119.00	\$68.10	\$108.00
4"	54.30	96.90	119.00	68.10	108.00

Less extension provision, deduct 4.70
Less float valve, deduct 12.00
Additional drain tile inlet, add 1.50
Approx. Wt. Lbs. 3"—80, 4"—83.



Z-750


Caulk Outlet

Tile pipe connection provides for subsoil drainage.

FIG. Z-752 Basement Subsoil DRAIN With Backwater Valve and Round Float


Pipe Size	Bronze Rim and Grate				Add for C. P.	Approx. Wt. Lbs.
	Coated (DC)	Galv. (G)	Coated (CB)	Galv. (GB)		
3"	\$30.00	\$56.20	\$40.50	\$67.50	\$ 8.00	80
4"	36.00	64.40	49.40	79.00	8.80	82

Add for B.W. Valve on tile inlets—\$3.00
Hinged strainer add—\$3.00
Deduct for B.W. Valve 3"—\$9.00; 4"—\$12.00
Available with brass swing check backwater valve in place of float valve.




Z-752

Tile pipe connection provides for subsoil drainage. Top strainer and frame can be set at any desired level with the use of sheet metal extension.



Z-754



Z-754-1


FLOOR DRAIN With Integral Trap, B. W. Valve and Floor Level Cleanout FIG. Z-754, Z-754-1

Pipe Size	Coated (DC)	Galv. (G)	Bronze Rim and Grate Coated (CB)	Galv. (GB)	Add for C. P.	Approx. Wt. Lbs.
A						
3"	\$44.30	\$66.90	\$54.80	\$78.30	\$ 8.00	82
4"	56.40	85.40	69.80	99.90	8.80	84
Add for bucket—3"	5.40	8.30				
—4"	6.80	11.40				
Strainer only	4.40	7.90				
Hinged strainer add	\$3.00					
Deduct for B.W. Valve 3"	—\$9.60					
4"	—\$12.80					

Pipe Size	G	H	K	L	M
A					
3"	20 ³ / ₄ "	15 ¹ / ₂ "	3 ¹ / ₂ "	4"	4"
4"	22"	16 ⁵ / ₈ "	4 ¹ / ₂ "	5"	4 ³ / ₄ "

Pipe Size	Coated (DC)	Galv. (G)
A		
3"	\$7.50	\$9.90
4"		

Z-754, Z-754-1 Furnished with solid cover when specified.


Adjustable Combination Basement and Subsoil DRAIN With Backwater Valve and Floor Level Cleanout FIG. Z-755

Z-755

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Grate Coated (CB)	Galv. (GB)	Add for C. P.	Approx. Wt. Lbs.
A							
3"	\$49.00	\$85.60	\$181.30	\$61.00	\$ 97.60	\$8.00	77
4"	53.00	92.00	196.10	65.00	104.00	8.80	79
Strainer only	4.40	7.90					
Hinged strainer add	\$3.00						
Deduct for B.W. Valve 3"	—\$9.60						
4"	—\$12.80						

Pipe Size	B-Dia.	G	H	K	L	M	N	P
A								
3"	9 ¹ / ₂ "	20 ³ / ₄ "	15 ¹ / ₂ "	4"	3 ¹ / ₂ "	4"	4"	8 ¹ / ₂ "
4"	9 ¹ / ₂ "	22"	16 ⁵ / ₈ "	4"	4 ¹ / ₂ "	5"	4 ³ / ₄ "	8 ¹ / ₂ "

Tile pipe connection provides for subsoil drainage. Top strainer and frame can be set at any desired level with the use of sheet metal extension. Furnished with solid cover when specified.

Adjustable Combination Basement and Subsoil DRAIN FIG. Z-755-2

Z-755-2

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Polished Bronze Top		Add for C. P.	Approx. Wt. Lbs.
A				Coated (CB)	Galv. (GB)		
3"	\$16.50	\$30.30	\$79.20	\$31.80	\$48.40	\$8.00	43
4"	22.00	40.40	88.00	34.00	52.40	8.80	44
Pipe Size	B-Dia.	H	J	M	N		
A							
3"	9½"	81½"	4"	17⁄8"	33⁄4"		
4"	91⁄2"	81½"	4"	17⁄8"	33⁄4"		


Tile pipe connections provide for subsoil drainage. Sheet metal extension piece cut to proper length permits location of strainer and frame at required level. Furnished with solid cover when specified.

FIG. Z-756 Adjustable Combination Basement and Subsoil DRAIN With Tile Inlets and Backwater Valve

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Polished Bronze Top Coated (CB)	Galv. (GB)	Add for C. P.	Approx. Wt. Lbs.
3"	\$30.50	\$51.70	\$128.80	\$42.80	\$63.80	\$8.00	70
4"	36.00	64.50	166.40	49.50	78.00	8.80	75

Deduct for B. W. Valve 3"—\$9.60; 4"—\$12.80

Pipe Size	B	G	H	J	K	L	M	N	P
3"	9 1/2"	18 3/8"	8 1/2"	4"	4 1/2"	5"	7 7/8"	3 3/4"	9 3/4"
4"	9 1/2"	18 3/8"	8 1/2"	4"	4 1/2"	5"	7 7/8"	3 3/4"	9 3/4"





Same service as Z-755-2, but with backwater valve and adjustable floor level cleanout. Tile pipe connection provides for subsoil drainage. Top strainer and frame can be set at any desired level with the use of sheet metal extension.

FIG. Z-760 Superservice Boiler House DRAIN and Trap With Backwater Valve and Sediment Bucket

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Grate Coated (CB)	Galv. (GB)
2"	\$61.10	\$98.80	\$213.60	\$80.30	\$119.00
3"	68.40	109.10	229.90	87.60	129.20
4"	80.10	126.40	260.20	99.30	146.50




Add for seepage pan 25.60 38.40 56.00 25.60 38.40
Add for clamping collar 6.00 10.80 16.00 6.00 10.80
Hinged grate add \$3.20
Less backwater valve, deduct 2"—\$6.40; 3"—\$9.60; 4"—\$12.80
Approx. Wt. Lbs. 2"—109, 3"—110, 4"—112.



For all heavy duty requirements. Regularly furnished with outlet for I.P.S. connection.

FIGS. Z-798, 798A, 798B Industrial Catch Basin Frames and COVERS

Z-798—Solid Cover					
B-Dia.	C	D	Coated (DC)	Galv. (G)	Approx. Wt. Lbs.
12 7/8"	14"	3"	\$23.60	\$ 56.70	24
18"	21"	5 1/8"	56.30	135.00	91
24"	27"	5"	85.50	205.20	218
Z-798A—Grate Cover					
B-Dia.	C	D			
12 7/8"	14"	3"	\$22.50	\$ 54.00	20
18" heavy	21"	5 1/8"	49.50	118.80	85
18" double duty	21"	5 1/8"	61.90	138.50	175
24" heavy	27"	5"	64.10	153.90	137
24" extra heavy	27"	5"	86.50	206.90	227
Z-798B—Convex Cover					
B-Dia.	C	D	E		
12 7/8"	14"	3"	5"	\$36.00	\$ 85.40
18"	21"	5 1/8"	5"	57.40	137.70
24"	27"	5"	5"	74.30	178.20



For general heavy industrial usage. Will not loosen from cement.




SWIMMING POOL DRAINS AND ACCESSORIES . . . Pages 45 to 51

Swimming Pool Discharge DRAIN


FIG. Z-800



Z-800



I.P.S. Outlet



Caulk Outlet

I. P. S. or inside caulk
Pipe Size Str. Coated Galv. All Bronze
A Dia. (DC) (G) (BR)
2" 8" \$17.50 \$29.40 \$50.40
3" 8" 18.40 30.80 52.50
4" 8" 20.30 34.00 58.80
Clamping collar, add 2.40 3.80 4.80
Chrome plated strainer, add 7.20 7.20
White metal strainer, add 12.80 12.80

I. P. S. or Inside Caulk
Pipe Size Str. Coated Galv. All Bronze
A Dia. (DC) (G) (BR)
3" 10" \$23.90 \$42.00 \$94.50
4" 10" 23.90 42.00 94.50
5" 10" 25.40 45.20 98.00
6" 10" 26.30 47.30 101.50
Clamping collar, add 3.20 4.80 5.60
Chrome plated strainer, add 11.20 11.20
White metal strainer, add 19.20 19.20

Pipe Size

Dimensions for Small Size Body

A	B	C	D	E	E*
2"	10"	13 1/2"	2"	2 3/4"	4 3/4"
3"	10"	13 1/2"	2"	2 3/4"	4 3/4"
4"	10"	13 1/2"	2"	2 3/4"	4 3/4"

*For caulked outlet.


Pipe Size

Dimensions for Large Size Body

A	B	C	D	E	E*
3"	13 1/4"	17"	2 1/4"	3 1/8"	4 5/8"
4"	13 1/4"	17"	2 1/4"	3 1/8"	4 5/8"
5"	13 1/4"	17"	2 1/4"	2 3/4"	5"
6"	13 1/4"	17"	2 1/4"	2 3/4"	5"

*For caulked outlet.

Anchorage flange provides permanent leak-proof installation.



Z-801—Caulk Outlet


Main Outlet Pool DRAIN

FIG. Z-801

Pipe Size A	E	Bronze Rim and Strainer		Approx. Wt. Lbs.
		Coated (CB)	Galv. (GB)	
6"	7 3/4"	\$142.20	\$156.50	180
8"	7 3/4"	147.50	165.50	185
10"	7 3/4"	168.50	201.70	189
12"	7 3/4"	195.60	237.80	195

I. P. S. outlet available.

Supersize rapid discharge drain can be installed in bottom, or side wall.
Anchorage flange assures tight installation.



Z-805—Caulk Outlet

Swimming Pool Discharge DRAIN

FIG. Z-805

Pipe Size A	Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Grate	
				Coated (CB)	Galv. (GB)
4-5-6"	\$ 59.50	\$102.60	\$220.50	\$ 82.60	\$124.80
6-8-10"	125.30	210.40	451.50	158.20	239.40
Clamping collar, add		3.50	5.30	10.50	
Add to (CB) and (GB) Lists for					
Pipe Size		C. P. Chrome Pl.		White Metal	W. M.
A					
4-5-6"		\$14.40			\$18.00
6-8-10"		16.00			32.00


Large strainer open area ratio. Quick discharge. Concrete anchorage flange.
Z-805 Continued on Following Page

(Continued from Previous Page)

FIG. Z-805 Swimming Pool Discharge DRAIN

Pipe Size A	B	E	H	Approx. Wt. Lbs.
4"	12"x12"	$10\frac{5}{8}" + 4\frac{3}{8}" = 15\frac{1}{4}"$	18"	94
5"	12"x12"	$10\frac{1}{8}" + 4\frac{3}{8}" = 14\frac{5}{8}"$	18"	95
6"	12"x12"	$9\frac{5}{8}" + 4\frac{3}{8}" = 14"$	18"	96
8"	12"x12"	$21\frac{5}{8}" + 4\frac{3}{8}" = 26"$	30"	125
10"	12"x12"	$20\frac{5}{8}" + 4\frac{3}{8}" = 25"$	30"	128
		$18\frac{5}{8}" = 24"$	30"	132

I. P. S. outlet available.




Z-805—Caulk Outlet

FIG. Z-807 Swimming Pool DRAIN With Non-Slip Top

Pipe Size A	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
2-3-4"	\$30.00	\$46.80	\$57.60	28

Caulk outlet available; outlet dimension approximately $1\frac{1}{2}"$ longer.

Grit top eliminates danger of slipping when wet. Particularly desirable around pool edge and adjacent areas. Adjustable head. Flashing provision if desired.



Z-807—I.P.S. Outlet


FIG. Z-808 Antiseptic Foot Bath DRAIN With Solid Screwed Top

Pipe Size A	Coated (DC)	Galv. (G)	All Bronze (BR)	Add for Chrome Locking Top Device	Pipe Size A	E
2-3-4"	\$29.30	\$39.60	\$44.80	\$3.80	2"	$2\frac{1}{2}"$
Clamping collar deduct	1.50	2.70	4.00		3"-4"	$2\frac{3}{4}"$


Approx. Wt. Lbs. 2"-3"-4"—15.

Caulk outlet available; "E" dimension approximately $1\frac{1}{2}"$ longer.

Strainer head has non-slip water tight top for retaining antiseptic foot bath water. By removing top, quick drainage is provided through the secondary strainer so that the foot bath can be scoured easily.



I.P.S. Outlet




Z-808

FIG. Z-808A Zoo Or Animal Den DRAIN With Flushing Connection

Pipe Size A	Bronze Top and Grate Coated (CB)	Galv. (GB)	C. P. Top	Add for W. M. Top	Approx. Wt. Lbs.
3 to 8"	\$132.80	\$175.50	\$25.60	\$44.80	115

Caulk outlet available; body height dimension the same.
Perforated top available.

Large drainage area assures rapid discharge. Flushing connection serves as a washdown for accumulations.




Z-808A—I.P.S. Outlet



Pool Or Pit DRAIN

FIG. Z-809



Z-809—Caulk Outlet


Pipe Size	Coated (DC)	Galv. (G)	With Bronze Frame and Grate Coated (CB)	Galv. (GB)	Add for Back Water Valve	Approx. Wt. Lbs.
A						
2-3-4"	\$20.60	\$30.90	\$36.60	\$56.30	\$12.80	48
5-6"	26.20	39.50	47.40	72.80	19.20	55
Clamping collar, add—small	7.70	9.60				
large	8.80	11.20				
Pipe Size	B	B'	C	C'	E	
A						
2-3-4"	9 $\frac{3}{8}$ "	7"	13"	11"	9"	
5-6"	11 $\frac{1}{8}$ "	8 $\frac{1}{2}$ "	14 $\frac{5}{8}$ "	12"	9 $\frac{1}{2}$ "	

I. P. S. outlet available.

Excellent for wall drainage in pools or any other installation at low sewer level. Backwater valve optional but usually desirable. Anchor-age flange.

POOL DRAIN And Overflow Connection-bronze

FIG. Z-809A



Z-809A—I.P.S. Outlet

Z-809B

Pipe Size	Height	E	Pol.	C. P.	Approx. Wt. Lbs.
A					
2"	6"	2 $\frac{1}{2}$ "	\$40.80	\$53.30	20
For each additional inch in height add			1.40	.40	
3"	6"	2 $\frac{3}{4}$ "	50.40	65.30	22
For each additional inch in height add			2.00	4.00	

Note: Lists cover complete drain.

Caulk outlet available; "E" dimension approximately 1 $\frac{1}{2}$ " longer.


LANE MARKER-bronze

FIG. Z-809B

Pol.	C. P.	Approx. Wt. Lbs.
\$13.60	\$18.70	6

These and many other special pool accessories are available.

Swimming Pool Discharge DRAIN, Angle Type Reversible FIG. Z-810




Z-810

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Strainer Coated (CB)	Galv. (GB)
A					
2-3-4"	\$27.00	\$36.30	\$ 72.60	\$39.80	\$ 51.70
4-5-6"	55.20	77.60	147.60	72.00	96.80

Add to (CB) and (GB) Lists for

Pipe Size	C. P.	W. M.
A		
2-3-4"	\$10.20	\$12.80
4-5-6"	15.40	16.00



I.P.S. Outlet

Pipe Size	B	B'	C	D	E	E'	F	Approx. Wt. Lbs.
A								
2"	5"	5"	7 $\frac{1}{2}$ "	1 $\frac{1}{4}$ "	+1 $\frac{13}{16}$ "	2 $\frac{3}{4}$ "	7"	18
3"	5"	5"	7 $\frac{1}{2}$ "	1 $\frac{1}{4}$ "	+1 $\frac{19}{32}$ "	2 $\frac{3}{4}$ "	7"	19
4"	5"	5"	7 $\frac{1}{2}$ "	1 $\frac{1}{4}$ "	+ $\frac{3}{4}$ "	2 $\frac{3}{4}$ "	7"	20
4"	7"	7"	12 $\frac{5}{8}$ "	1 $\frac{1}{4}$ "	+ $\frac{13}{16}$ "	3 $\frac{1}{2}$ "	11 $\frac{3}{4}$ "	65
5"	7"	7"	12 $\frac{5}{8}$ "	1 $\frac{1}{4}$ "	+ $\frac{9}{32}$ "	3 $\frac{1}{2}$ "	11 $\frac{3}{4}$ "	66
6"	7"	7"	12 $\frac{5}{8}$ "	1 $\frac{1}{4}$ "	— $\frac{1}{4}$ "	3 $\frac{1}{2}$ "	11 $\frac{3}{4}$ "	67

Caulk outlet available; "E'" dimension approximately 1 $\frac{1}{2}$ " longer.

Angle face serves as overflow; assures continuous drainage even though leaves, paper, etc. may clog the bottom surface of the pool drain. Outlet may be made either vertically or horizontally.

FIGS. Z-820-822 Swimming Pool GUTTER DRAINS - bronze

FIG. Z-820

Pipe Size	A	B	E	Pol.	C. P.	W. M.	Approx. Wt. Lbs.
1½-2"	2¼"	3¾"	2¾"	\$ 7.20	\$ 8.80	\$ 9.60	2
2-3"	2¾"	5½"	2½"	11.20	13.30	14.40	3



FIG. Z-821

Pipe Size	A	Pol.	C. P.	W. M.	Approx. Wt. Lbs.
1½-2"		\$11.20	\$13.80	\$14.40	3





FIG. Z-822

Pipe Size	A	Pol.	C. P.	W. M.	Approx. Wt. Lbs.
1½-2½"		\$13.60	\$16.20	\$18.00	5

For any type of narrow gutter drainage.



Z-820



Z-821-I.P.S. Outlet


Z-822-I.P.S. Outlet

FIG. Z-823 Swimming Pool GUTTER DRAIN

Pipe Size	With Bronze Strainer	Coated	Galv.	All Bronze	Add for C. P.	W. M.	Approx. Wt. Lbs.
2-3"		\$12.00	\$17.30	\$24.00	\$3.60	\$5.60	8

Caulk outlet available; body height dimension approximately 1½" longer.

Practical for walks, driveways, and other narrow installations.



Z-823

FIG. Z-825 and Z-825A Swimming Pool GUTTER DRAINS - bronze




FIG. Z-825

Pipe Size	A	Pol.	C. P.	W. M.	Approx. Wt. Lbs.
1-1½-2"		\$ 8.80	\$12.00	\$15.20	2

FIG. Z-825A


Pipe Size	A	Pol.	C. P.	W. M.	Approx. Wt. Lbs.
1½-2-3"		26.40	34.40	42.80	9

Vertical faces serve as overflows.





Z-825-I.P.S. Outlet

Z-825A-I.P.S. Outlet



Z-826—I.P.S. Outlet



Z-827—I.P.S. Outlet

Swimming Pool GUTTER DRAINS

FIG. Z-826-827

FIG. Z-826

Pipe Size

A
1 1/2-2-2 1/2"Pol.
\$10.40C. P.
\$14.20W. M.
\$14.60Approx.
Wt. Lbs.
4

FIG. Z-827

2-2 1/2-3"


12.80

16.00

18.80

5

Vertical faces serve as overflows.



Z-830—I.P.S. Outlet


Swimming Pool GUTTER DRAIN

FIG. Z-830

Pipe Size

A
1 1/2-2"Pol.
\$16.80C. P.
\$18.40W. M.
\$19.20Approx.
Wt. Lbs.
7

Angle outlet simplifies installation.



Z-835—I.P.S. Inlet

Swimming Pool SPRAY INLET

FIG. Z-835

Pipe Size

A

E

1 1/2-2"

2 1/2"

3"

2 3/4"

4"

2 3/4"

Coated
(DC)Galv.
(G)All Bronze
(BR)C. P.
addW. M.
addApprox.
Wt. Lbs.

\$17.60

\$23.00

\$24.00

\$4.80

\$8.00

12

19.20

25.90

26.40

4.80

8.00

13

20.80

28.80

28.80

4.80

8.00

14

Clamping collar add


1.50

2.70

4.00

Caulk outlet available; "E" dimension approximately 1 1/2" longer.

For swimming pool circulating inlets above water level. Flashing provision guards against leakage.



Z-837—I.P.S. Inlet

Wading Pool SPRAY INLET

FIG. Z-837

Pipe Size

A
1 1/2"Plain
Bronze

\$20.00

Polished
Bronze

\$22.40

Add for
C. P.
Top

\$4.40

Approx.
Wt. Lbs.

3

Balanced face perforations provide uniform spray. Face removable for cleaning.

FIG. Z-838 Children's Play Pool Spray HEAD

Pipe Size	Polished Bronze	Add for C. P. Dome	Approx. Wt. Lbs.
A			
2"	\$128.00	\$20.00	33

Pressure reducing chamber behind balanced face perforations enables children to play directly on the face without harm. Face removable for cleaning. Angle body design with concrete anchors provide rigid installation.




FIG. Z-839 Swimming Pool SPRAY INLET

Pipe Size	Polished Bronze	Add for C. P.	Approx. Wt. Lbs.
A			
2"	\$59.20	\$8.00	11

Provides uniform spray under balanced pressure.




FIG. Z-840 Swimming Pool FLUSHING INLET

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	C. P. add	W. M. add	Approx. Wt. Lbs.
A						
1 1/2-2-2 1/2"	\$21.00	\$27.90	\$32.80	\$1.60	\$2.40	12
Less clamping collar deduct	1.50	2.70	4.00			
Spray heads only			15.20			

For swimming pool surface flushing and recirculating inlets at water level. Diverging spray flushes surface of pool; supplies clean water for circulation. Has flashing provision.





FIG. Z-845 Swimming Pool FLUSHING INLET


Pipe Size	Pol. Bronze	C. P.	W. M.	Approx. Wt. Lbs.
A				
1 1/2-2-2 1/2"	\$21.00	\$24.80	\$26.20	7

For same service as Z-840.





Z-850



I.P.S. Inlet


Swimming Pool FLUSHING INLET - bronze

FIG. Z-850


Pipe Size	Pol.	C. P.	W. M.	Approx. Wt. Lbs.
A				
1 1/2"-2 1/2"	\$14.00	\$15.60	\$18.00	6

For same service as Z-845. Has anchorage provision.


Neck 2 3/8" Not IPS Thread



Z-855



I.P.S. Outlet

DETAIL-"A"
Flow Regulating Device

Swimming Pool RECIRCULATING FITTING


FIG. Z-855

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	C. P. add	W. M. add	Approx. Wt. Lbs.
A						
1 1/2"-2"	\$13.60	\$19.20	\$28.80	\$2.00	\$ 3.00	14
3"	18.60	25.10	42.40	2.60	4.00	22
Clamping collar add	1.60	2.90	4.00			
Add for detail "A" when used with Z-855 Inlet Body						
1 1/2"-2"	6.40	7.40	9.60			
3"	9.60	11.20	14.40			
Detail "A" flow regulating device only						
1 1/2"-2"	13.40	13.40	16.00			
3"	20.60	22.20	24.00			

Pipe Size	B	C	D
A			
1 1/2"-2"	4"x4"	6 3/4"	1"-2"
3"	6"x6"	8"	1"-2"

Hub or spigot connections available.

Detail "A" shows flow regulating device. Long body extends through wall. Anchorage flange provided.




Z-865—I.P.S. Outlet


Swimming Pool Vacuum Cleaning Connection

FIG. Z-865

Pipe Size	E	J	Coated (DC)	Galv. (G)	All Bronze (BR)	C. P. add	W. M. add	Approx. Wt. Lbs.
A								
1 1/2"-2"	2 1/2"	1 1/2"-2"	\$16.80	\$22.10	\$24.80	\$2.10	\$3.20	13
3"	2 3/4"	1 1/2"-2"	18.40	24.00	28.80	2.10	3.20	14
4"	2 3/4"	1 1/2"-2"	20.00	26.90	31.20	2.10	3.20	15
Clamping collar add			1.50	2.70	4.00			
Plug add			1.60	1.60	1.60	1.30	1.60	



Z-895—I.P.S. Inlet



Pipe Size


A
1 1/2"-3/4"-1"

CHLORINE SPRAY INLET - bronze


FIG. Z-895

Pol. Face	C. P. add	W. M. add	Approx. Wt. Lbs.
\$19.80	\$2.80	\$4.00	2

An inexpensive manner of introducing chlorine into pool.



Z-900



I.P.S. Inlet and Outlet

SWIMMING POOL HAIR INTERCEPTOR, Cast Iron


FIG. Z-900

Pipe Size	A	B	C	D	E	F	Coated (DC)	Galv. (G)
2"	9 $\frac{3}{16}$ "	3 $\frac{3}{4}$ "	5 $\frac{1}{2}$ "	15 $\frac{7}{16}$ "	21 $\frac{1}{4}$ "		\$117.00	\$152.10
3"	12 $\frac{1}{4}$ "	5 $\frac{1}{2}$ "	7 $\frac{1}{2}$ "	17 $\frac{3}{4}$ "	26 $\frac{1}{8}$ "		117.00	152.10
4"	16 $\frac{7}{8}$ "	7 $\frac{1}{8}$ "	10 $\frac{5}{8}$ "	25 $\frac{5}{16}$ "	36 $\frac{1}{8}$ "		117.00	152.10


Approx. Wt. Lbs. 2"—50, 3"—80, 4"—95.

"F" dimension—space required for basket removal

Clamp cover provides quick opening and closing. Tested for 250 lbs. pressure for working pressures of 125 lbs. Furnished with air relief valve. Bottom cleanout.



Z-902



I.P.S. Connections

SWIMMING POOL HAIR INTERCEPTOR

FIG. Z-902

Pipe Size	All Bronze (BR)	Approx. Wt. Lbs.
A 1 $\frac{1}{2}$ "	\$70.00	16


Spare Basket \$20.00; Spare Tube \$20.00

Screen and condition of fluid readily examined through lucite tube. Screen set eccentrically with respect to body minimizes pressure drop. Interceptor is supportable in pipe line in any position. Flow may be in either direction through it. Interceptor may be completely disassembled for cleaning and is therefore sanitary. Cleanouts at top and bottom so interceptor may be drained prior to cleaning. Open area ratio 11:1.


ACID RESISTING PRODUCTS

HI-SIL


Acid Resisting Floor Drains




Z-5501



Z-5687



Z-7081 & Z-9058




Z-9334

Fig. No.	Size Outlet Inches	Wt. Lbs.	Price With Strainer	Extra Strainer Price	A In.	B In.	C In.	D In.	E In.	F In.	Flashing Ring
Z-5500	2-3-4-6	45	\$42.00	\$7.50							No
Z-5501	2-3-4-6	45	64.50	7.50							Yes
Z-7081-A	1 $\frac{1}{2}$	35	49.20	4.10	4	6 $\frac{1}{2}$	3 $\frac{7}{8}$	1 $\frac{1}{2}$	10 $\frac{3}{8}$	9	No
Z-7081-B	2	37	49.20	4.10	4	6 $\frac{1}{2}$	3 $\frac{7}{8}$	1 $\frac{1}{2}$	10 $\frac{3}{8}$	9	No
Z-9058-3	3	70	120.00	7.50	8	9	5 $\frac{7}{8}$	1 $\frac{1}{2}$	14	14 $\frac{1}{2}$	No
Z-9058-4	4	73	120.00	7.50	8	9	6 $\frac{3}{8}$	1 $\frac{1}{2}$	14	14 $\frac{1}{2}$	No
Z-5687	2-3-4-6	53	60.00	7.20							No
Z-5687-A	2-3-4-6	53	79.00	7.20							Yes
Z-9334	2	37	58.00	7.50							No




Hi-Sil Acid Resisting Traps



NON-SYPHON P TRAPS

Fig. No.	Size A Inches	Price	B In.	C In.	D In.	E In.
Z-7268	1½	\$28.40	8	4½	6¾	5¼
Z-7269	2	33.60	8	5½	6	9


Approx. Wt. Lbs. Fig. No. Z-7268—18, Fig. No. Z-7269—31.



DRUM TRAPS

Fig. No.	Size In.	Price	A In.	B In.	D In.	E In.	G In.
Z-5498	1½	\$57.65	11	2¾	4	9¾	2¾
Z-6165	2	58.55	11¾	2¾	4½	10¾	2¾


Approx. Wt. Lbs. Fig. No. Z-5498—28, Fig. No. Z-6165—31.



LONG SINK TRAPS

Fig. No.	Size Inches	Price	A In.	B In.
Z-5419-A	1½	\$22.00	6¾	4¼
Z-7075	2	26.00	7¾	5


Approx. Wt. Lbs. Fig. No. Z-5419-A—12, Fig. No. Z-7075—27.

ACID RESISTING
BACKWATER
VALVES
PALMER TYPE

Size Inches	Price
3	\$25.00
4	47.00
6	89.00
8	98.00

Price does not include tee.


Hi-Sil Acid Resisting Miscellaneous Products



Z-5045, Z-5070, Z-5095 and Z-5144

ACID RESISTING INSERTABLE JOINTS

Fig. No.	Size, Inches	A—Inches	B—Inches	Price	Weight, Lbs.
5045	2	7¾	6½	\$7.50	11
5070	3	8¾	7¾	9.80	16
5095	4	9½	7¾	14.90	22
5144	6	9½	7¾	25.20	30


ACID RESISTING
CLEANOUT
PLUGS

Size Inches	Weight Pounds	Price
1½	2¾	\$3.95
2	3½	4.70
3	6½	7.90
4	11	14.20
6*	14	19.55

*With bolted cover.

All Prices, Hi-Sil Acid Resisting Products, F.O.B. Erie, Pa. (No Freight Allowed)

TRAPS AND VALVES . . . Pages 53 to 63



Z-1000—I.P.S. Outlet

DEEP SEAL "P" TRAP


FIG. Z-1000

Pipe Size	A	E	G	H	J	K	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1 1/4"	2"	4 1/4"	6 7/8"	3 1/4" I.P.	2 1/2"	\$ 5.60	\$ 9.00	\$16.00	2	
1 1/2"	2 3/8"	4 3/4"	7 5/8"	3 1/4" I.P.	2 1/2"	6.20	10.60	17.60	3	
2"	1 3/4"	6 1/16"	9 1/2"	1 1/4" I.P.	4"	6.70	11.50	19.20	8	
3"	3"	7 1/2"	13"	1 1/4" I.P.	5"	10.60	17.00	25.60	17	
4"	4"	9 1/2"	15 1/16"	1 1/4" I.P.	5"	16.00	26.90	40.00	33	
For bronze cleanout plug add							1.60			

For bronze cleanout plug add

1.60

Designed for use with floor and area drains.



Z-1005—I.P.S. Outlet

DEEP SEAL TRAP WITH FLOOR LEVEL CLEANOUT

FIG. Z-1005

Pipe Size	Coated (DC)	Galv. (G)	If Backwater Device not Required, Deduct	Approx. Wt. Lbs.
2"	\$31.50	\$43.20	\$ 6.40	60
3"	49.50	66.60	9.60	70
4"	57.00	77.40	12.80	80

Drain not included in above prices.

Regularly furnished with backwater device. For use with any type floor or area drain.


J. A. ZURN MFG. CO., ERIE, PA., U.S.A.

FIG. Z-1010 SHALLOW SEAL "P" TRAP


Pipe Size	A	E	G	H	K	Coated (DC)	Galv. (G)	All Bronze (BR)
1 1/4"	3 5/8"	4 5/8"	3 5/8"	1 1/2"	1 1/2"	\$1.50	\$ 2.30	\$ 4.80
1 1/2"	3 11/16"	4 3/4"	3 11/16"	1 1/2"	1 1/2"	1.80	2.70	5.60
2"	5 3/8"	5 11/16"	4 1/4"	2"	2"	2.30	3.60	6.40
3"	7"	7"	8"	2"	2"	5.40	7.60	16.00
4"	7 1/2"	9 3/4"	5 1/2"	1"	1"	9.00	14.40	28.80

For brass cleanout, add 1.60
Approx. Wt. Lbs. 1 1/4"—2 1/2", 1 1/2"—3, 2"—5, 3"—13, 4"—35.

For use with any type floor drain where space limitation is important.



I.P.S. Outlet




Z-1010

FIG. Z-1015 COMBINED TRAP, B.W. SEWER VALVE AND CLEANOUT


Pipe Size	A	C	G	H	J	K	Coated (DC)	Deduct for Backwater Valve, if not desired
3"	5 1/4"	11 1/4"	15 7/8"	4"	4"	4"	\$30.00	\$ 9.00
4"	4 3/4"	13"	18"	4"	5"	5"	35.00	12.00

Approx. Wt. Lbs. 3"—35, 4"—42.

For use with any type floor or area drain.



I.P.S. Inlet and Spigot Outlet



Z-1015

FIG. Z-1021 AUTOMATIC TRAP-PRIMER

Furnished with 1/2" or 3/4" I. P. Connections—\$10.00


Union Connection—Price on Application

To provide any Drain with Primer Connection, add to list prices \$2.50


Approx. Wt. Lbs. 2

Provides the only means of maintaining proper and constant seal in basement floor drain traps and other traps used infrequently. Seldom used traps tend to lose their seals by evaporation. Primer is installed in a frequently used water supply line, and connected to the trap. (See dimensional diagram to the right) Flow is from left to right; water enters the primer, forces the diaphragm upward, and opens the valve, allowing water to replenish the trap seal. The diaphragm, with flat valve seat, insures that "liming" and other hard water deposits will not freeze the plunger. Tapered flow regulator pin meters the water—as pressure increases, the pin rises, reducing the flow.

Prevents foul and unsanitary sewer odors from entering the building. Complies with all modern plumbing and sanitary codes.



"A"—1/2", 3/4" "B"—1/2"
Width—I.P.S.—3 3/4" Union Conn.—6 3/4"




Z-1021—I. P. Connection Patented

FIG. Z-1030 PIPE ADAPTER

Iron Pipe to Soil Hub

Pipe Size	B	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
2"	4"	\$ 2.00	\$ 3.00	\$ 4.90	3
3"	4 1/2"	2.80	4.20	7.00	5
4"	4 3/4"	4.20	6.30	10.50	6
5"	4 1/4"	5.30	8.80	13.20	8
6"	4 1/4"	6.30	10.20	15.80	9
8"	4 1/4"	9.00	13.50	22.40	15




Z-1030


FIG. Z-1035 PIPE ADAPTER—45°

Iron Pipe to Soil Hub

Pipe Size	C	D	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
2"	2"	3"	2.50	\$ 3.60	\$ 5.70	4
3"	2 3/8"	4"	3.40	5.00	8.00	6
4"	3"	4 1/2"	4.90	7.30	12.00	7
5"	2 1/2"	3 3/4"	6.30	10.00	15.00	9
6"	2 1/2"	3 3/4"	7.50	11.70	18.00	12
8"	4"	5 5/8"	10.00	15.50	26.20	20



Z-1035




Z-1040

PIPE ADAPTER

Iron Pipe to Soil Spigot

FIG. Z-1040

Pipe Size	B	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
2"	6 1/2"	\$1.30	\$ 2.00	\$ 3.10	2
3"	6 1/2"	1.80	2.80	4.40	4
4"	6 1/2"	2.70	4.70	7.00	6
5"	6 1/2"	3.70	6.50	9.80	8
6"	6 1/2"	4.80	8.30	12.60	10
8"	6 1/2"	7.90	13.90	21.00	17




Z-1041

PIPE ADAPTER—45°

Iron Pipe to Soil Spigot

FIG. Z-1041

Pipe Size	D	E	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
2"	2"	6"	\$2.10	\$ 3.50	\$ 5.60	3
3"	2 1/2"	6"	3.20	5.50	8.40	7
4"	2 3/4"	6"	4.80	8.30	12.60	10
5"	3"	6"	5.80	10.20	15.40	12
6"	3 1/2"	6"	7.40	12.80	19.60	16




Z-1042

PIPE ADAPTER—90°

Iron Pipe to Soil Spigot

FIG. Z-1042

Pipe Size	B	C	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
2"	2 3/4"	6"	\$ 2.70	\$ 4.70	\$ 7.00	5
3"	3 3/4"	7"	3.90	6.70	10.50	8
4"	4"	8"	6.90	11.90	18.20	14
5"	5"	8 1/2"	8.40	14.70	22.40	16
6"	5 1/2"	9"	10.00	17.40	26.60	17



Z-1090

BACKWATER VALVE



FIG. Z-1090

Pipe Size	A	B	E	G	J	K	Coated (DC)	Approx. Wt. Lbs.
2"		4 1/8"	4 1/2"	7"	5"	2 7/8"	\$ 18.00	23
3"		5 1/4"	5 1/8"	7 7/8"	6"	3 5/8"	22.50	30
4"		6 1/8"	5 5/8"	8 1/2"	6 5/8"	4 1/16"	31.50	34
5"		7 1/4"	6 1/8"	9 1/2"	7 3/16"	4 5/8"	46.50	50
6"		8 5/16"	6 5/8"	10"	7 3/4"	5 1/8"	54.00	57
8"		10"	6 7/8"	11 3/4"	9 1/2"	6 3/16"	90.00	79
10"		12 1/2"	8"	12 7/8"	10 3/4"	7 3/8"	216.00	102
12"		14 3/8"	9 5/8"	13 3/8"	11 3/4"	9"	270.00	180
15"		16 3/4"	10 3/4"	17 1/2"	14 3/4"	10 3/4"	594.00	325
18"	Dimensions on request						738.00	
24"	Dimensions on request						1350.00	
30"	Dimensions on request						3060.00	

Non-fouling swing gate and clean sweep waterways. For main sewer lines in buildings to protect from back flow of sewage or heavy rainfall.

FIG. Z-1091 BACKWATER VALVE—OPEN TYPE

Pipe Size			C.I. Body and Bronze Valve Assembly	With Flanged Ends	Approx. Wt. Lbs.
A	C	H			
2"	5 1/2"	4 1/2"	\$ 14.40	\$ 17.30	10
3"	6 1/2"	5"	18.00	21.60	12
4"	7 1/2"	5"	25.20	30.30	15
5"	8 1/2"	5 1/4"	37.50	45.00	20
6"	9 1/2"	5 1/4"	43.20	51.90	23
8"	11 1/2"	6"	72.00	86.40	42
10"	13 1/2"	7"	172.80	207.40	58
12"	15 1/2"	8 1/2"	216.00	266.40	70
15"	17 1/2"	12 1/2"	475.20	570.30	120
18"	Dimensions on request		590.40	708.50	
24"	Dimensions on request		1080.00	1286.00	
30"	Dimensions on request		2440.80	2936.60	



Z-1091


For use in a manhole at end of sewer line, settling basins, etc., as protection against tidewater and flood.

Soil Pipe Connection

FIG. Z-1095 BACKWATER VALVE

Pipe Size	Coated (DC)	Approx. Wt. Lbs.	Pipe Size	Coated (DC)	Approx. Wt. Lbs.
A			A		
2"	\$ 29.70	23	5"	\$ 72.00	50
3"	35.10	30	6"	79.20	57
4"	43.20	34	8"	118.80	79
			10"	270.00	102
			12"	345.00	180

Pipe Size	B.I.P.S.	E	G	J	K
A					
2"	4"	4"	7"	5"	27 7/8"
3"	5"	4 5/8"	7 7/8"	6"	35 5/8"
4"	6"	5 1/8"	8 1/2"	6 5/8"	41 1/8"
5"	7"	5 5/8"	9 1/2"	7 3/16"	45 5/8"
6"	8"	7 1/8"	10"	7 3/4"	51 1/8"
8"	10"	7 1/8"	11 3/4"	9 1/2"	63 3/16"
10"	12"	8"	12 7/8"	10 3/4"	73 3/8"
12"	14"	9 5/8"	13 3/8"	11 3/4"	9"





Z-1095

For same service as Z-1090. Bronze removable cover provides extension of cleanout in deep sewers to floor level.

**FIG. Z-1100 RESIDENCE AND APARTMENT HOUSE BATH TRAP
SELF-CLEANING**

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1 1/2"	\$5.40	\$8.30	\$12.20	9

Unique design causes swirling current which washes inside walls and completely changes the water seal with each discharge from the tub. Full depth of water seal guards the cover from foul odors from the sewer line. No back siphonage. Extra large cleanout.




Z-1100

**FIG. Z-1101 RESIDENCE AND APARTMENT HOUSE BATH TRAP
SELF-CLEANING**

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1 1/2"	\$6.60	\$10.70	\$16.00	11

Unique design causes swirling current which washes inside walls and completely changes the water seal with each discharge from the tub. Full depth of water seal guards the cover from foul odors from the sewer line. No back siphonage. Extra large cleanout.




Z-1101

(Continued on following page)



(Continued from preceding page)




Z-1102

RESIDENCE AND APARTMENT HOUSE BATH TRAP **FIG. Z-1102**
SELF-CLEANING

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1 1/2"	\$ 9.90	\$14.80	\$19.50	12


Unique design causes swirling current which washes inside walls and completely changes the water seal with each discharge from the tub. Full depth of water seal guards the cover from foul odors from the sewer line. No back siphonage. Extra large cleanout.



Z-1103

RESIDENCE AND APARTMENT HOUSE BATH TRAP **FIG. Z-1103**
SELF-CLEANING

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1 1/2"	\$9.00	\$13.70	\$18.60	12




Z-1105

DWELLING HOUSE BATH TRAP **FIG. Z-1105**
SELF-CLEANING

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1 1/2"	\$5.40	\$8.30	\$12.20	9


Unique design causes swirling current which washes inside walls and completely changes the water seal with each discharge from the tub. Full depth of water seal guards the cover from foul odors from the sewer line. No back siphonage. Extra large cleanout.



Z-1106

DWELLING HOUSE BATH TRAP **FIG. Z-1106**
SELF-CLEANING


Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1 1/2"	\$6.80	\$11.50	\$17.00	11



Z-1107

DWELLING HOUSE BATH TRAP **FIG. Z-1107**
SELF-CLEANING

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1 1/2"	\$9.90	\$14.80	\$19.50	11



Z-1108

DWELLING HOUSE BATH TRAP **FIG. Z-1108**
SELF-CLEANING

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1 1/2"	\$7.20	\$10.40	\$14.10	11


(Continued on following page)

(Continued from preceding page)

FIG. Z-1110 FEDERAL HOUSING ADJUSTABLE BATH TRAP SELF-CLEANING

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1½"	\$ 6.30	\$ 9.90	\$15.40	13


Unique design causes swirling current which washes inside walls and completely changes the water seal with each discharge from the tub. Full depth of water seal guards the cover from foul odors from the sewer line. No back siphonage. Extra large cleanout.



Z-1110

FIG. Z-1111 FEDERAL HOUSING ADJUSTABLE BATH TRAP SELF-CLEANING


Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1½"	\$ 7.60	\$12.40	\$19.20	14



Z-1111

FIG. Z-1115 FEDERAL HOUSING ADJUSTABLE BATH TRAP SELF-CLEANING

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1½"	\$ 8.70	\$12.70	\$17.90	13




Z-1115

FIG. Z-1120 HOTEL TUB AND SHOWER TRAP SELF-CLEANING, RAPID FLOWING

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
2"	\$ 8.30	\$12.60	\$20.80	20


Designed especially to carry off drainage discharge rapidly with minimum fouling. Incorporates same features as in Z-1100.



Z-1120

FIG. Z-1121 HOTEL TUB AND SHOWER TRAP SELF-CLEANING, RAPID FLOWING


Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
2"	\$10.00	\$14.80	\$22.70	20



Z-1121

(Continued on following page)

(Continued from preceding page)




Z-1125

**COLLECTIVE DWELLINGS BATH TRAP
UNIVERSAL ADJUSTMENT**

FIG. Z-1125

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1 1/2"	\$ 5.40	\$10.70	\$16.80	7

Adjustable inlet—swivel return bend; any lateral direction. Adjustable outlet—any lateral direction. Adapters supplied for lead or soil pipe.




Z-1126

**COLLECTIVE DWELLINGS BATH TRAP
UNIVERSAL ADJUSTMENT**

FIG. Z-1126

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1 1/2"	\$ 8.60	\$14.20	\$18.90	8




Z-1127

**COLLECTIVE DWELLINGS BATH TRAP
UNIVERSAL ADJUSTMENT**

FIG. Z-1127

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1 1/2"	\$4.20	\$8.30	\$12.90	4




Z-1128

**COLLECTIVE DWELLINGS BATH TRAP
UNIVERSAL ADJUSTMENT**

FIG. Z-1128

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1 1/2"	\$ 5.90	\$ 9.00	\$15.00	3



Z-1130

**HOSPITAL BATH TRAP
SELF-CLEANING, NON-SIPHONING**

FIG. Z-1130

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1 1/2"	\$ 7.60	\$14.40	\$24.10	9

Severest siphonic pull will not drain water seal. Self-cleansing of all inside walls. Water seal guards cleanout plug against foul odors.

(Continued on following page)

(Continued from preceding page)

FIG. Z-1133 HOSPITAL BATH TRAP
SELF-CLEANING, NON-SIPHONING

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1½"	\$ 7.50	\$14.40	\$24.10	9




FIG. Z-1135 HOSPITAL BATH TRAP
SELF-CLEANING, NON-SIPHONING

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1½"	\$ 7.20	\$16.00	\$25.50	6




FIG. Z-1138 HOSPITAL BATH TRAP
SELF-CLEANING, NON-SIPHONING

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1½"	\$ 7.20	\$16.00	\$25.50	6




FIG. Z-1140 HOSPITAL ADJUSTABLE BATH TRAP
SELF-CLEANING, NON-SIPHONING

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1½"	\$ 10.10	\$19.60	\$34.30	10

Severest siphonic pull will not drain water seal. Self-cleansing of all inside walls. Water seal guards cleanout plug against foul odors.






FIG. Z-1143 HOSPITAL ADJUSTABLE BATH TRAP
SELF-CLEANING, NON-SIPHONING

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Approx. Wt. Lbs.
1½"	\$10.10	\$19.60	\$34.30	11




(Continued on following page)



Z-1145

Pipe Size
1 1/2"Coated
(DC)
\$ 7.50Galv.
(G)
\$16.20All Bronze
(BR)
\$25.60Approx.
Wt. Lbs.
6**HOSPITAL ADJUSTABLE BATH TRAP**
SELF-CLEANING, NON-SIPHONING

FIG. Z-1145



Z-1148

Pipe Size
1 1/2"Coated
(DC)
\$ 8.70Galv.
(G)
\$18.60All Bronze
(BR)
\$29.50Approx.
Wt. Lbs.
6**HOSPITAL ADJUSTABLE BATH TRAP**
SELF-CLEANING, NON-SIPHONING

FIG. Z-1148



Z-1160


**RESEALING LAVATORY TRAP**

FIG. Z-1160

Pipe Size	A	C	D	E	Pol. Bronze	Chrome Pl. Bronze	Approx. Wt. Lbs.
1 1/4"		3 5/8"	6 1/8"	2"	\$10.20	\$12.90	3
1 1/2"		4 1/4"	6 5/8"	2 1/2"	11.70	15.00	4

Severest siphonic pull will not drain water seal. Ground face union connection permits disconnection at any time with free access to trap or waste line. Self-cleansing of inside walls. Eliminates need for separate vent.


Z-1161—Tubing Inlet
and I.P.S. OutletPipe Size
A
1 1/4"
1 1/2"C
3 5/8"
4 1/4"D
6 1/8"
6 5/8"E
7"
7 3/8"Pol. Bronze
\$11.70
13.50Chrome Pl. Bronze
\$15.00
17.40Approx. Wt. Lbs.
3 1/2
4 1/2**RESEALING LAVATORY TRAP**

FIG. Z-1161


Z-1163—Tubing Inlet
and OutletPipe Size
A
1 1/4"
1 1/2"C
3 3/8"
4 1/4"D
6 1/8"
6 5/8"E
7"
7 3/8"H
7 3/4"
7 3/4"Pol. Bronze
\$13.50
16.20Chrome Pl. Bronze
\$16.20
19.50Approx. Wt. Lbs.
4
5**RESEALING LAVATORY TRAP**

FIG. Z-1163


(Continued on following page)



(Continued from preceding page)

FIG. Z-1164 RESEALING LAVATORY TRAP

Pipe Size	C	D	E	G	Pol. Bronze	Chrome Pl. Bronze	Approx. Wt. Lbs.
A							
1 1/4"	3 5/8"	25"	7"	2"	\$13.50	\$17.40	4
1 1/2"	4 1/4"	25"	7 3/8"	2"	16.20	21.20	5



Z-1164

FIG. Z-1167 ADJUSTABLE BRONZE BATH TRAP


Pipe Size	A	D Min.-Max.	E Min.-Max.	Approx. Wt. Lbs.
1 1/4" Iron Pipe, I.P.S. Inlet and Outlet		5 3/4"—8 1/2"	2"—4 3/4"	5
1 1/2" Iron Pipe, I.P.S. Inlet and Outlet		5 3/4"—8 1/2"	2"—4 3/4"	5



Z-1167, Z-1167-1

FIG. Z-1167-1 ADJUSTABLE BRONZE BATH TRAP


Pipe Size	A	D Min.-Max.	E Min.-Max.	Approx. Wt. Lbs.
1 1/4" Iron Pipe—With Shield, I.P.S. Inlet and Outlet		5 3/4"—8 1/2"	2"—4 3/4"	7
1 1/2" Iron Pipe—With Shield, I.P.S. Inlet and Outlet		5 3/4"—8 1/2"	2"—4 3/4"	7



Z-1167, Z-1167-1

FIG. Z-1167L ADJUSTABLE BRONZE BATH TRAP

Pipe Size	A	D Min.-Max.	E Min.-Max.	Approx. Wt. Lbs.
1 1/4" Lead Pipe, Hub Inlet and Outlet		5 3/4"—8 1/2"	2"—4 3/4"	5
1 1/2" Lead Pipe, Hub Inlet and Outlet		5 3/4"—8 1/2"	2"—4 3/4"	5



Z-1167L, Z-1167L-1

FIG. Z-1167L-1 ADJUSTABLE BRONZE BATH TRAP


Pipe Size	A	D Min.-Max.	E Min.-Max.	Approx. Wt. Lbs.
1 1/4" Lead Pipe—With Shield, Hub Inlet and Outlet		5 3/4"—8 1/2"	2"—4 3/4"	7
1 1/2" Lead Pipe—With Shield, Hub Inlet and Outlet		5 3/4"—8 1/2"	2"—4 3/4"	7

FIG. Z-1168 ADJUSTABLE BRONZE BATH TRAP

Pipe Size	A	Approx. Wt. Lbs.
1 1/4" Iron Pipe Outlet, Tubing Inlet		6
1 1/2" Iron Pipe Outlet, Tubing Inlet		6

FIG. Z-1168-1 ADJUSTABLE BRONZE BATH TRAP

Pipe Size	A	Approx. Wt. Lbs.
1 1/4" Iron Pipe Outlet, Tubing Inlet—With Shield		7
1 1/2" Iron Pipe Outlet, Tubing Inlet—With Shield		7




Z-1168, Z-1168-1

(Continued on following page)



(Continued from preceding page)



Z-1168L, Z-1168L-1

ADJUSTABLE BRONZE BATH TRAP

FIG. Z-1168L

Pipe Size A—1 1/4" Lead Pipe, Hub Outlet—Tubing Inlet.....	\$7.20	Approx. Wt. Lbs. 6
Pipe Size A—1 1/2" Lead Pipe, Hub Outlet—Tubing Inlet.....	7.80	6

ADJUSTABLE BRONZE BATH TRAP


FIG. Z-1168L-1

Pipe Size A—1 1/4" Lead Pipe, Hub Outlet, Tubing Inlet—With Shield.....	\$8.00	Approx. Wt. Lbs. 7
Pipe Size A—1 1/2" Lead Pipe, Hub Outlet, Tubing Inlet—With Shield.....	8.60	7

INTERCEPTORS . . . Pages 63 to 65

STANDARD MODEL CAST IRON GREASEPTOR With Patented Flow Control Tee

FIG. Z-1170



Size No.	**G.P.M. Rated Capacity	**Lbs. Grease Capacity
100	4	8
200	6	12
300	9	18
400	14	28
400LT	22	44
500	20	40
600	25	50
600LT	30	60
700	40	80

J I.P.S.	B	B'	C	D	E	A I.P.S.	Sani-Coated
1 1/2"*, 2"	17 3/4"	9 3/4"	3 3/4"	10"	7 1/4"	2"	\$ 37.50
1 1/2"*, 2"	19 1/4"	12 1/8"	3 5/8"	11 1/8"	8 1/8"	2"	52.50
1 1/2"*, 2"	22"	14 1/4"	3 3/4"	11 3/4"	8 1/2"	2"	90.00
1 1/2"*, 2", 3"	24"	17"	3 3/4"	13 1/4"	8 3/4"	2", 3"	124.50
1 1/2"*, 2"	21 3/8"	14 1/4"	2 3/4"	12 1/4"	2 3/4"	2"	199.50
1 1/2"*, 2", 3", 4"	27 3/8"	17 1/2"	4 1/2"	14 3/4"	10 1/4"	2", 3", 4"	184.50
1 1/2"*, 2", 3", 4"	30 3/4"	20 1/4"	4 3/8"	16 5/8"	12 1/8"	2", 3", 4"	291.00
1 1/2"*, 2", 3"	26 1/4"	17 7/8"	3 3/8"	12 3/4"	3 3/8"	2", 3"	306.00
2", 3", 4"	32 1/2"	23"	4 1/4"	18 1/2"	14"	2", 3", 4"	505.50

Approx. Wt. Lbs. 100—71, 200—91, 300—139, 400—188, 500—216, 600—331, 700—464, 400LT—135, 600LT—230.

Soil pipe connections available

Larger sizes for special applications available to specification.

*Recommended I. P. Sizes.

Z-1170—Standard Greaseptor

Flow Control Tee


Furnished on all Sizes and Types.

Z-1171—Deluxe—Cover Removable With Basket

**Flowrate and grease capacities listed are with controlled flow, at 90% rated average efficiency as tested in accordance with War Department Standard Specifications for Temporary Housing, 8000 E, P-13, addenda No. 2—Specifications for Mobilization Construction Equipment P. E. 620 and War Dept. Corps of Engineers Tentative Specification P. E. 620, May 27, 1944.

Assures free flowing drainage through pipe lines at all times by intercepting, separating, accumulating and recovering grease from waste water lines.

Flow Control Tee furnished with every greaseptor; its use guarantees foolproof operation and maximum efficiency.



B'=WIDTH

Z-1170, Z-1171—C.I. Greaseptors-Dimensional Detail

DE LUXE MODEL CAST IRON GREASEPTOR With Patented Flow Control Tee

FIG. Z-1171

Size No.	A I.P.S.	B	B'	C	D	E	J I.P.S.	Sani-Coated
100	1 1/2"*, 2"	17 3/4"	9 3/4"	3 3/4"	10"	7 1/4"	2"	\$ 60.00
200	1 1/2"*, 2"	19 1/4"	12 1/8"	3 5/8"	11 1/8"	8 1/8"	2"	75.00
300	1 1/2"*, 2"	22"	14 1/4"	3 3/4"	11 3/4"	8 1/2"	2"	120.00
400	1 1/2"*, 2", 3"	24"	17"	3 3/4"	13 1/4"	8 3/4"	2", 3"	157.50
500	1 1/2"*, 2", 3", 4"	27 3/8"	17 1/2"	4 1/2"	14 3/4"	10 1/4"	2", 3"	225.00

Approx. Wt. Lbs. 100—67 1/2, 200—86 1/2, 300—132, 400—178 1/2, 500—205.

Soil pipe connections available

Larger sizes for special applications available to specification.

*Recommended I. P. Sizes.

Has integral vertical baffle, horizontal basket baffle and cover, easily removed for cleaning. Baffles are attached to cover.

ADD FOR PORCELAIN ENAMEL FINISH FIGS. Z-1170 AND Z-1171

Size No.	Inside or Outside	Size No.	Inside and Outside
100	\$ 54.00	100	\$ 72.00
200	60.00	200	84.00
300	84.00	300	120.00
400	111.00	400	187.50
400LT	111.00	400LT	187.50
500	204.00	500	294.00
600	270.00	600	345.00
600LT	270.00	600LT	345.00
700	285.00	700	390.00

FIG. Z-1171

"VGE" GREASEPTOR WITH Flow Control Tee


Size No.	*G.P.M. Rated Capacity	*Lbs. Grease Capacity	A I.P.S.	B	B'	C	D	E	J I.P.S.	V.G.E.
350—VGE	12	24	2"	25 1/2"	16 1/2"	4 1/4"	12 1/8"	9"	2"	\$124.50
450—VGE	18	36	2"	29"	19 1/2"	4 1/2"	15 1/4"	9 7/8"	2"	184.50
550—VGE	25	50	2"	33"	22 1/2"	4 5/8"	18 7/8"	12 7/8"	2"	291.00

Approx. Wt. Lbs. 350—76, 450—128, 550—171.


*At 90% rated average efficiency as tested in accordance with War Department Standard Specifications for Temporary Housing 8000 E, P-13, Addenda No. 2—Specifications for Mobilization Construction Equipment P. E. 620, and War Dept. Corps of Engineers Tentative Specification P. E. 620, May 27, 1944.

Made of Vitreous Glazed Earthenware. Impervious to thermal shock. Easily cleaned inside and out because of smooth surfaces; therefore thoroughly sanitary. Especially desirable for hospital and public eating facilities.

Flow Control Tee furnished with every "VGE" greaseptor—see details on page 63.



Z-1171—V.G.E. Greaseptor.
I.P.S. Inlet and Outlet




Z-1171—V.G.E. Greaseptor. I.P.S. Inlet and Outlet


FIG. Z-1175 HAIR INTERCEPTOR

Pipe Size A	B	C	D	Coated (DC)	All Bronze Pol. C. P.	Approx. Wt. Lbs
1 1/4-1 1/2"	6 3/4"	3 3/4"	5 5/8"	\$17.10	\$36.00 \$40.00	8

For barber shops, beauty parlors, clubs, dormitories, swimming pools, etc.; for sinks and lavatories in industrial or commercial usage. Perforated brass basket, removable for easy cleaning.



Slip Joint Tubing Inlet,
I.P.S. Outlet




Z-1175

FIG. Z-1175A HAIR INTERCEPTOR, Adjustable Outlet

Pipe Size A	B	D	E	Coated (DC)	All Bronze Pol. (CP)	Approx. Wt. Lbs.
1 1/4-1 1/2"	6 1/8"	9 1/2"	5 3/8"	\$17.10	\$36.00 \$40.00	9


Same service as Z-1175.



Z-1175A
Slip Joint Tubing Inlet,
I.P.S. Adjustable Outlet



Z-1180, Size No. 1



I.P.S. Inlet and Outlet

SOLIDS INTERCEPTOR, Size No. 1


FIG. Z-1180

Pipe Size	A	B	C	D	E	H	L	Capacity	
2"	8 1/8"	8 3/4"	2 5/8"	4 1/8"	11"	9 3/4"	158.8	cu. in.	\$60.00

Approx. Wt. Lbs. 2"—19.

Available in Cast Iron—Prices and Dimensions on Request.

Made of Vitreous China. Brass screen. Aluminum basket removable for easy cleaning. For hospital and dental sinks and laboratories where waste water contains plaster, metal, or abrasives.



Z-1180, Size No. 2, I.P.S. Inlet and Outlet

SOLIDS INTERCEPTOR, Size No. 2

FIG. Z-1180

Pipe Size	A	B	C	D	E	H	L	Capacity	Approx. Wt. Lbs.
2"	19 3/4"	19 3/4"	5 1/16"	5 1/16"	18 1/16"	22"	1964.5	cu. in.	\$135.00 135


Available in Cast Iron—Prices and Dimensions on Request.

Made of Vitreous Glazed Earthenware. Impervious to thermal shock. Brass screen. Aluminum basket removable for easy cleaning. Same service as Z-1180, Size No. 1.


CLEANOUTS . . . Pages 65 to 67

SUPREMO PERFECT SEAL CLEANOUTS AND CLEANOUT TEES

SUPREMO PERFECT SEAL CLEANOUT FIG. Z-1300



Z-1300—Perfect Seal Cleanout Patented



Z-1300

Pipe Size	With Rust-proofed C. I. Cover	With Bronze Cover	All Bronze	Approx. Wt. Lbs.
2"	\$ 1.60	\$ 2.70	\$ 4.60	2
3"	2.00	3.30	5.80	4
4"	2.30	4.00	6.80	5
5"	4.80	7.60	13.20	6
6"	6.80	10.20	19.90	8
8"	13.80	19.90	25.80	13
10"	21.60	28.50	36.80	20
12"	30.80	40.60	52.40	28

For all soil pipe cleanout openings in every type of building. Provides positive gas-tight and water-tight connection, yet won't stick in removal.

We suggest the following specifications for consideration in adopting these products to meet plumbing codes written around the old style brass and iron "Trap Screw Ferrule" idea:


"Where a joint is made by a metal to metal contact, equivalent to a ground joint, the plug may be of extra heavy cast iron rustproofed after the threads are cut, and the contact must be made with a non-corrosive metal."

(Continued on following page)

SUPREMO PERFECT SEAL CLEANOUTS (Continued)

FIG. Z-1305 Perfect Seal Cleanout, With Flush Cover

Pipe Size	With Rust-Proofed C. I. Cover	With Bronze Cover	All Bronze	Approx. Wt. Lbs.
2"	\$ 1.60	\$ 2.70	\$ 4.60	2
3"	2.00	3.30	5.80	3
4"	2.30	4.00	6.80	5
5"	4.80	7.60	13.20	7
6"	6.80	10.20	19.90	8
8"	13.80	19.90	25.80	13
10"	21.60	28.50	36.80	20
12"	30.80	40.60	52.40	28



Z-1315

FIG. Z-1315 SUPREMO PERFECT SEAL CLEANOUT TEE WITH RAISED COVER

Pipe Size	With Rust-Proofed C. I. Plug	With Bronze Plug	Approx. Wt. Lbs.
2"	\$ 4.40	\$ 5.30	7
3"	5.20	6.40	15
4"	6.10	7.70	16
5"	10.10	14.00	22
6"	13.80	16.50	35

Z-1315

A	B	C	D
2"	10"	4 3/8"	3"
3"	12"	5 1/2"	3 1/8"
4"	12"	5 3/4"	3 1/2"
5"	13"	6 1/2"	4 1/4"
6"	14"	7 1/16"	4 3/4"




Z-1326

Z-1315, Z-1320 For all installations of cleanout tees, vertical or horizontal, in any type of building.

FIG. Z-1326 SUPREMO PERFECT SEAL FLOOR LEVEL CLEANOUT


Pipe Size	C	D	Polished	C. P.	Approx. Wt. Lbs.
2"	5"	8 1/4"	\$ 6.10	\$ 7.80	7
3"	5"	8 1/4"	7.80	9.50	8
4"	6"	8 1/4"	9.50	11.30	12
5"	8"	8 1/4"	14.70	18.20	20
6"	8"	8 1/4"	18.40	21.90	26

For use in industrial plants and other buildings where cleanout openings occur in heavy traffic open areas. Adjustable top compensates for variations in floor surface.



Caulk Connection

FIG. Z-1310 PERFECT SEAL CLEANOUT WITH RUST-PROOFED C. I. COVER, BRONZE ACCESS PLATE AND SCREW




Z-1310

Z-1320 SUPREMO PERFECT SEAL CLEANOUT TEE WITH BRONZE ACCESS PLATE AND SCREW; RUST-PROOFED CAST IRON COVER.

Pipe Size	Plate Diam.	Pol.	C. P.	Approx. Wt. Lbs.
2"	5"	\$ 5.50	\$ 6.80	8
3"	5"	6.00	7.50	16
4"	7"	7.50	9.00	18
5"	7"	11.00	12.50	24
6"	7"	14.20	15.70	37

Z-1320

A	B	C	D	S
2"	10"	4 3/8"	3"	5 1/4"
3"	12"	5 1/2"	3 1/8"	5 1/4"
4"	12"	5 3/4"	3 1/2"	7 1/4"
5"	13"	6 1/2"	4 1/4"	7 1/4"
6"	14"	7 1/16"	4 3/4"	7 1/4"




Z-1320

FIG. Z-1327 AREAWAY CLEANOUT

Pipe Size	Coated (DC)	Galv. (G)	All Bronze (BR)	Bronze Rim and Cover Coated (CB)	Galv. (GB)	Approx. Wt. Lbs.
2"	\$15.00	\$25.20	\$57.60	\$25.50	\$37.80	24
3"	16.50	27.00	59.20	27.00	39.60	25
4"	18.00	28.80	60.80	28.50	41.40	26
Clamping collar, add	2.30	3.60	4.80	2.30	3.60	


For cleanouts in open areaways or as access to horizontal drainage lines.



Z-1327



Z-1329




HEAVY DUTY FLOOR LEVEL CLEANOUT

FIG. Z-1329

Pipe Size	B	C	D	Coated (DC)	Add for Galv. Housing	Approx. Wt. Lbs.
2"	6 3/4"	4 3/4"	8"	\$ 8.60	\$2.30	17
3"	6 3/4"	4 3/4"	8"	9.60	2.30	18
4"	6 3/4"	5 1/2"	8"	10.70	2.30	21
5"	8 3/4"	5 1/2"	8"	13.80	3.50	28
6"	8 3/4"	5 1/2"	8"	14.40	3.50	36
Cleanout housing only						
2-3-4				6.40	2.30	
5-6				8.00	3.50	

For cleanout openings occurring in open areas and subject to heavy traffic. Adjustable top eliminates need for accuracy of floor levels.




Z-1329-2

TRAFFIC CLEANOUT EXTENSION

FIG. Z-1329-2

Pipe Size	C	D	Coated (DC)	Cast Iron	Galv. (G)	Approx. Wt. Lbs.
2"	6 3/4"	8"	\$ 5.90		\$ 8.70	15
3"	6 3/4"	8"	7.20		10.80	16
4"	6 3/4"	8"	7.80		11.70	18
5"		on request	9.90		13.70	25
6"	8 3/4"	8"	11.70		17.60	30

Provides access to drain lines through factory floor. Cleanout plug protected by heavy deep flange, non-slip cover.



Z-1370


WALL ACCESS CLEANOUT

FIG. Z-1370

Pipe Size	B	1/4" Depth	1"	2"	Polished Bronze 3"	4"	5"	6"	Approx. Wt. Lbs.
1 1/2"	5"	\$ 5.30	\$ 8.80	\$16.30	\$17.90	\$19.20	\$20.80	\$23.20	4
2"	5"	5.90	9.30	16.70	18.30	19.70	21.30	23.70	5
3"	5"	8.00	10.30	17.40	18.80	20.20	21.80	29.60	6
4"	7"	12.20	12.60	18.10	19.40	20.80	22.80	35.50	8
5"	7"	17.60	17.90	26.20	28.20	30.10	33.90	51.20	11
6"	7"	20.30	20.50	30.70	33.60	35.80	37.40	54.70	15

Add for C. P.—15%
Add for W. M.—50%

Furnished with bronze cleanout plug tapped to accommodate bronze wall plate of desired depth. Fitting not furnished.



Z-1380

ACCESS CLEANOUT

FIG. Z-1380

Pipe Size	C	D	Pol.	All Bronze	C. P.	Approx. Wt. Lbs.
2"	5 1/2"	1"	\$ 5.80		\$ 7.70	3
3"	5 1/2"	1"	6.70		8.60	4
4"	6 3/4"	1"	7.70		9.60	5
5"	8"	1"	9.60		11.50	6
6"	9 1/2"	1"	11.50		13.40	8
8"	11 1/2"	1"	14.40		16.30	12

MISCELLANEOUS . . . Pages 68 to 69

FIG. Z-1381, Z-1382 DECK PLUG—NON-SLIP

Pipe Size	A	C	D	Machine Finish	All Bronze Pol.	C. P.	Approx. Wt. Lbs.
2"		4"-4 3/4"	1 1/4"-3 1/8"	\$ 7.20	\$ 9.40	\$11.40	3
3"		4 3/4"-6"	1 1/2"-3 1/8"	11.20	13.60	16.10	4
4"		6"-7 3/8"	1 1/2"-3 1/4"	13.20	16.40	18.90	6
5"		9 3/8"	1 3/4"-3 1/2"	21.60	25.20	28.60	10
6"		9 3/8"	1 3/4"-3 1/2"	33.60	37.20	41.20	12
8"***		11"	2"	60.00	72.00	80.00	18

Provides floor cleanout where flush finish with floor level is desired. Non-slip safety top for exposed installations.


*Caulk dimensions

**Available I.P.S. only

Note: specify Z-1382 for caulk connection



Z-1382
Caulk Connection




Z-1381—I.P.S. Connection

FIG. Z-1385 ACCESS BOX—HINGED COVER

A	B	C	Coated (DC)	Galv. (G)	All Bronze Pol.	C. P.	Approx. Wt. Lbs.
6x6"	1 3/4"	4"	\$1.80	\$ 3.10	\$ 6.40	\$ 8.60	3
8x8"	1 3/4"	6"	2.40	4.10	8.80	11.30	5
10x10"	1 3/4"	7"	6.60	11.20	18.00	21.50	7
12x12"	1 3/4"	10"	9.00	15.10	24.00	29.00	11

Non-slip carborundum surface—same price as chrome (C.P.)

Floor or Wall access to valves, pipe-lines, shut-off cocks, hose connections.



Z-1385

FIG. Z-1385-1 ACCESS BOX—SECURED COVER


A	B	C	Coated (DC)	Galv. (G)	All Bronze Pol.	C. P.	Approx. Wt. Lbs.
6x6"	7x7"	1"	\$1.80	\$ 3.10	\$ 5.40	\$ 7.60	3
8x8"	9x9"	1"	2.40	4.10	7.80	10.30	5
10x10"	11x11"	1"	5.80	10.20	16.20	19.70	6 1/2
12x12"	13x13"	1"	8.20	14.10	21.10	26.10	10

Non-slip carborundum surface—same price as chrome (C.P.)

Floor or Wall access to valves, pipe-lines, shut-off cocks, hose connections.

Anchorage Lugs assure secure installation.

Full size opening for Handhole.




Z-1385-1


FIG. Z-1386 ACCESS BOX AND VENT

Pipe Size	Coated (DC)	Galv. (G)	Approx. Wt. Lbs.
4"	\$8.40	\$14.10	17

Relief vent on drainage system. Will prevent entry of sticks, etc., without retarding access of ample free air. Removable access cleanout.



Z-1386




Z-1386A—Caulk Connection

VENT BOX

FIG. Z-1386A

Pipe Size	B	D	E	Coated (DC)	Galv. (G)	Bronze Grate	Approx. Wt. Lbs.
A							
4"	6 3/4" Sq.	4"	2"	\$ 7.50	\$13.50	\$22.50	25

Unique cover design prevents insertion of large objects. Provides outside air to plumbing system or building interior.




Z-1387—Caulk Connection

VENT BOX

FIG. Z-1387

Pipe Size	Coated (DC)	Galv. (G)	Approx. Wt. Lbs.
A			
4"	\$7.50	\$13.50	8

Consists of outside vent ring and secured center cleanout, removable only with special tool. Removable center plate allows cleaning. Same service as Z-1386A.



Z-1388—I.P.S. Connection


FRESH AIR INLET

FIG. Z-1388

Pipe Size	B	D	Pol.	All Bronze	C. P.	Approx. Wt. Lbs.
A						
3"	5 1/2"	1"	\$ 9.60		\$12.80	5
4"	6 3/4"	1"	11.50		14.70	6
*4"	8"	1 3/4"	16.00		20.80	10
5"	8"	1"	20.80		25.00	15
6"	9 1/2"	1"	23.00		30.70	18

*Denotes New York State Specification

For boiler rooms, garages, laundries.



Z-1389

FRESH AIR INLET

FIG. Z-1389

Pipe Size	Pol.	All Bronze	C. P.	Approx. Wt. Lbs.
A				
4"	\$4.80		\$8.00	2


Provides simple and secure means for covering outside vent pipes.

HYDRANTS . . . Pages 70 to 75

FIG. Z-1392 PARK SPRINKLING VALVE AND CONTROL BOX, Frost Proof

Pipe Size	A	H	Iron Box and Top		Iron Box and Bronze Top		Approx. Wt. Lbs.
			I. S.	B. S.	I. S.	B. S.	
3/4"	36"		\$53.20	\$70.20	\$66.20	\$ 82.20	82
3/4"	48"		55.70	78.50	67.70	90.50	86
3/4"	60"		56.20	88.20	69.20	100.20	90
1"	36"		65.60	88.80	79.10	100.80	85
1"	48"		67.10	98.60	80.60	110.60	89
1"	60"		68.60	108.30	82.10	120.30	93

For school grounds, public parks, golf courses, swimming pools, and other locations where large control boxes are desirable for housing additional valves and connections for drinking fountains or other fixtures. Non-freezing valve, removable for repair without digging up connections.



Z-1392—I.P.S. Inlet, Hose Connection

FIG. Z-1395 WALL HYDRANT


A	B	C	D	Approx. Wt. Lbs.
3/4"	2"	as spec.	5 1/2"	
1"	2 1/2"	as spec.	5 1/2"	
A—3/4" Size—Polished bronze face				
Wall Thickness	Galv. Casing	Brass Casing	Approx. Wt. Lbs.	
9"	\$16.50	\$19.70	7	
11"	17.50	20.90	7 1/2	
13"	18.50	22.10	8	
15"	19.50	23.30	9	
16"	20.00	23.90	9 1/2	
18"	21.00	25.00	10	
20"	22.00	26.20	10 1/2	
22"	23.00	27.40	11	

A—1" Size—Polished bronze face							
Wall Thickness	Galv. Casing	Brass Casing	Approx. Wt. Lbs.	Wall Thickness	Galv. Casing	Brass Casing	Approx. Wt. Lbs.
9"	\$22.40	\$25.00	9	24"	\$31.40	\$35.50	13½
11"	23.60	26.40	9½	26"	32.60	36.90	14
13"	24.80	27.80	10	28"	33.80	38.30	14½
15"	26.00	29.20	11	30"	35.00	39.70	15
16"	26.60	29.90	11½	32"	36.20	41.10	15½
18"	27.80	31.30	12	34"	37.40	42.50	16
20"	29.00	32.70	12½	36"	38.60	43.90	16½
22"	30.20	34.10	13				

Chrome plated face add 1.90
White metal face add 2.90



Z-1395





I.P.S. Inlet, Hose Connection

For outside hose connection to prevent freezing or tampering with valve. For public buildings, institutions, etc. Valve removable for repair without digging up connections.

FIG. Z-1400 CAP CLOSURE

Type	Pipe Size		C	D	All Bronze		Approx. Wt. Lbs.
	A	B			Pol.	C. P.	
Type "S"	3/8"	1 1/4"	3/8"	7/8"	\$1.10	\$1.30	1 1/2
Type "W"	1 1/2"	3"	1"	1 1/2"	2.70	3.20	1 1/2


For use where water supply connections for future use are desired. Counter-sunk head on face for easy removal.



Z-1400



Z-1405



SYPHON PREVENTER

FIG. Z-1405

Complete, Each \$16.00
Approx. Wt. Lbs. 6.

For emergency use on existing installations where siphonic action has developed on waste or vent lines. A simple vent relief which automatically releases entrained air in any vent line or chamber such as old type grease traps, etc.


Z-1480—I.P.S. Inlet,
Hose ConnectionCOMPRESSION VALVE DRY PIPE HYDRANT,
Full-Covered Casing

FIG. Z-1480



Depth		Approx.		Approx.	Pipe Size		
H	3/4"	Wt. Lbs.	1"	Wt. Lbs.	A	D	E
2'	\$21.60	30	\$40.50	35	3/4"	18"	8 5/16"
3'	22.50	33	41.70	38	1"	18"	8 3/4"
4'	23.40	37	42.90	42			
5'	24.30	40	44.10	45			
6'	25.20	47	45.30	52			

Non-freezing valve, removable for repair without digging up connections. Valve construction assures long life.

FIG. Z-1481 COMPRESSION VALVE DRY PIPE HYDRANT, Semi-Covered Casing

Depth H	3/4"	Approx. Wt. Lbs.	1"	Approx. Wt. Lbs.	Pipe Size A	D	E
2'	\$19.50	28	\$31.90	33	3/4"	18"	7"
3'	20.40	31	33.10	36	1"	18"	7 1/4"
4'	21.30	34	34.30	39			
5'	22.20	37	35.50	42			
6'	23.10	45	36.70	50			

Non-freezing valve, removable for repair without digging up connections. Valve construction assures long life.




Z-1481

FIG. Z-1482 COMPRESSION VALVE DRY PIPE HYDRANT, Exposed Casing


Depth H	3/4"	Approx. Wt. Lbs.	1"	Approx. Wt. Lbs.	1 1/4"	Approx. Wt. Lbs.	1 1/2"	Approx. Wt. Lbs.
2'	\$15.00	17	\$26.60	22	\$51.00	25	\$63.40	26
3'	15.90	21	27.80	26	52.60	29	65.30	30
4'	16.80	25	29.00	30	54.20	33	67.20	34
5'	17.70	28	30.20	33	55.80	36	69.10	37
6'	18.60	32	31.40	37	57.40	40	71.00	41

Pipe Size A	D	E
3/4"	18"	7"
1"	18"	7 1/4"
1 1/4"	18"	7 3/4"
1 1/2"	18"	7 7/8"

Non-freezing valve, removable for repair without digging up connections. Valve construction assures long life.



Z-1482




Z-1483—I.P.S. Inlet,
Hose Connection

COMPRESSION VALVE HYDRANT

FIG. Z-1483

Depth	Heavy Duty				Pipe Size		E	H
	1 1/2"	Approx. Wt. Lbs.	2"	Approx. Wt. Lbs.	A	D		
2'	\$70.50	38	\$110.10	57	1 1/2"	18"	6 1/2"	as spec.
3'	73.90	42	116.50	62	2"	18"	7 1/2"	as spec.
4'	77.30	46	122.90	67				
5'	80.70	50	129.30	72				
6'	84.10	54	135.70	77				
8'	87.50	58	142.10	82				
10'	90.90	62	148.50	87				

Non-freezing valve, removable for repair without digging up connections. Valve construction assures long life.



I.P.S. Inlet, Hose Connection

Z-1490

COMPRESSION VALVE DRY PIPE STREET WASHER, Round Head

FIG. Z-1490

Depth	Pipe Size			A	B	D	H
	3/4"	1"	1 1/4"				
2'	\$15.00	\$26.60	\$51.00	3/4"	4 5/8"	2 1/8"	as spec.
3'	15.90	27.80	52.60	1 1/4"	7 1/2"	2 3/8"	as spec.
4'	16.80	29.00	54.20				
5'	17.70	30.20	55.80				
6'	18.60	31.40	57.40				

I. P. 3/4" Approx. Wt. Lbs. 2'—12, 3'—16, 4'—20, 5'—24, 6'—28.

I. P. 1" Approx. Wt. Lbs. 2'—15, 3'—19, 4'—23, 5'—27, 6'—31.

I. P. 1 1/4" Approx. Wt. Lbs. 2'—16, 3'—20, 4'—24, 5'—28, 6'—32.

Non-freezing valve, removable for repair without digging up connections. Valve construction assures long life.

FIG. Z-1491 COMPRESSION VALVE DRY PIPE STREET WASHER, Square Head

Depth	Pipe Size			A	B	B'	D	H
	3/4"	1"	1 1/4"					
2'	\$15.00	\$26.60	\$51.00	3/4"	5 1/2"	4 11/16"	2 1/2"	as spec.
3'	15.90	27.80	52.60	1 1/4"		on request		
4'	16.80	29.00	54.20					
5'	17.70	30.20	55.80					
6'	18.60	31.40	57.40					

I. P. 3/4" Approx. Wt. Lbs. 2'—12, 3'—16, 4'—20, 5'—24, 6'—28.

I. P. 1" Approx. Wt. Lbs. 2'—15, 3'—19, 4'—23, 5'—27, 6'—31.

I. P. 1 1/4" Approx. Wt. Lbs. 2'—16, 3'—20, 4'—24, 5'—28, 6'—32.

Non-freezing valve, removable for repair without digging up connections. Valve construction assures long life.






FIG. Z-1492 COMPRESSION VALVE STREET WASHER

Depth	Heavy Duty		Approx. Wt. Lbs.	Pipe Size	A	D	E	H
	1 1/2"	2"						
2'	\$70.50	\$110.10	23	1 1/2"	1 1/8"	1 5/32"	as spec.	
3'	73.90	116.50	26	2"	1 1/4"	1 5/16"	as spec.	
4'	77.30	122.90	29					
5'	80.70	129.30	32					
6'	84.10	135.70	35					
8'	87.50	142.10	38					
10'	90.90	148.50	41					

Non-freezing valve, removable for repair without digging up connections. Valve construction assures long life.






Z-1493—I.P.S. Inlet,
Hose Connection

HOSE BOX—SHORT PATTERN STREET WASHER, Square Head FIG. Z-1493

Pipe Size	A	B	B'	D	H	$\frac{3}{4}$ "	1"	Approx. Wt. Lbs.
$\frac{3}{4}$ -1"		$5\frac{1}{2}$ "	$4\frac{11}{16}$ "	$2\frac{1}{2}$ "	$6\frac{3}{16}$ "	\$12.00	\$16.00	7
Add for locking device						2.50	2.50	

Non-freezing valve, removable for repair without digging up connections.
Valve construction assures long life.



Z-1494—I.P.S. Inlet,
Hose Connection

HOSE BOX—SHORT PATTERN STREET WASHER, Round Head FIG. Z-1494


Pipe Size	A	B	D	H	$\frac{3}{4}$ "	1"	Approx. Wt. Lbs.
$\frac{3}{4}$ -1"		$4\frac{5}{8}$ "	$2\frac{1}{8}$ "	$5\frac{11}{16}$ "	\$12.00	\$16.00	6
Add for locking device					2.50	2.50	

Non-freezing valve, removable for repair without digging up connections.
Valve construction assures long life.


ZURN V-E-L CLOSET CONNECTIONS

V-E-L MEANS VITAL ELEMENT LEAD—A LEAD PIPE VITAL SECTION ON A CAST IRON CONNECTION

The test specimen illustrated below consisting of a piece of eight pound lead pipe and a wiped and caulked joint exactly as employed in the Zurn V-E-L Closet Connection was tested by the Case School of Applied Science, to compare the strength of the lead pipe to the strength of the wiped and caulked joint. The pipe failed at a pulling load of 2650 pounds with no deformation or effect on the joint. Thus the results of the test made for determining the ultimate strength of the joint indicate that this joint, in addition to being simpler and more economical to make, is approximately three times as strong as the lead pipe which it joins to the connection.



Z-2036—V-E-L Closet Connection



Test Specimen
(See Above)





Flexible lead inlet on cast iron section makes closet connection permanently gas-tight and water-tight. Brass ferrule extending up into lead pipe prevents molten solder from running over. Inner portion of the hub extending above the outer portion prevents molten lead from overflowing inside. Flattened top of horizontal section maintains full drainage area of pipe while securing maximum lead pipe inlet for flexibility against shrinkage of joist or settlement of building.

FIG. Z-2036 V-E-L CLOSET BEND, Plain

Pipe Size	Length	Coated (DC)	Approx. Wt. Lbs.
3"	16"	\$8.10	15
4"	16"	8.10	17

FIG. Z-2046 V-E-L CLOSET BEND, Two 45° Tappings

Pipe Size	I. P. S. Tap	L	Coated (DC)	Approx. Wt. Lbs.
B	A			
3"	1 1/2"	16"	\$9.30	22
4"	1 1/2"	16"	9.30	26



Z-2046—Lead Pipe Inlet,
Soil Pipe Outlet



ZURN

OFFERS YOU THE FAMOUS DRAININDICATOR

The Circular Slide Rule to Determine Proper and Economical Pipe Sizing for Sanitary Drainage, Ordinary Surface or Storm Water Drainage, or any of these conditions combined, Saves Hours Figuring Out Building Drainage Specifications

ANOTHER EXAMPLE OF ZURN SPECIALIZED ENGINEERING SERVICE
FOR ARCHITECTS AND ENGINEERS

12 Instant Answers to Building Drainage Specification Problems provided for the 8 major types of buildings by the Zurn Drainindicator.

1. Pipe Sizing Scale.

2. Fixture Unit Scale for determining sanitary drainage pipe sizes.

4. Roof Area Scale for determining storm drainage pipe sizes.

THIS unique pipe sizing and drainage specification chart is even easier to use than a slide rule! You don't use it to make calculations, you just set up the project on it and turn the dial to get the answers! There are no chances for errors—the calculations have been worked out by experts and thoroughly checked. No rough estimates are necessary—the pipe specifications are reduced to exact sizes for every condition and type of building.

6. Shows recommended types of Roof Drains and catalog figure numbers.

7. Shows recommended types of Floor Drains and catalog figure numbers.

8. Shows recommended types of Area Drains and catalog figure numbers.

3. Fixture Unit Table for quickly determining proper drainage pipe sizes.


12. Maximum Rainfall in inches per hour in 30 major U. S. cities, embracing entire range of varying climatic conditions.

5. Shows type, application, and capacity of recommended Zurn Greaseceptor on basis of GPM, pieces washed per hour and meals served per day.

9. Shows recommended types of Shower Drains and catalog figure numbers.

10. Shows recommended types of Miscellaneous Fixtures and Fittings and catalog figure numbers.

11. Shows recommended types of Toilet Room Drains and catalog figure numbers.



SEND FOR YOUR DRAININDICATOR TODAY...

A COMPLIMENTARY COPY FREE
EXTRA COPIES, \$1.00 EACH

SEND FOR YOUR COPY OF THIS CATALOG



The Zurn Carrier Catalog No. 50 is the only complete and authoritative source of information for the support of wall type plumbing fixtures. Full product information is given as well as dimensional data, installation diagrams, sample specifications for easy specification writing and full of interesting illustrations.



J. A. ZURN MFG. CO., PLUMBING DIVISION, ERIE, PA., U.S.A.



J. A. ZURN MFG. CO., ERIE, PA., U. S. A.

General Terms and Conditions of Sale

TERMS—Net 30 days. Interest chargeable at 6% on unpaid accounts after 30 days from date of shipment. On shipments of \$10.00 or less, a service charge of 20% will be made with a minimum charge of \$1.00. Minimum invoice charge \$2.00.

Any terms and conditions appearing on your orders which are inconsistent with terms of our quotations and conditions of sale shall be of no effect.

SHIPPING WEIGHTS when shown are estimates only and are not guaranteed.

FREIGHT ALLOWANCE—F.O.B. Erie with actual rail freight allowed up to \$1.00 per cwt. on shipments of 500 lbs. or more. Specific routing instructions where rates are in excess of rail rates, will be charged at the difference between such rates.

PRICES—List prices shown herein supersede all previous list prices issued. All prices subject to change without notice. All other list prices and/or quotations are hereby withdrawn.

List prices herein are stated to provide a convenient price rating for, and appropriate price relationship between, products described in order conveniently to permit resale at prices fixed by our vendees.

The possession of this price list by any person is not to be construed as an offer to sell him, nor anyone else, the goods listed at the prices and terms stated.

TAXES—All taxes imposed under any existing or future statutes may be added to the price herewith effective and shall be paid by the buyer.

SHIPPING DATES—Promise of shipping dates are estimates, but not guaranteed.

All orders are accepted with the understanding that deliveries may be deferred and that it may be necessary to invoice at prices in effect on the date of shipment.

CANCELLATIONS—Cancellations or change in specifications of special material can only be honored by written notice with the understanding that any charges incurred will be chargeable to purchaser.

RETURNED GOODS—No material is to be returned without our written permission and then only on the basis of a 15% handling charge, and transportation charges prepaid, in addition to any charge that may be necessary for reconditioning to make material salable. This applies to regular standard cataloged material; any other will only be acceptable for return on credit basis of scrap metal price as determined by us. Return of any material without our written permission will eliminate any credit except that determined by us. Any returned material will be credited only on basis of purchase or current price, whichever is lower at time, all on basis of foregoing provisions.

GUARANTEE—All products are guaranteed against defective material or poor workmanship, and will be replaced free of charge upon return to factory with transportation charges prepaid. No allowance for labor or damage shall be honored. Claims for errors must be made within five (5) days after receipt of goods.




SALES OFFICES IN PRINCIPAL CITIES

Albany, N. Y.
Albuquerque, N. M.
Baltimore, Md.
Birmingham, Ala.
Boston, Mass.
Buffalo, N. Y.
Charlotte, N. C.
Chicago, Ill.
Cincinnati, Ohio


Cleveland, Ohio
Dallas, Texas
Dayton, Ohio
Denver, Col.
Des Moines, Iowa
Detroit, Mich.
Houston, Tex.
Knoxville, Tenn.
Los Angeles, Calif.
Memphis, Tenn.

Milwaukee, Wis.
Minneapolis, Minn.
Montreal, Canada
Nashville, Tenn.
Newark, N. J.
New Orleans, La.
New York, N. Y.
Philadelphia, Pa.
Pittsburgh, Pa.
Portland, Ore.

Richmond, Va.
Salt Lake City, Utah
San Francisco, Calif.
Santurce, P. R.
Seattle, Wash.
Syracuse, N. Y.
Tampa, Fla.
Tucson, Ariz.
Washington, D. C.



J. A. ZURN MFG. CO.
16TH STREET PLANT
ERIE, PA., U.S.A.



J. A. ZURN MFG. CO.
PITTSBURGH AVE. PLANT
ERIE, PA., U.S.A.

OUR ENGINEERING DEPARTMENT
IS AT YOUR DISPOSAL CONCERNING ANY
BUILDING-PLUMBING-DRAINAGE PROBLEM

J. A. ZURN MFG. CO., ERIE, PA., U. S. A.

BUILDING • PLUMBING • DRAINAGE • PRODUCTS ... ROOF TO BASEMENT

2052 St Catherine W.